



青岛启航轮胎有限公司
QINGDAO QIHANG TYRE CO., LTD.



2015-2016

农业轮胎

AGRICULTURAL TIRE

AGRICULTURAL TIRES R-1



规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG	
4.00-12	TT	4PR	R-1	535	112	3.00D	240	280
5.00-12	TT	6PR	R-1	590	145	4.00E	200	280
6.00-12	TT	6PR	R-1	635	152	4.50E	250	405
6.00-14	TT	8PR	R-1	690	165	4.50E	250	600
6.00-16	TT	8PR	R-1	690	165	4.50E	250	495
6.50-16	TT	8PR	R-1	765	180	4.50E	250	565
7.50-16	TT	8PR	R-1	810	205	5.50F	210	650
7.50-20	TT	8PR	R-1	910	205	5.50F	240	760
8.3-16	TT	6PR	R-1	790	211	W7	230	695
8.3-20	TT	10PR	R-1	788	211	W7	240	695
8.3-24	TT	6PR	R-1	993	211	W7	240	810
9.5-20	TT	8PR	R-1	950	240	W8	210	955
9.5-24	TT	6PR	R-1	1,048	241	W8	210	940
11.2-24	TT	8PR	QH613	1,103	284	W10	250	1,150
11.2-24	TL	8PR	QH613	1,103	284	W10	250	1,150
11.2-28	TT	6PR	QH615	1,205	284	W10	180	1,000
11.2-28	TT	8PR	QH615	1,205	284	W10	250	1,180
11.2-38	TT	6PR	QH616	1,459	284	W10	180	1,150
11.2-38	TL	8PR	QH616	1,459	284	W10	250	1,320
12.4-24	TT	8PR	QH611/QH666	1,159	315	W11	220	1,285
12.4-24	TT	12PR	QH611/QH666	1,159	315	W11	330	1,600
12.4-28	TT	8PR	QH615	1,260	315	W11	170	1,400
12.4-28	TT	12PR	QH615	1,260	315	W11	330	1,650
12.4-36	TT	8PR	QH666	1,464	315	W11	220	1,500
12.4-36	TT	12PR	QH666	1,464	315	W11	330	1,850
12.4-38	TT	8PR	QH611	1,514	315	W11	220	1,600
12.4-38	TT	12PR	QH611	1,514	315	W11	320	1,850
13.6-24	TT	8PR	QH611	1,210	345	W12	190	1,400
13.6-24	TT	12PR	QH611	1,210	345	W12	260	1,600
13.6-28	TT	8PR	QH611	1,311	345	W12	210	1,645
13.6-28	TT	12PR	QH611	1,311	345	W12	250	1,900
13.6-38	TT	8PR	QH611	1,565	345	W12	210	1,750
13.6-38	TT	12PR	QH611	1,565	345	W12	260	2,000
14.9-24	TT	8PR	QH611/QH666	1,265	378	W13	180	1,600



QH611



QH612



QH613

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG	
14.9-24	TT	12PR	QH611/QH666	1,265	378	W13	260	2,000
14.9-24	TL	8PR	QH611/QH666	1,265	378	W13	180	1,600
14.9-26	TT	8PR	QH611	1,316	378	W13	190	1,950
14.9-26	TT	12PR	QH611	1,316	378	W13	260	2,060
14.9-28	TT	8PR	QH612	1,367	378	W13	180	1,700
14.9-28	TT	12PR	QH612	1,367	378	W13	250	1,950
15.5-38	TT	10PR	QH611/QH666	1,569	394	W14L	220	2,000
15.5-38	TT	12PR	QH611/QH666	1,569	394	W14L	260	2,120
16.9-24	TT	10PR	QH611	1,333	429	W15L	170	1,850
16.9-24	TT	12PR	QH611	1,333	429	W15L	230	2,120
16.9-28	TT	10PR	QH611	1,435	429	W15L	190	2,120
16.9-28	TT	12PR	QH611	1,435	429	W15L	230	2,360
16.9-30	TT	10PR	QH611	1,485	429	W15L	190	2,240
16.9-30	TT	12PR	QH611	1,485	429	W15L	230	2,500
16.9-34	TT	10PR	QH611	1,587	429	W15L	190	2,360
16.9-34	TT	12PR	QH611	1,587	429	W15L	230	2,575
18.4-26	TT	12PR	QH611/QH666	1,450	467	DW16	220	2,650
18.4-26	TT	14PR	QH611/QH666	1,450	467	DW16	250	2,800
18.4-30	TT	10PR	QH611/QH666	1,552	467	W16L	180	2,500
18.4-30	TT	12PR	QH611/QH666	1,552	467	W16L	220	2,900
18.4-34	TT	10PR	QH611/QH666	1,654	467	W16L	180	2,725
18.4-34	TT	12PR	QH611/QH666	1,654	467	W16L	220	3,000
18.4-38	TT	10PR	QH611/QH666	1,755	467	W16L	180	2,900
18.4-38	TT	12PR	QH611/QH666	1,755	467	W16L	220	3,250
18.4-42	TT	10PR	QH666	1,857	467	W16L	180	3,000
18.4-42	TT	12PR	QH666	1,857	467	W16L	220	3,350
20.8-38	TT	10PR	QH611	1,834	528	W18L	150	3,150
20.8-38	TT	12PR	QH611	1,834	528	W18L	190	3,550
23.1-26	TT	12PR	QH611	1,605	587	DW20	170	3,250
23.1-26	TT	16PR	QH611	1,605	587	DW20	220	3,750
23.1-30	TT	12PR	QH611	1,707	587	DW20	170	3,450
23.1-30	TT	16PR	QH611	1,707	587	DW20	225	4,000
24.5-32	TT	12PR	QH666	1,803	622	DW21A	170	4,000
24.5-32	TT	16PR	QH666	1,803	622	DW21A	210	4,500

IRRIGATION TIRES R-1

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG	
11.2-38	TT	6PR	QH616	1,420	260	W10	180	1,150
11.2-38	TL	6PR	QH616	1,420	260	W10	180	1,150
14.9-24	TT	6PR	QH616	1,265	378	W13	140	1,360
14.9-24	TL	6PR	QH616	1,265	378	W13	140	1,360



QH615



QH666



QH616

AGRICULTURAL TIRES R-2

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
14.9-24 TT	8PR	QH651	1305	378	W13	180	1600
14.9-28 TT	8PR	QH651	1406	378	W13	180	1700
18.4-30 TT	10PR	QH651	1550	467	W16L	180	2500
18.4-34 TT	10PR	QH651	1655	467	W16L	180	2725
18.4-38 TT	10PR	QH651	1755	467	W16L	180	2900
23.1-26 TT	12PR	QH651	1605	587	DW20	170	3250
23.1-26 TT	16PR	QH651	1605	587	DW20	220	3750
23.1-30 TT	12PR	QH651	1829	610	DW20	170	3450
23.1-30 TT	16PR	QH651	1829	610	DW20	225	4000



QH651

PADDY TIRES

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
6.50-16 TT	6PR	PR-1	813	165	5.00F	250	565
7.50-16 TT	8PR	PR-1	889	203	5.50F	210	650
8.3-20 TT	8PR	PR-1	940	203	W7	270	970
8.3-24 TT	8PR	PR-1	1,041	180	W7	270	1,135
9.5-24 TT	8PR	PR-1	1,143	230	W8	310	1,420
11.2-24 TT	8PR	PR-1	1,194	280	W10	210	1,465
11-32 TT	10PR	PR-1	1,448	305	W10	160	1,080
12.4-28 TT	8PR	PR-1	1,320	305	W11	200	1,785
13.6-38 TT	10PR	PR-1	1,700	330	W12	250	2,780
16.9-34 TT	10PR	PR-1	1,651	406	W15L	220	3,385



FLOATATION TIRES I-3

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
400/60-15.5 TL	14PR	QH643	874	400	13	360	2,900
550/45-22.5 TL	16PR	QH643	1,067	533	16	280	4,375
600/50-22.5 TL	16PR	QH643	1,170	610	20	260	5,150
600/50-22.5 TL	18PR	QH643	1,170	610	20	290	5,600



QH643

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
15.5/65-18 TL	10PR	F102	915	395	W13	350	2300
18.0-15.5 TL	10PR	F101	980	450	13.00	350	4185



F101



F102

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
26 × 12-12 TL	8PR	I-3	648	307	10.50I	140	810
31 × 15.5-15 TL	8PR	I-3	792	391	13.00	310	1250



I-3

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
405/70-20 TL	14PR	M880	1076	407	13.00	350	3250
405/70-24 TL	14PR	M880	1178	407	13.00	350	3550



M880

FORESTRY TIRES

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
28L-26-16 TL	16PR	LS-2	1,620	715	DW25	210	4750
30.5L-32-18 TL	18PR	LS-2	1,845	715	DH27	210	5950



LS-2

INDUSTRIAL TRACTOR F-3

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
11L-15 TL	10PR	QH631	813	279	8LB	360	1060
11L-16 TL	12PR	QH631	838	279	8LB	440	1250
11L-16 TL	12PR	QH632	838	279	8LB	440	1250
11L-16 TL	12PR	QH633	838	279	8LB	440	1250



QH631



QH632



QH633

FARM TIRES F-2

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
4.00-12 TT/TL	4PR	QH621	535	110	3.00D	340	250
4.00-19 TT/TL	4PR	QH621	720	110	3.00D	360	325
5.00-15 TT/TL	4PR	QH621	665	140	4J	300	325
5.00-16 TT/TL	6PR	QH621	665	150	4.00E	390	475
5.50-16 TT/TL	8PR	QH621	710	150	4.00E	370	530
6.00-16 TT/TL	8PR	QH621	740	160	4.00E	450	675
6.50-16 TT/TL	8PR	QH621	750	175	4.50E	420	735
7.5L-15 TT/TL	8PR	QH621	745	208	6LB	330	750
7.50-16 TT/TL	8PR	QH621	810	205	5.50F	390	775
7.50-18 TT/TL	8PR	QH621	860	205	5.50F	390	850
7.50-20 TT/TL	8PR	QH621	910	205	5.50F	370	1,020
9.5L-15 TT/TL	8PR	QH621	780	240	8LB	330	850
11L-15 TT/TL	8PR	QH621	810	280	8LB	300	950
9.00-16 3RIB TT/TL	8PR	QH621	890	245	W7L	400	1,200
10.00-16 3RIB/4RIB TT/TL	10PR	QH621/QH622	910	275	W8L	360	1,120
11.00-16 3RIB/4RIB TT/TL	10PR	QH621/QH622	970	315	W10L	330	1,320



QH621



QH622

IMPLEMENT TIRES

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
6.50-16 TT	10PR	QH671	760	165	4.50E	410	1010
7.00-16 TT	12PR	QH672	790	176	5.50	410	1335



QH671



QH672

IMPLEMENT & TRAILER TIRES IMP700

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
10.8/80-12 TL	8PR	IMP700	710	264	9.0	390	1250
10.0/75-15.3 TL	10PR	IMP700	760	264	9.0	390	1525
11.5/80-15.3 TL	12PR	IMP700	865	290	9.0	410	2145
12.5/80-15.3 TL	14PR	IMP700	875	307	9.0	510	2810
13.0/65-18 TL	14PR	IMP700	890	336	11.0	430	2575
11L-16 TL	12PR	IMP700	33	15	8LB	400	1250



IMP700

IMPLEMENT TIRES I-1

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
6.50-16 TT/TL	10PR	QH641	735	173.0	4.50E	410	920
7.50-16 TT/TL	10PR	QH641	788	211.0	5.50F	410	1215
9.00-16 TT/TL	10PR	QH641	848	234.0	6LB	360	1500
10.5/80-18 TT/TL	12PR	QH641	885	276.0	9.0	410	1550
760L-15 TT/TL	8PR	QH641	734	193	6LB	360	950
9.5L-14 TT/TL	8PR	QH641	741	241	7LB	300	1,090
9.5L-15 TT/TL	8PR	QH641	780	240	8LB	300	1,120
11L-14 TT/TL	8PR	QH641	750	280	8LB	250	1,120
11L-15 TT/TL	8PR	QH641	810	280	8LB	250	1,150
11L-15 TT/TL	12PR	QH641	810	280	8LB	360	1,450
11L-16 TT/TL	8PR	QH641	835	280	8LB	250	1,215
12.5L-15 TT/TL	12PR	QH641	823	318	10LB	360	1,750



QH641



工业轮胎

INDUSTRIAL TIRE



SKS-1

SKS-2

SKS-3

SKS-4

SKID STEER

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
10-16.5 TL	10PR	SKS-1	779	261	8.25	520	2135
12-16.5 TL	12PR	SKS-1	830	312	9.75	550	2865
14-17.5 TL	14PR	SKS-1	922	351	10.50	550	3875
15-19.5 TL	14PR	SKS-1	1029	391	11.75	485	4565
11L-16 TL	12PR	SKS-1	838	279	8.00	440	1250
10.7/75-15.3 TL	12PR	SKS-1	760	264	9.00	410	1600
10-16.5 TL	12PR	SKS-2	795	264	8.25	620	2375
12-16.5 TL	14PR	SKS-2	835	307	9.75	620	3075
10-16.5 TL	12PR	SKS-3	773	264	8.25	620	2375
12-16.5 TL	14PR	SKS-3	831	307	9.75	620	3075
10-16.5 TL	12PR	SKS-4	820	264	8.25	620	2375
12-16.5 TL	14PR	SKS-4	831	325	9.75	620	3075
10-16.5 TL	10PR	SKS-5	775	264	8.25	520	2135
12-16.5 TL	12PR	SKS-5	831	320	9.75	550	2865
23*8.5-12 TL	6PR	SKS-5	574	213	7.00I	340	820
27*8.5-15 TL	6PR	SKS-5	678	213	7JA	340	1030
27*10.5-15 TL	6PR	SKS-5	691	259	8.50	340	1080
10-16.5 TL	12PR	SKS-6	795	264	8.25	620	2375
12-16.5 TL	14PR	SKS-6	585	416	7.00I	620	3075
10-16.5 TL	12PR	SKS-7	773	264	8.25	620	2375
12-16.5 TL	14PR	SKS-7	835	307	9.75	620	3075
10-16.5 TL	10PR	SKS-8	779	261	8.25	520	2135
12-16.5 TL	12PR	SKS-8	830	312	9.75	550	2865



SKS-5



SKS-6



SKS-7



SKS-8

INDUSTRIAL TRACTORS TIRES R-4

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
10.0/75-15.3 TL	10PR	QH602	760	264	9.0	390	1525
11.5/80-15.3 TL	12PR	QH602	865	290	9.0	410	2145
15.5/80-24 TL	12PR	QH602	1280	378	W13	300	2900
15.5/80-24 TL	16PR	QH602	1280	378	W13	400	3300



QH602

ALL TRACTION UTILITY TIRES I-3/R-4

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
10.5/80-18 TL	10PR	QH603	912	274	9.0	370	1935
12.5/80-18 TL	12PR	QH603	1001	350	9.0	370	2625
12.5/80-18 TL	12PR	QH604	1001	350	9.0	370	2625



QH603



QH604

INDUSTRIAL TRACTORS TIRES R-4

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
16.9-24 TL	12PR	QH601	1236	429	DW15	260	3250
16.9-28 TL	12PR	QH601	1435	430	DW15	260	3450
18.4-26 TL	12PR	QH601	1426	467	DW16A	250	3875
18.4-26 TL	16PR	QH601	1426	467	DW16A	300	4000
17.5L-24 TL	12PR	QH601	1241	445	DW15L	260	3000
19.5L-24 TL	12PR	QH601	1314	495	DW17L	230	3450
21L-24 TL	12PR	QH601	1402	533	DW18A	220	3875



QH601

INDUSTRIAL TRACTORS TIRES

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
19.5L-24 TL	12PR	QH608	1314	495	DW17L	230	3455
19.5L-24 TL	12PR	QH609	1314	495	DW17L	230	3455



QH608



QH609

Excavator Tires

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
8.25-20 TTF	14PR	QH107	992	245	6.50	675	2060
9.00-20 TTF	14PR	QH107	1030	260	7.00	700	3000
10.00-20 TTF	16PR	QH107	1062	280	7.00	810	3000



QH107

Fork Lift Tires

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
4.00-8 TTF	8PR	QH201	422	108	2.50C	960	690
5.00-8 TTF	10PR	QH201	469	131	3.00D	1000	1290
6.00-9 TTF	10PR	QH201	540	160	4.00E	860	1680
6.50-10 TTF	12PR	QH201	590	178	5.00F	970	2170
7.00-9 TTF	10PR	QH201	590	190	5.00S	850	1865
7.00-12 TTF	12PR	QH201	676	192	5.00S	860	2720
7.00-15(29x8-15) TTF	12PR	QH201	760	199	5.50	860	3150
7.50-15 TTF	12PR	QH201	798	215	6.00G	790	3490
8.15-15(28x9-15) TTF	14PR	QH201	684	221	7.00BD	930	4255
8.25-12 TTF	12PR	QH201	728	210	5.00S	695	2000
8.25-15 TTF	14PR	QH201	834	236	6.50	720	3935
10.00-20 TTF	16PR	QH202	1055	278	7.50	790	6765
12.00-20 TTF	20PR	QH202	1125	315	8.50	965	8970



QH201



QH202

工程轮胎

OFF THE ROAD TIRE



OTR GRADERS TIRES G-2/L-2

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
13.00-24	TL 12PR	QH808	1280	330.0	8.00TQ	300	2725
13.00-24	TL 16PR	QH808	1280	330.0	8.00TQ	325	3075
14.00-24	TL 12PR	QH808	1350	360.0	8.00TQ	250	3075
14.00-24	TL 16PR	QH808	1350	360.0	8.00TQ	350	3650
15.5-25	TL 12PR	QH808	1275	395.0	12.00/13	250	2650
17.5-25	TL 12PR	QH808	1350	445.0	14.00/1.5	200	2900
17.5-25	TL 16PR	QH808	1350	445.0	14.00/1.5	280	3350
17.5-25	TL 20PR	QH808	1350	445.0	14.00/1.5	305	3650
20.5-25	TL 16PR	QH808	1490	520.0	17.00/2.0	225	4000
23.5-25	TL 16PR	QH808	1615	595.0	19.00/2.5	200	4750



QH808

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
15.5-25	TL 12PR	QH807	1275	395	12.00/13	250	2650
17.5-25	TL 12PR	QH807	1350	445	14.00/1.5	200	2900
17.5-25	TL 16PR	QH807	1350	445	14.00/1.5	280	3350
17.5-25	TL 20PR	QH807	1350	445	14.00/1.5	305	3650
20.5-25	TL 16PR	QH807	1490	520	17.00/2.0	225	4000



QH807

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
14.00-24	TL 12PR	QH809	1350	360	9.00DC	250	3075
14.00-24	TL 16PR	QH809	1350	360	9.00DC	350	3650



QH809

OTR TIRES L-3/E-3

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG	
13.00-25	TL/TTF	24PR	QH811	1295	711	8.5	300	2720
14.00-24	TL/TTF	16PR	QH811	1370	375	11.00	375	4000
14.00-24	TL/TTF	24PR	QH811	1370	375	11.00	575	5150
15.5-25	TL/TTF	12PR	QH811	1275	395	12.00/1.3	250	3250
17.5-25	TL/TTF	16PR	QH811	1350	445	14.00/1.5	475	7300
20.5-25	TL/TTF	20PR	QH811	1490	520	17.00/2.0	450	9500
23.5-25	TL/TTF	20PR	QH811	1615	595	19.00/2.5	300	7300
26.5-25	TL/TTF	28PR	QH811	1743	645	22.00/3.0	350	10000
29.5-25	TL/TTF	28PR	QH811	1850	750	22.00/3.0	325	11500
16.00-24	TL/TTF	20PR	QH811	1490	430	11.25	400	5450
16.00-25	TL/TTF	24PR	QH811	1490	430	11.25	750	11500
16.00-25	TL/TTF	28PR	QH811	1490	430	11.25	875	12700
18.00-25	TL/TTF	32PR	QH811	1615	495	13.00	850	16000
16/70-20	TL	16PR	QH811	1067	635	13.00	350	2600
16/70-24	TTF	16PR	QH811	1067	635	13.00	350	2600



QH811

OTR TIRES L-3/E-3 New pattern

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG	
17.5-25	TL/TT	16PR	QH812	1350	445	14.00/1.5	300	4250
20.5-25	TL/TT	20PR	QH812	1490	520	17.00/2.0	325	6000
23.5-25	TL/TT	20PR	QH812	1615	595	19.00/2.5	300	7300
26.5-25	TL/TT	28PR	QH812	1743	645	22.00/3.0	350	10000



QH812

OTR TIRES L-5

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG	
17.5-25	TL/TT	16PR	L5	1340	420.0	14.00/1.5	475	7300
20.5-25	TL/TT	20PR	L5	1479	500.0	17.00/2.0	450	9500
23.5-25	TL/TT	20PR	L5	1588	568.0	19.00/2.5	375	10900
26.5-25	TL/TT	28PR	L5	1758	643.0	22.00/3.0	475	15500
29.5-25	TL/TT	28PR	L5	1868	718.0	25.00/3.5	425	17500



L5

PNEUMATICS SHAPED SOLID TIRE

规格 SIZE	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	单胎负荷 MAX LOADING KG						
					COUNTERBALANCED LIFT TRUCK						OTHER INDUSTRIAL 16KM/H
					10KM/H		16KM/H		25KM/H		
LOAD	ROTATION	LOAD	ROTATION	LOAD	ROTATION						
5.00-8	QH304	469.0	126.0	3.00	1210	970	1175	880	1095	820	840
6.00-9	QH304	545.0	140.0	4.00	1920	1535	1855	1390	1730	1295	1325
6.50-10	QH304	597.0	157.0	5.00	2640	2110	2545	1910	2370	1780	1820
7.00-9	QH304	578.0	170.0	5.00	2730	2015	2605	1925	2530	1790	1940
7.00-12	QH304	683.0	168.0	5.00	3015	2410	2910	2185	2710	2035	2075
7.00-15	QH303	759.0	178.0	5.50	3590	2870	3465	2600	3225	2420	2475
8.25-12	QH303	735.0	206.0	5.00	3325	2660	3215	2410	2995	2245	2295
8.25-15	QH304	847.0	205.0	6.50	4940	3950	4765	3575	4440	3330	3405
16x6-8	QH304	418.0	156.0	4.33	1500	1200	1445	1085	1345	1010	1035
18x7-8	QH304	457.0	165.0	4.33	2350	1880	2265	1700	2110	1585	1620
21x8-9	QH304	535.0	189.0	6.00	2810	2250	2715	2035	2530	1895	1940
23x9-10	QH304	600.0	195.0	6.50	3420	2735	3300	2475	3076	2305	2355
27x10-12	QH304	683.0	236.0	8.00	4465	3570	4315	3235	4020	3015	3080
28x9-15	QH304	700.0	230.0	7.00	4090	3270	3945	2960	3675	2755	2820
250-15	QH303	734.0	226.0	7.00	4675	3740	4515	3385	4250	3155	3225



QH303



QH304

PRESS ON SOLID TIRE

规格 SIZE	花纹编号 PATTERN	MM	单胎负荷 MAX LOADING KG						
			COUNTERBALANCED LIFT TRUCK						OTHER INDUSTRIAL 16KM/H
			10KM/H		16KM/H		25KM/H		
LOAD	ROTATION	LOAD	ROTATION	LOAD	ROTATION				
10-5x6 1/2	QH301	254x127x165.1	940.0	850.00	910	840	730		
14x4 1/2x8	QH301	356x114x203.2	1090.0	965.00	1040	960	960		
15 1/2x6x10	QH301/QH302	394x152x254	1735.0	1540.00	1660	1535	1335		
16x5x10 1/2	QH301/QH302	406x127x266.7	1400.0	1250.00	1340	1240	1080		
16x6x10 1/2	QH301/QH302	406x152x266.7	1780.0	1580.00	1700	1570	1370		
16 1/4x5x11 1/4	QH301/QH302	413x127x285.8	1415.0	1260.00	1350	1250	1090		
16 1/4x6x11 1/4	QH301/QH302	413x152x285.8	1780.0	1580.00	1710	1580	1370		
18x6x12 1/8	QH301/QH302	457x152x308	1950.0	1740.00	1860	1720	1500		
18x7x12 1/8	QH301/QH302	457x178x308	2370.0	2110.00	2270	2100	1820		
18x8x12 1/8	QH301/QH302	457x203x308	2790.0	2480.00	2670	2470	2150		
21x6x15	QH301/QH302	533x152x381	2280.0	2020.00	2160	2000	1740		
21x7x15	QH301/QH302	533x178x381	2670.0	2380.00	2550	2360	2050		
21x8x15	QH301/QH302	533x203x381	3110.0	2795.00	3000	2780	2420		
22x12x16	QH302	599x305x406.4	5235.0	4660.00	5000	4630	4030		
22x9x16	QH301/QH302	559x229x406.4	3750.0	3340.00	3590	3320	2890		
9x5x5	QH301	229x127x127	890.0	790.00	850	785	680		



QH301



QH302