

















































	ROAD	LONG®IONAL HAUL	MIXED SERVICE	OFF ROAD
POSITION				
		 HS101  HS109  HS201  HS206	 HS166  HS203  HS208  HS209	 HS715K  HS735+  HS918  HS928
ALL POSITION		 HS207  HS216  HS217  HS219	 HS218  HS218K  HS268  HS716  HS718	 HS938+  HS958+  HS968+
 		 HS259	 HS303	
STEER/TRAILER				
		 HS103  HS107  HS202	 HS102  HS108  HS18  HS228	 HS715K  HS725  HS735+
DRIVE				 HS755+  HS801Q  HS918+  HS978
		 HS106  HS205	 HS102	
TRAILER				



Pattern characteristic:
Specially recipe design provides tear resistance, high wear resistance, and excellent load capacity, Low rolling resistance & noise emission, excellent heat radiation, guiding stability. Excellent fuel efficiency.
Suitable conditions:
Suitable for steer or all wheel position of bus and truck running on high-grade road.

HS101



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
11R22.5-16	16	146/143M	M	HS101	8.25	1050	3000	2725	830	279
12R22.5-18	18	152/149M	M	HS101	9.00	1084	3550	3250	930	300
295/80R22.5-18	18	152/149M	M	HS101	9.00	1044	3550	3250	900	298
315/80R22.5-20	20	157/153L	L	HS101	9.00	1076	4125	3650	860	312



Pattern characteristic:
Low heat generating, excellent high speed driving character, good handling quality.
Suitable conditions:
Suitable for driving wheel position, Steer and trailer wheel, suitable for high way and good quality road use.

HS109



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
315/80R22.5-20	20	157/153L	L	HS109	9.00	1076	4125	3650	860	312



Pattern characteristic:
Suitable for medium/long-haul vehicles Running on high-grade road, excellent load capacity, straight shallow grooves offers an excellent drive, straight ride and anti-sidewall scuffing performance.
Suitable conditions:
Suitable for all wheel position, Running on the national highway and high way.

HS201



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
315/70R22.5-20	20	157/153L (M+S)	L	HS201	9.00	1014	3750	3350	900	312



Pattern characteristic:
High wear resistance, High cost performance.
Suitable conditions:
Suitable for all position of buses and light trucks running on Highway and roads of common grades.

HS206



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
750R16LT	14	122/118L	L	HS206	6.00G	802	1500	1320	770	210
9.5R17.5-18	18	143/141M	K	HS206	6.75	842	2725	2575	930	240



Pattern characteristic:
Suitable for highway and good quality road condition drive wheel, trailer wheel suitable for common or poor road surface, such as country road with anti-crack character, good abrasion resistance, anti-puncture character, excellent traction performance and loading character deepened & widened pattern of groove design, increase the traveled range and improve the adaptability to bad roads steering wheel, trailer wheel.
Suitable conditions:
Suitable for all position of buses and light trucks running on Highway and roads of common grades.

HS207



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
11R22.5-16	16	146/143M	M	HS207	8.25	1050	3000	2725	830	279
11R24.5-16	16	149/146L	L	HS207	8.25	1100	3250	3000	830	279



Pattern characteristic:
3 continuous ribs, and the circumferential grooves enhances superior adhesion properties of the ground, excellent wet skid resistance, special tread design, providing a low heating up, wear resistance.
Suitable conditions:
Suitable for all wheel position, running on high way and The national highway.

HS216



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R24-20	20	160/157K	K	HS216	8.50	1226	4500	4125	775	313



Pattern characteristic:
High wear resistance, High cost performance, Excellent traction performance and brake performance.
Suitable conditions:
Suitable for all position of buses and light trucks running on Highway and roads of common grades.

HS217



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
11R22.5-16	16	146/143M	M	HS217	8.25	1050	3000	2725	830	279
11R24.5-16	16	149/146L	L	HS217	8.25	1100	3250	3000	830	279



Pattern characteristic:
High wear resistance, High cost performance, Excellent anti-side-skid character and good drainage character, good handling quality.
Suitable conditions:
Suitable for all position of buses and light trucks running on Highway and roads of common grades.

HS219



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
11R22.5-14	14	144/142M	M	HS219	6.25	1050	2800	2650	720	279
11R24.5-14	14	146/143M	M	HS219	8.25	1100	3000	2725	720	279
285/75R24.5-14	14	144/141L	L	HS219	8.25	1056	2800	2575	830	283
295/75R22.5-14	14	144/141M	M	HS219	9.00	1014	2800	2575	760	298



Pattern characteristic:
4 straight groove can provide superior braking and driving performances, superior adhesion properties of the ground, excellent wet skid resistance, eccentric wear resistance.
Suitable conditions:
steer and trailer tyre, medium/long-haul vehicles, running on high-grade road.

HS259



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1100R20-18	18	152/149K	K	HS259	8.00	1082	3550	3250	930	286



Pattern characteristic:
TMS technology and special compound for smooth tread wear. Special pattern design provides good anti eccentric wear. Block tread.
Suitable conditions:
Suitable for driving wheel position of middle/long distance trucks running on good road condition.

HS103



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
11R22.5-16	16	146/143M	M	HS103	8.25	1050	3000	2725	830	279
12R22.5-18	18	152/149M	M	HS103	9.00	1084	3550	3250	930	300
295/80R22.5-18	18	152/149M	M	HS103	9.00	1044	3550	3250	900	298



Pattern characteristic:
Specially recipe design provides wear-resistance, low heat generation, Excellent traction and draining performance, more original mileage. Mix pattern supplies excellent traction performance, braking performance, supper driving and anti-wet ability.
Suitable conditions:
Stuitable for driving position, medium/long-haul vehicles, running on high-grade road.

HS107



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
12R22.5-18	18	152/149M	M	HS107	9.00	1084	3550	3250	930	300
13R22.5-18	18	154/151L	L	HS107	9.75	1124	3750	3450	850	320



Pattern characteristic:
Mixed pattern design provide strong traction and breaking power. Longer block pattern design enhance the ability of anti eccentric wear and the abnormal wear. Five deep grooves, multi blocks & tiny kerfs on the blocks assure a firm grip and a powerful tr
Suitable conditions:
Suitable for driving wheel position on good road condition.

HS202



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
295/80R22.5-18	18	152/149M	M	HS202	9.00	1044	3550	3250	900	298
315/70R22.5-20	20	157/153L (M+S)	L	HS202	9.00	1014	3750	3350	900	312



Pattern characteristic:
Excellent traction and draining performance, more original mileage.
Suitable conditions:
Trailer tyre of bus and truck, not suitable for drive and steer wheel position running on well-paved roads and mixed pavements and medium/long-haul vehicles.

HS106



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
385/65R22.5-20	20	160K	K	HS106	11.75	1072	4500	4500	900	389



Pattern characteristic:
Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, excellent fuel efficiency.
Suitable conditions:
Suitable for all wheel position, medium/long-haul vehicles, running on mixed pavements.

HS166



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
385/65R22.5-20	20	160K	K	HS166	11.75	1072	4500	4500	900	389



Pattern characteristic:
Improved tread design, high wear resistance and eccentric wear resistance. Low rolling resistance, save fuel consumption, good handling quality.
Suitable conditions:
Trailer tyre suitable for long-distance transportation, running on high-grade road.

HS205



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
11R22.5-16	16	146/143M	M	HS205	8.25	1050	3000	2725	830	279
11R24.5-16	16	149/146L	L	HS205	8.25	1100	3250	3000	830	279
285/75R24.5-16	16	147/144L(M+S)	L	HS205	8.25	1056	3075	2800	830	283
295/75R22.5-16	16	146/143L	L	HS205	9.00	1014	3000	2725	830	298
205/75R17.5-14	14	124/122M(M+S)	M	HS205	6.00	753	1600	1500	750	205
215/75R17.5-16	16	126/124M(M+S)	M	HS205	6.00	767	1700	1600	700	212
225/70R19.5-14	14	128/126M(M+S)	M	HS205	6.75	811	1800	1700	760	226
235/75R17.5-16	16	132/130M(M+S)	M	HS205	6.75	797	2000	1900	775	233
245/70R19.5-16	16	135/133M(M+S)	M	HS205						
255/70R22.5-16	16	140/137M(M+S)	M	HS205	7.50	930	2500	2300	830	255
265/70R19.5-16	16	140/138M(M+S)	M	HS205	7.50	867	2500	2360	775	262
275/70R22.5-16	16	148/145M(M+S)	M	HS205	8.25	958	3150	2900	900	276



Pattern characteristic:
Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, excellent fuel efficiency.
Suitable conditions:
Suitable for all wheel position, medium/long-haul vehicles, running on mixed pavements.

HS203



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
315/80R22.5-20	20	157/153L	L	HS203	9.00	1076	4125	3650	860	312



Pattern characteristic:
Wide tread width design provides excellent driving and gripping power. Extra deep tread provides an extra powerful traction and a long tread life. Closed shoulder maintains a good irregular wear resistance. With excellent crack and tear resistance character.
Suitable conditions:
Suitable for Light, heavy duty and bus all position on good or non-paved road.

HS208



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
11R22.5-16	16	146/143M	M	HS208	8.25	1050	3000	2725	830	279
11R24.5-16	16	149/146L	L	HS208	8.25	1100	3250	3000	830	279
285/75R24.5-16	16	147/144L(M+S)	L	HS208	8.25	1056	3075	2800	830	283
295/75R22.5-16	16	146/143L	L	HS208	9.00	1014	3000	2725	830	298



Pattern characteristic:
 Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, excellent fuel efficiency.
Suitable conditions:
 Suitable for all wheel position, medium/long-haul vehicles, running on mixed pavements.

HS209



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
385/65R22.5-20	20	160K	K	HS209	11.75	1072	4500	4500	900	389



Pattern characteristic:
 Block tread pattern provides excellent gripping and traction power. Tough belt construction for smooth wear and longer mileage. Special tread compound for high resistance against tread cut.
Suitable conditions:
 Suitable for all position of trucks running on non-paved roads.

HS218



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS218	8.50	1122	4000	3650	900	313
1100R20-18	18	152/149K	K	HS218	8.00	1082	3550	3250	930	286
1000R20-18	18	149/146K	K	HS218	7.50	1052	3250	3000	930	275
900R20-16	16	144/142K	K	HS218	7.00	1018	2800	2650	900	258



Pattern characteristic:
 Block tread pattern provides excellent gripping and traction power. Tough belt construction for smooth wear and longer mileage. Special tread compound for high resistance against tread cut.
Suitable conditions:
 Suitable for all position of trucks running on non-paved roads.

HS218K



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R24-20	20	160/157K	K	HS218K	8.50	1226	4500	4125	775	313



Pattern characteristic:
 Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, excellent fuel efficiency.
Suitable conditions:
 Suitable for all wheel position, medium/long-haul vehicles, running on mixed pavements.

HS268



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS268	8.50	1122	4000	3650	900	313
1100R20-18	18	152/149K	K	HS268	8.00	1082	3550	3250	930	286
1000R20-18	18	149/146K	K	HS268	7.50	1052	3250	3000	930	275
900R20-16	16	144/142K	K	HS268	7.00	1018	2800	2650	900	258
825R20-16	16	139/137K	K	HS268	6.50	974	2430	2300	930	236
825R16LT	16	128/124K	K	HS268	6.50H	860	1800	1600	770	230
750R16LT	14	122/118L	L	HS268	6.00G	802	1500	1320	770	210
700R16LT	14	118/114K	K	HS268	5.50F	778	1500	1320	770	202
6.50R16LT	12	110/105K	K	HS268	4.50	755	1060	925	670	182
11R22.5-16	16	146/143M	M	HS268	8.25	1050	3000	2725	830	279
12R22.5-18	18	152/149M	M	HS268	9.00	1084	3550	3250	930	300
13R22.5-18	18	154/151L	L	HS268	9.75	1124	3750	3450	850	320
315/80R22.5-20	20	157/153L	L	HS268	9.00	1076	4125	3650	860	312
1200R24-20	20	160/157K	K	HS268	8.50	1226	4500	4125	775	313



Pattern characteristic:
 Excellent load capacity and Super abrasion resistance, tear resistance, high wear resistance, suitable to vehicles on low grade road and medium/long-haul vehicles.
Suitable conditions:
 All wheel position, high-grade road.

HS716



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1100R20-18	18	152/149K	K	HS716	8.00	1082	3550	3250	930	286
12R22.5-18	18	152/149K	M	HS716	9.00	1084	3550	3250	930	300



Pattern characteristic:
Tire adopt super structure, with excellent carrying capacity, super wear-resistant and anti-puncture tread formulation, suitable for poor road condition, dedicated to the short-distance use.
Suitable conditions:
All-wheel position, Ordinary Road, bad road.

HS718



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS718	8.50	1122	4000	3650	900	313



Pattern characteristic:
Reinforced belt and body construction enhance the loading ability. Special tread compound for high resistance against tread cut.
Suitable conditions:
Suitable for driving wheel position on good road condition and non-paved roads.

HS108



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R24-20	20	160/157K(M+S)	M	HS108	8.50	1226	4500	4125	775	313



Pattern characteristic:
Four straight groove can provide excellent braking and driving performances.
Suitable conditions:
Suitable for steering wheel, trailer wheel, medium/long-haul vehicles, Running on good or common mixed pavements.

HS303



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
295/80R22.5-18	18	152/149M	M	HS303	9.00	1044	3550	3250	900	298



Pattern characteristic:
Reinforced belt and body construction enhance the loading ability. Special tread compound for high resistance against tread cut.
Suitable conditions:
Suitable for driving wheel position on good road condition and non-paved roads.

HS18



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R24-20	20	160/157K(M+S)	M	HS18	8.50	1226	4500	4125	775	313



Pattern characteristic:
Mixed pattern design provide strong traction and breaking power. Longer block pattern design enhance the ability of anti eccentric wear and the abnormal wear. Five deep grooves, multi blocks & tiny kerfs.
Suitable conditions:
Suitable for trailer and driving wheel position, no suitable for steer position of short/middle distance trucks running on good road condition.

HS102



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
315/80R22.5-20	20	157/153L	L	HS102	9.00	1076	4125	3650	860	312



Pattern characteristic:
Reinforced belt and body construction enhance the loading ability. Special tread compound for high resistance against tread cut.
Suitable conditions:
Suitable for driving wheel position on good road condition and non-paved roads.

HS228



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R24-20	20	160/157K(M+S)	K	HS228	8.50	1226	4500	4125	775	313



Pattern characteristic:
Transverse big block type and deepened pattern design, provides superior driving performance. The open type groove design has a good self-cleaning ability. In particular, the strength of reinforced carcass design, provide greater carrying capacity. In par.
Suitable conditions:
Overload, bad road short haul dump truck driving wheel or all wheel position. The construction site, mines, mud and other serious adverse road conditions.

HS715 矿山型



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS715K	8.50	1122	4000	3650	900	313
1100R20-18	18	152/149K	K	HS715K	8.00	1082	3550	3250	930	286
1000R20-18	18	149/146K	K	HS715K	7.50	1052	3250	3000	930	275
900R20-16	16	144/142K	K	HS715K	7.00	1018	2800	2650	900	258



Pattern characteristic:
Transverse big block type and deepened pattern design, provides superior driving performance. The open type groove design has a good self-cleaning ability. In particular, the strength of reinforced carcass design, provide greater carrying capacity. In par.
Suitable conditions:
Overload, bad road short haul dump truck driving wheel or all wheel position. The construction site, mines, mud and other serious adverse road conditions.

HS735+ 矿山型



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS735+	8.50	1122	4000	3650	900	313
1100R20-18	18	152/149K	K	HS735+	8.00	1082	3550	3250	930	286



Pattern characteristic:
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.
Suitable conditions:
Suitable for short mileage vehicles running on various of non-paved roads.

HS918



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS918	8.50	1122	4000	3650	900	313
1100R20-18	18	152/149K	K	HS918	8.00	1082	3550	3250	930	286
825R16LT	16	128/124K	K	HS918	6.50H	860	1800	1600	770	230
750R16LT	14	122/118L	L	HS918	6.00G	802	1500	1320	770	210
1200R24-20	20	160/157K		HS918	8.50	1226	4500	4125	775	313



Pattern characteristic:
Block tread pattern provides excellent gripping and traction power. Tough belt construction for smooth wear and longer mileage. Special tread compound for high resistance against tread cut.
Suitable conditions:
Suitable for all position of trucks running on non-paved roads.

HS928



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
9.5R17.5-18	18	143/141M	K	HS928	6.75	842	2725	2575	930	240
315/80R22.5-20	20	156/150K	L	HS928	9.00	1076	4125	3650	860	312



Pattern characteristic:
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.
Suitable conditions:
Suitable for short mileage vehicles running on various of non-paved roads.

HS938+



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS938+	8.50	1122	4000	3650	900	313
1100R20-18	18	152/149K	K	HS938+	8.00	1082	3550	3250	930	286



Pattern characteristic:
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.
Suitable conditions:
Suitable for short mileage vehicles running on various of non-paved roads.

HS958+



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS958+	8.50	1122	4000	3650	900	313
1100R20-18	18	152/149K	K	HS958+	8.00	1082	3550	3250	930	286



Pattern characteristic:
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.
Suitable conditions:
Suitable for short mileage vehicles running on various of non-paved roads.

HS968+



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS968+	8.50	1122	4000	3650	900	313
1100R20-18	18	152/149K	K	HS968+	8.00	1082	3550	3250	930	286



Pattern characteristic:
Special designed mine pattern tyre for harsh road ,with wide tyre crown and deep tread, which could provide higher mileage.The large lateral pattern block can produce the driving forces, maintaining excellent grip performance both in the dry and wet pavem.
Suitable conditions:
Truck drive tyre, use for Mining/Mountain road.

HS725 矿山型



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS725	8.50	1122	4000	3650	900	313
1100R20-18	18	152/149K	K	HS725	8.00	1082	3550	3250	930	286



Pattern characteristic:
Special designed mine pattern tyre for harsh road ,with wide tyre crown and deep tread, which could provide higher mileage.The large lateral pattern block can produce the driving forces, maintaining excellent grip performance both in the dry and wet pavem.
Suitable conditions:
Truck drive tyre, use for Mining/Mountain road.

HS755+ 矿山型



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS755+	8.50	1122	4000	3650	900	313
1100R20-18	18	152/149K	K	HS755+	8.00	1082	3550	3250	930	286



Pattern characteristic:
Unique belt structure, with high wear-resistance and low producing heat crown formulation. Has a strong grip and wet-slip resistance performance. Optimized and enhanced bead design, especially for special conditions. Radial structure of the carcass, ma.
Suitable conditions:
Truck drive tyre, suitable for low speed ride on bad or common road, such as mine road, mountain road.

HS801Q



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1200R20-20	20	156/153K	K	HS801Q	8.50	1122	4000	3650	900	313
1100R20-18	18	152/149K	K	HS801Q	8.00	1082	3550	3250	930	286
1000R20-18	18	149/146K	K	HS801Q	7.50	1052	3250	3000	930	275
13R22.5-18	18	154/151L	L	HS801Q	9.75	1124	3750	3450	850	320



Pattern characteristic:
Tough belt construction, with high wear resistance and good impact force, Reinforced bead provide good traction.
Suitable conditions:
Suitable for driving wheel position of short/middle distance trucks on good road conditions .

HS918+



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1000R20-18	18	149/146K	K	HS918+	7.50	1052	3250	3000	930	275



Pattern characteristic:
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.
Suitable conditions:
Suitable for short mileage vehicles running on various of non-paved roads.

HS978



SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)
							SINGLE	DUAL		
1000R20-18	18	149/146K	K	HS978	7.50	1052	3250	3000	930	275



5.50-13 6.00-13 6.50-14 6.00-15 6.00-16 6.50-15 7.00-15 7.00-16 7.50-15 7.50-16
7.50-20 8.25-16 8.25-20 9.00-20 10.00-20 11.00-20 12.00-20

曲线花纹

The tyres have small in rolling resistance and sideslip-preventing.They are suitable for driving in high speed and saving oil and beneficial.

HS228



5.00-16 5.50-16 6.50-15 6.50-14 6.50-16 7.00-16 7.50-16 7.50-20 8.25-16
8.25-20 9.00-16 9.00-20 10.00-20 11.00-20 12.00-20

八角花纹

The tyres are suitable for driving on sandstone road with good standing wear and high in loading ability.

HS868



14.00-24 17.5-25 20.5-25 23.5-25 16.00-25 26.5-25 16/70-20 13.00-25 18.00-25 29.5-25
16/70-24

条形花纹

For the complex,variable and harsh conditions of use,the tyres have the different feautres of wearing resistance and wearing cutted,safe and reliable.

HS668

轮胎规格 Tyre Size	层级 Ply Rating	轮辋 Rim		新胎充气外缘尺寸 Inflated Dimension		最大负荷 Max Load		相应气压 Inflation Pressure
		标准轮辋 Standard rim	允许轮辋 Permitted rim	断面宽(mm) Section Width	外直径(mm) Overall Diameter	Single Load	Dual Load	
5.00-16LT	8	3.50	3 1/2 J 4.00B	145	685	375	-	250
5.50-16LT	8	4.00	4 1/2 J	165	705	425	-	250
550-13LT	6.8	4J	4 1/2 J 5J	160	620	565	500	420
6.00-14LT	6.8		4J5J	170	680	685	600	420
6.00-15LT	6.8	4.50E	4 1/2 K	170	705	720	630	420
6.00-16LT	6.8,10	4.50E	4.00E	170	730	860	755	530
7.50-20	8,10,12,14	6.0	6.00T 6.5 6.50T	215	935	1885	1655	810
*7.50-16LT	6.8,10,12,14	5.50F	6.00G	200	775	1220	1075	630
**11.00-20	12,14,16,18	8.0	8.00V 8.5 8.5V5 8.50V	293	1085	3270	2870	810
12.00-20	16,18	8.5	8.50V 8.50V5 9.00V	315	1125	3730	3270	810
6.00-13LT	6.8		4J5J	170	655	655	570	6.8.
6.00-14LT	6.8		4J5J	170	680	685	600	420
6.00-15LT	6.8	4.50E	4 1/2 K	170	705	720	630	420
6.00-16LT	6.8,10	4.50E	4.00E	170	730	860	755	530
6.50-14LT	6.8	4 1/2 J	5J	180	705	785	690	420
6.50-15LT	6.8	4.50E	4 1/2 K 5K 5 1/2 K 5.50F	180	730	820	720	420
*6.50-16LT	6.8,10,12	5.50F	5.00E 5.50F	185	750	975	860	530
7.00-15LT	6.8,10	5.50F	6.00G	200	750	1040	915	530
*7.00-16LT	6.8,10,12,14	5.50F	6.00G	200	775	1220	1075	630
7.50-15LT	8,10,12	6.00G	5.50F 6.50H	215	780	1370	1210	630
*7.50-16LT	6.8,10,12,14	6.00G	5.50F 6.50H	215	805	1405	1240	630
*8.25-16LT	6.8,10,12,14,16	6.50H	6.00G	235	855	1705	1500	630
9.00-16LT	6.8,10,12,14	6.50H	6.00G 7.00H	255	890	1955	1720	630

轮胎规格 Tyre Size	层级 Ply Rating	轮辋 Rim		新胎充气外缘尺寸 Inflated Dimensions		最大负荷 Max Load		相应气压 Inflation Pressure
		标准轮辋 Standard rim	允许轮辋 Permitted rim	断面宽(mm) Section Width	外直径(mm) Overall Diameter	Single Load	Dual Load	
7.50-20	8,10,12,14	6.0	6.00T 6.5 6.50T	215	935	1885	1655	810
8.25-20	10,12,14,16	6.5	6.50T 7.0 7.00T 7.0T50	235	974	2205	1940	810
9.00-20	10,12,14,16	7.0	7.00T 7.0T50 7.5 6.5 7.50V	259	1018	2575	2255	770
10.00-20	12,14,16,18	7.5	7.50V 8.0 8.00V 8.0V50	278	1055	3000	2630	810
11.00-20	12,14,16,18	8.0	8.00V 8.5 8.5V50 8.50V	293	1085	3270	2870	810
12.00-20	16,18	8.5	8.50V 8.50V50 9.00V	315	1125	3730	3270	810
10.00-20	12,14,16,18	7.5	7.50V 8.0 8.00V 8.0V50	278	1055	3000	2630	810
11.00-20	12,14,16,18	8.0	8.00V 8.5 8.5V50 8.50V	293	1085	3270	2870	810
12.00-20	16,18	8.5	8.50V 8.50V50 9.00V	315	1125	3730	3270	810



23.5-25

花纹

The tyres have the features of good grasping force to ground,standing the sideslip-preventing,and the tyres are suitable for all kinds of conditions of road and climates.

HS866



23.5-25

花纹

With strong ground grip, good self-cleaning, good standing wear and high in loading ability.

HS686



6.00-13 6.00-14 6.00-15 6.50-16 7.00-16 7.50-16 8.25-16 9.00-20 10.00-20 11.00-20

矿山花纹

With strong ground grip, good self-cleaning, good standing wear and high in loading ability.

HS118

轮胎规格 Tyre Size	层级 Ply Rating	轮辋 Rim		新胎充气外缘尺寸 Inflated Dimensions		最大负荷 Max Load			相应气压 Inflation Pressure	气门嘴型号 Valve Size
		标准轮辋 Standard rim	允许轮辋 Permitted rim	断面宽(mm) Section Width	外直径(mm) Overall Diameter	65 km/h	50 km/h	15 km/h		
17.5-25	18	14.00/1.5	—	445	1398	-	-	5440	280	Z1-01-8
20.5-25	20	17.00/20	—	520	1548	4880	5900	6580	350	Z1-01-6
23.5-25	20	19.5/2.5	—	595	1673	5530	6680	7460	280	Z1-01-8
14.00-24	16/24	10.00	—	375	1370	4760/6030			420/630	Z1-01-8
16.00-25	20/28	11.25/2.0	—	430	1546	6220/7360			420/560	Z1-01-8
26.5-25	16/20	22.00/3.0	—	675	1750	11500/13200			275/350	Z1-01-8
16/70-20	10/14	13.00	—	410	1075	4200/5150			325/450	Z1-01-8
18.00-25	20/28	13.00/2.5	—	495	1615	7230/8810			350/490	Z1-01-8
29.5-25	16/22	25.00/3.5	—	750	1875	12900/15000			250/325	Z1-01-8
16/70-24	10/14	13.00	—	410	1175	4750/5650			325/4.50	Z1-01-8



5.00-8 6.00-9 6.50-10 7.00-9 7.00-12 28X9-15 8.25-12 8.25-15

叉车花纹

The drawing quality is good and the tyres are high in loading and good warmtherasing.

HS688

Industrial tyre 叉车胎 Forklift tyre	轮胎规格 Tyre Size	层级 Ply Rating	轮辋 Rim		新胎充气外缘尺寸 Inflated Dimensions		最大负荷 Max Load				相应 气压 Inflation Pressure	气门嘴型号 Valve Size
			标准轮辋 Standard rim	允许轮辋 Permitted rim	断面宽(mm) Section Width	外直径(mm) Overall Diameter	10 km/h	25 km/h	40 km/h	50 km/h		
	5.00-8	8.10	3.50D	3.00D	137	470	950	765	665	595	800	TZ1-45
	6.00-9	10	4.00E	4.50E	160	540	1410	1135	985	885	850	TZ1-45
	6.50-10	10	5.00F	5.50F	175	590	1545	1245	1080	970	775	TZ1-45
	7.00-9	10	5.00S	-	190	590	1865	1500	1300	1170	850	TZ1-45
	7.00-12	12	5.00S	5.50S	190	676	2225	1790	1505	1400	850	TZ1-45
	28X9-15	12,14,16	7.0	7.00T	222	710	3515	2705	2180	1850	900	-
	8.25-12	12	6.5	5.00S	235	765	2950	2375	2060	1855	750	TZ1-50
	8.25-15	14	6.5	6.50T	235	840	3230	2600	2255	2030	800	TZ1-50

TECHNICAL FILE

KAPSEN

SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)	M+S
							SINGLE	DUAL			
1200R20-20	20	156/153K	K	HS268	8.50	1122	4000	3650	900	313	
1200R20-20	20	156/153K	K	HS218	8.50	1122	4000	3650	900	313	
1200R20-20	20	156/153K	K	HS801Q	8.50	1122	4000	3650	900	313	
1200R20-20	20	156/153K	K	HS918	8.50	1122	4000	3650	900	313	
1200R20-20	20	156/153K	K	HS718	8.50	1122	4000	3650	900	313	
1200R20-20	20	156/153K	K	HS715K	8.50	1122	4000	3650	900	313	
1200R20-20	20	156/153K	K	HS725	8.50	1122	4000	3650	900	313	
1200R20-20	20	156/153K	K	HS735+	8.50	1122	4000	3650	900	313	
1200R20-20	20	156/153K	K	HS755+	8.50	1122	4000	3650	900	313	
1200R20-20	20	156/153K	K	HS938+	8.50	1122	4000	3650	900	313	
1200R20-20	20	156/153K	K	HS958+	8.50	1122	4000	3650	900	313	
1200R20-20	20	156/153K	K	HS968+	8.50	1122	4000	3650	900	313	
1100R20-18	18	152/149K	K	HS268	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS218	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS716	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS258	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS259	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS801Q	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS918	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS715K	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS725	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS735+	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS755+	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS938+	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS958+	8.00	1082	3550	3250	930	286	
1100R20-18	18	152/149K	K	HS968+	8.00	1082	3550	3250	930	286	
1000R20-18	18	149/146K	K	HS268	7.50	1052	3250	3000	930	275	
1000R20-18	18	149/146K	K	HS218	7.50	1052	3250	3000	930	275	
1000R20-18	18	149/146K	K	HS801Q	7.50	1052	3250	3000	930	275	
1000R20-18	18	149/146K	K	HS918+	7.50	1052	3250	3000	930	275	
1000R20-18	18	149/146K	K	HS715K	7.50	1052	3250	3000	930	275	
1000R20-18	18	149/146K	K	HS978	7.50	1052	3250	3000	930	275	
900R20-16	16	144/142K	K	HS268	7.00	1018	2800	2650	900	258	

SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)	M+S
							SINGLE	DUAL			
900R20-16	16	144/142K	K	HS218	7.00	1018	2800	2650	900	258	
900R20-16	16	144/142K	K	HS715K	7.00	1018	2800	2650	900	258	
825R20-16	16	139/137K	K	HS268	6.50	974	2430	2300	930	236	
825R16LT	16	128/124K	K	HS268	6.50H	860	1800	1600	770	230	
825R16LT	16	128/124K	K	HS918	6.50H	860	1800	1600	770	230	
750R16LT	14	122/118L	L	HS268	6.00G	802	1500	1320	770	210	
750R16LT	14	122/118L	L	HS206	6.00G	802	1500	1320	770	210	
750R16LT	14	122/118L	L	HS918	6.00G	802	1500	1320	770	210	
700R16LT	14	118/114K	K	HS268	5.50F	778	1500	1320	770	202	
650R16LT	12	110/105K	K	HS268	4.50	755	1060	925	670	182	
9.5R17.5-18	18	143/141M	K	HS206	6.75	842	2725	2575	930	240	
9.5R17.5-18	18	143/141M	K	HS928	6.75	842	2725	2575	930	240	
11R22.5-16	16	146/143M	M	HS101	8.25	1050	3000	2725	830	279	
11R22.5-16	16	146/143M	M	HS205	8.25	1050	3000	2725	830	279	
11R22.5-16	16	146/143M	M	HS268	8.25	1050	3000	2725	830	279	
11R22.5-16	16	146/143M	M	HS103	8.25	1050	3000	2725	830	279	
11R22.5-16	16	146/143M	M	HS208	8.25	1050	3000	2725	830	279	
11R22.5-16	16	146/143M	M	HS207	8.25	1050	3000	2725	830	279	
11R22.5-16	16	146/143M	M	HS217	8.25	1050	3000	2725	830	279	
11R22.5-14	14	144/142M	M	HS219	6.25	1050	2800	2650	720	279	
11R24.5-16	16	149/146L	L	HS205	8.25	1100	3250	3000	830	279	
11R24.5-16	16	149/146L	L	HS207	8.25	1100	3250	3000	830	279	
11R24.5-16	16	149/146L	L	HS217	8.25	1100	3250	3000	830	279	
11R24.5-16	16	149/146L	L	HS208	8.25	1100	3250	3000	830	279	
11R24.5-14	14	146/143M	M	HS219	8.25	1100	3000	2725	720	279	

TECHNICAL FILE

KAPSEN

SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)	M+S
							SINGLE	DUAL			
12R22.5-18	18	152/149M	M	HS101	9.00	1084	3550	3250	930	300	
12R22.5-18	18	152/149M	M	HS268	9.00	1084	3550	3250	930	300	
12R22.5-18	18	152/149M	M	HS301	9.00	1084	3550	3250	930	300	
12R22.5-18	18	152/149M	M	HS302	9.00	1084	3550	3250	930	300	
12R22.5-18	18	152/149M	M	HS107	9.00	1084	3550	3250	930	300	
12R22.5-18	18	152/149K	M	HS716	9.00	1084	3550	3250	930	300	
12R22.5-18	18	152/149M	M	HS103	9.00	1084	3550	3250	930	300	
13R22.5-18	18	154/151L	L	HS268	9.75	1124	3750	3450	850	320	
13R22.5-18	18	154/151L	L	HS107	9.75	1124	3750	3450	850	320	
13R22.5-18	18	154/151L	L	HS801Q	9.75	1124	3750	3450	850	320	
285/75R24.5-16	16	147/144L	L	HS205	8.25	1056	3075	2800	830	283	M+S
285/75R24.5-16	16	147/144L	L	HS208	8.25	1056	3075	2800	830	283	M+S
285/75R24.5-14	14	144/141L	L	HS219	8.25	1056	2800	2575	830	283	
295/75R22.5-16	16	146/143L	L	HS205	9.00	1014	3000	2725	830	298	
295/75R22.5-16	16	146/143L	L	HS208	9.00	1014	3000	2725	830	298	
295/75R22.5-14	14	144/141M	M	HS219	9.00	1014	2800	2575	760	298	
295/80R22.5-18	18	152/149M	M	HS101	9.00	1044	3550	3250	900	298	
295/80R22.5-18	18	152/149M	M	HS202	9.00	1044	3550	3250	900	298	
295/80R22.5-18	18	152/149M	M	HS303	9.00	1044	3550	3250	900	298	
295/80R22.5-18	18	152/149M	M	HS103	9.00	1044	3550	3250	900	298	
315/80R22.5-20	20	157/153L	L	HS101	9.00	1076	4125	3650	860	312	
315/80R22.5-20	20	157/153L	L	HS268	9.00	1076	4125	3650	860	312	
315/80R22.5-20	20	157/153L	L	HS109	9.00	1076	4125	3650	860	312	
315/80R22.5-20	20	156/150K	L	HS928	9.00	1076	4125	3650	860	312	
315/80R22.5-20	20	157/153L	L	HS102	9.00	1076	4125	3650	860	312	
315/80R22.5-20	20	157/153L	L	HS203	9.00	1076	4125	3650	860	312	

SIZE	PR	LI & SS	SS	PATTERN	STANDARD RIM	OUTER DIAMETER (mm)	MAX LOAD(KG)		MAX PRESSURE (KPA)	SECTION WIDTH (mm)	M+S
							SINGLE	DUAL			
385/65R22.5-20	20	160K	K	HS106	11.75	1072	4500	4500	900	389	
385/65R22.5-20	20	160K	K	HS166	11.75	1072	4500	4500	900	389	
385/65R22.5-20	20	160K	K	HS209	11.75	1072	4500	4500	900	389	
1200R24-20	20	160/157K	K	HS268	8.50	1226	4500	4125	775	313	
1200R24-20	20	160/157K	K	HS218K	8.50	1226	4500	4125	775	313	
1200R24-20	20	160/157K	K	HS216	8.50	1226	4500	4125	775	313	
1200R24-20	20	160/157K	K	HS228	8.50	1226	4500	4125	775	313	M+S
1200R24-20	20	160/157K		HS918	8.50	1226	4500	4125	775	313	
1200R24-20	20	160/157K	M	HS108	8.50	1226	4500	4125	775	313	M+S
1200R24-20	20	160/157K	M	HS18	8.50	1226	4500	4125	775	313	M+S
315/70R22.5-20	20	157/153L	L	HS201	9.00	1014	3750	3350	900	312	M+S
315/70R22.5-20	20	157/153L	L	HS202	9.00	1014	3750	3350	900	312	M+S
205/75R17.5-14	14	124/122M	M	HS205	6.00	753	1600	1500	750	205	M+S
215/75R17.5-16	16	126/124M	M	HS205	6.00	767	1700	1600	700	212	M+S
225/70R19.5-14	14	128/126M	M	HS205	6.75	811	1800	1700	760	226	M+S
235/75R17.5-16	16	132/130M	M	HS205	6.75	797	2000	1900	775	233	M+S
245/70R19.5-16	16	135/133M	M	HS205							M+S
255/70R22.5-16	16	140/137M	M	HS205	7.50	930	2500	2300	830	255	M+S
265/70R19.5-16	16	140/138M	M	HS205	7.50	867	2500	2360	775	262	M+S
275/70R22.5-16	16	148/145M	M	HS205	8.25	958	3150	2900	900	276	M+S