



CONTACTO

+1 (561) 249-2973
+1 (305) 890-5386
Fax. 305.238.7721

9020 Bellhurst Way
Suite #108
West Palm Beach, FL, 33411



CATÁLOGO LEAO PCR





LEAO TIRE



Contents

Company Profile.....01	Radial Agricultural Tire.....52
Radial Passenger Car Tire....02-20	Bias Tire.....53-59
Radial Passenger Car Tire.....02	Bias Truck / Bus Tire.....53
Light Truck Tire.....17	Solid Tire for Fork Lifts.....59
Radial Truck and Bus Tire....21-51	
Radial Truck and Bus Tire.....21	
Winter Tire.....50	

Company Profile

Shandong Linglong Tire Co., Ltd. is a large manufacturing enterprise engaging in the production of pneumatic tires. After 37 years' development, the company has grown into a tire manufacturer with the strongest research and development capability in China. Linglong has independently developed more than 3000 specifications covering light truck radial tires, truck and bus radial tires, high performance passenger radial tires and specialty tires. With a worldwide marketing network, Linglong is stepping towards the top world tire brands.

Linglong has introduced world advanced production equipment and testing apparatus. The company established a quality control system which monitors the entire production line and controls the quality of the semi-finished products in every process, thus guaranteeing the quality of the final products. The company meets and accedes various quality certifications such as Chinese CCC, American DOT Certification, American EPA SmartWay Certification, European ECE Certification, and GCC Certification of Arab countries. In 2011, Linglong was granted status of exemption from export inspection and became the first authorized company in China since the reinstatement of export inspection exemption policy by the Government.

Linglong is committed to technological development and has set up two R&D centers in Zhaoyuan and Beijing that be home to the first laboratory with national-level authentication in tire industry and the first indoor noise laboratory in China, as well as a post-doctoral research center and an academic research center. The company introduced more than 500 world advanced testing apparatus including dynamic imprint experiment machine and LMS system. In 2011, Linglong technical center was designated as national level enterprise technical center.

By virtue of the advanced equipment and a research team of more than 750 staff, the company has developed a series of leading technology in the industry and first-class products in China. The "low-aspect ratio, wet-skid resistance, low noise and ultra high performance car radial tire" won the "Second National Prize for Progress in Science and Technology". "Linglong Brand" car radial tire and "Linglong Brand" truck radial tire were recommended by China Rubber Industry Association as "Brand Products", and "Linglong Trademark" was designated as "Well-known Trademark of China".

As a corporate citizen, Linglong is committed to its social responsibilities in addition to its own development. It sponsored the first women car-racing team in China—Linglong Beauty Car Racing Team, and title-sponsored Shandong Linglong Tire Chess Team, which is the cradle for Hou Yifan, the youngest Chess Queen in history. Linglong is official sponsor for China Women's Volleyball Team, and in 2011 the program "Linglong Tire and China Women's Volleyball Team" was recommended as one of the "Top Ten Classical Cases in Sports Marketing by China Central Television".

Shandong Linglong Tire Co., Ltd. has been striving to expand market and develop market networks. It has over 10,000 domestic outlets and was recommended as an "Excellent Supplier" by Shanxi Automobile Group, Changchun First Automobile Workshop and SGMW. It sells tires in 160 countries and regions in collaboration with tire marketing tycoons, and passed the assessment for global suppliers by two of the world top six automobile manufacturers. It established Linglong tire franchised store, a platform for worldwide standardized, star-rated and one-stop marketing services.

Excellence, innovation, social responsibility and market network are the essences of the well-recommended corporate culture in addition to its quality products. The company has repeatedly been listed in "China Rubber Industry Top 50 Competitive Companies", "China Chemical Industry Top 500 Companies", "2011 China Top 500 Companies", and won the honorary title of "National Model Company for Quality, Honesty and Commitment" and "China 500 Most Valuable Brands", with a brand value of RMB 11.652 billion.

Radial Passenger Car Tire

NOVA-FORCE UHP

Ultra high performance



Size	Load index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
215/40R16XL	86	W	7 1/2J	530	290	218	578	7.8
195/45R16XL	84	V	6 1/2J	500	290	195	582	7.8
205/45R16XL	87	W	7J	545	290	206	590	7.8
205/50R16	87	W	6 1/2J	545	250	214	612	7.8
225/50R16XL	96	V	7J	710	290	233	632	7.8
205/55R16XL	94	W	6 1/2J	670	290	214	632	7.8
215/55R16XL	97	W	7J	730	290	226	642	7.8
205/40R17XL	84	W	7 1/2J	500	290	212	596	7.8
215/40R17XL	87	W	7 1/2J	545	290	218	604	7.8
215/45R17XL	91	W	7J	615	290	213	626	7.8
225/45R17XL	94	W	7 1/2J	670	290	225	634	7.8
235/45ZR17XL	97	W	8J	730	290	236	644	7.8
245/45R17XL	99	W	8J	775	290	243	652	7.8
205/50R17XL	93	W	6 1/2J	650	290	214	638	7.8
225/50R17XL	98	W	7J	750	290	233	658	7.8
215/35R18XL	84	W	7 1/2J	500	290	218	607	7.8
225/40R18XL	92	W	8J	630	290	230	637	7.8
235/40R18XL	95	W	8 1/2J	690	290	241	645	7.8
245/40R18XL	97	W	8 1/2J	730	290	248	653	7.8
225/45R18XL	95	W	7 1/2J	690	290	225	659	7.8
245/45R18XL	100	W	8J	800	290	243	677	7.8
255/45R18XL	103	W	8 1/2J	875	290	255	687	7.8
265/30R19XL	93	W	9 1/2J	650	290	271	643	7.8
225/35R19XL	88	W	8J	560	290	230	641	7.8
235/35R19XL	91	W	8 1/2J	615	290	241	647	7.8
235/30R20XL	88	Y	8 1/2J	560	290	242	650	7.8

Stand out in Summer Tire Test 2011 by Test World Oy, Finland, beating many world-class brands.

- Asymmetrical design provides optimal ground contact and shortens braking distance on wet and dry surfaces.
- Lug-type shoulder blocks improve handling performance.
- Exterior rim flange protector helps guard wheels from curb damage.

NOVA-FORCE HP

High performance



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
185/55R14	80	H	6J	450	250	194	560	7.7
165/60R14	75	H	5J	387	250	170	554	7.3
185/60R14	82	H	5 1/2J	475	250	189	578	7.7
175/65R14	82	H	5J	475	250	177	584	7.3
185/65R14	86	H	5 1/2J	530	250	189	596	7.8
195/50R15	82	V	6J	475	250	201	577	8.0
185/55R15	82	V	6J	475	250	194	585	7.7
195/55R15	85	V	6J	515	250	201	595	8.0
175/60R15	81	H	5J	462	250	177	591	7.3
185/60R15XL	88	H	5 1/2J	560	290	189	603	7.7
195/60R15	88	H/V	6J	560	250	201	615	8.0
205/60R15	91	H/V	6J	615	250	209	627	8.2
175/65R15	84	H	5J	500	250	177	609	7.3
185/65R15	88	H	5 1/2J	560	250	189	621	8.0
195/65R15	91	H/V	6J	615	250	201	635	8.0
205/65R15	94	H/V	6J	670	250	209	647	8.2
205/50R16	87	V	6 1/2J	545	250	214	612	8.2
205/55R16	91	V	6 1/2J	615	250	214	632	8.2

- Four straight wide circumferential grooves reduce hydroplaning effectively.
- Symmetric tread pattern design offers comfort and quietness.
- A solid center rib enhances handling stability.
- Optimized pitch sequence reduces noise.

NOVA-FORCE GP

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
145/70R13	71	T	4.50B	345	250	150	534	7.6
155/65R13	73	T	4.50B	365	250	157	532	7.6
155/65R14	75	T	4 1/2J	387	250	157	558	7.6
155/70R12	73	S	4.50B	365	250	157	523	7.6
155/70R13	75	T	4.50B	387	250	157	548	7.6
155/80R13	79	T	4.50B	437	250	157	578	7.6
165/65R13	77	T	5.00B	412	250	170	544	7.6
165/65R14	79	T	5J	437	250	170	570	7.6
165/70R13	79	T	5.00B	437	250	170	562	7.6
165/70R14	81	T	5J	462	250	170	588	7.6
175/60R13	77	H	5.00B	412	250	177	540	7.6
175/65R13	80	T	5.00B	450	250	177	558	7.6
175/65R14	82	T	5J	475	250	177	584	7.6
175/70R13	82	T	5.00B	475	250	177	576	7.6
175/70R14	84	T	5J	500	250	177	602	7.6
185/65R14	86	T	5 1/2J	530	250	189	596	7.8
185/65R15	88	T	5 1/2J	560	250	189	621	7.8
185/70R14	88	T	5 1/2J	560	250	189	616	7.8
195/65R15	91	T	6J	615	250	201	635	7.8
205/60R14	88	H	6J	560	250	209	602	7.8

- Seal lateral grooves of shoulder reduce noise.
- Irregular pitch design provides comfort and quietness.
- Aiming to three grooves design in Europe marketing, ensuring the tread pattern groove feature, improving the stability of high-speed handling.

LION SPORT UHP

Ultra high performance



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
195/45R16XL	84	V	6 1/2J	500	290	195	582	7.8
205/40R17XL	84	W	7 1/2J	500	290	212	596	7.8
205/45R16XL	87	W	7J	545	290	206	590	7.8
205/45R17XL	88	W	7J	560	290	206	616	7.8
205/50R16	87	W	6 1/2J	545	250	214	612	7.8
205/50R16	87	V	6 1/2J	545	250	214	612	7.8
205/50R17XL	93	W	6 1/2J	650	290	214	638	7.8
205/55R16XL	94	W	6 1/2J	670	290	214	632	7.8
215/35R18XL	84	W	7 1/2J	500	290	218	607	7.8
215/40R16XL	86	W	7 1/2J	530	290	218	578	7.8
215/40R17XL	87	W	7 1/2J	545	290	218	604	7.8
215/45R17XL	91	W	7J	615	290	213	626	7.8
215/55R16XL	97	W	7J	730	290	226	642	7.8
225/35R19XL	88	W	8J	560	290	230	641	7.8
225/40R18XL	92	W	8J	630	290	230	637	7.8
225/45R17XL	94	W	7 1/2J	670	290	225	634	7.8
225/45R18XL	95	W	7 1/2J	690	290	225	659	7.8
225/50R16XL	96	V	7J	710	290	233	632	7.8
225/50R17XL	98	W	7J	750	290	233	658	7.8
235/30R20XL	88	Y	8 1/2J	560	290	242	650	7.8
235/35R19XL	91	W	8 1/2J	615	290	241	647	7.8
235/40R18XL	95	W	8 1/2J	690	290	241	645	7.8
235/45ZR17XL	97	W	8J	730	290	236	644	7.8
235/50R18XL	101	W	7 1/2J	825	290	245	693	7.8
245/40R18XL	97	W	8 1/2J	730	290	248	653	7.8
245/45R17XL	99	W	8J	775	290	243	652	7.8
245/45R18XL	100	W	8J	800	290	243	677	7.8
255/45R18XL	103	W	8 1/2J	875	290	255	687	7.8
265/30R19XL	93	W	9 1/2J	650	290	271	643	7.8

- Symmetrical design provides optimal ground contact and shortens braking distance on wet and dry surfaces.
- Lug-type shoulder blocks improve handling performance.
- Exterior rim flange protector helps guard wheels from curb damage.

LION SPORT HP

High performance



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
185/70R14	88	H	5 1/2J	560	250	189	616	7.7
195/70R14	91	H	6J	615	250	201	630	7.9
185/60R14	82	H	5 1/2J	475	250	189	578	7.7
185/60R15	84	H	5 1/2J	500	250	189	603	7.7
195/60R15	88	H	6J	560	250	201	615	8.0
205/60R15	91	H	6J	615	250	209	627	8.2
215/60R15	94	H	6 1/2J	670	250	221	639	8.4
185/65R15	88	H	5 1/2J	560	250	189	621	7.7
195/55R15	85	V	6J	515	250	201	595	8.0
195/50R15	82	V	6J	475	250	201	577	8.0
195/65R15	91	H/V	6J	615	250	201	635	8.0
205/65R15	94	H	6J	670	250	209	647	8.2
215/65R15	96	H	6 1/2J	710	250	221	661	8.4
205/55R16	91	H	6 1/2J	615	250	214	632	8.2
205/60R16	92	H	6J	630	250	209	652	8.2
225/60R16	98	H	6 1/2J	750	250	228	676	8.4
235/60R16	100	H	7J	800	250	240	688	8.6
235/55R17	99	H	7 1/2J	775	250	245	690	8.4
235/65R17	104	H	7J	900	250	240	738	8.6
225/55R17	97	H	7J	730	300	247	677	8.8

- Four straight wide circumferential grooves reduce hydroplaning effectively.
- Symmetric tread pattern design offers comfort and quietness.
- A solid center rib enhances handling stability.
- Optimized pitch sequence reduces noise.

LION SPORT GP

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
175/70R13	82	T	5.00B	475	250	177	576	8.7
185/65R14	86	T	5 1/2J	530	250	189	596	8.9
185/65R15	88	T	5 1/2J	560	250	189	621	8.9
185/70R14	88	T	5 1/2J	560	250	189	616	8.9
195/70R14	91	T	6J	615	250	201	630	8.9
205/70R15	96	T	6J	710	250	209	669	9.2
205/75R15	97	S	5 1/2J	730	250	203	689	9.2
215/70R15	98	T	6 1/2J	750	250	221	683	9.2
215/75R15	100	S	6J	800	250	216	703	9.2
225/75R15	102	S	6J	850	250	223	719	9.2
235/75R15	105	S	6 1/2J	925	250	235	733	9.2
175/65R14	82	T	5J	475	250	177	584	8.7

- Four straight wide circumferential grooves reduce hydroplaning effectively.
- Symmetric tread pattern provides comfort and quietness.
- A solid center rib enhances handling stability.
- Optimized pattern pitch sequence reduces noise.

RADIAL660

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
P225/75R15	102	S	6J	850	250	223	719	10.3

- High mileage and wear resistance.
- Good handling at high speed.
- Excellent traction while running on snow and ice.
- High performance tire suits all terrain.

RADIAL619

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
195/65R15	91	H	6J	615	250	201	635	8.0

- Pattern with strong grippage improves swerve performance when run in high speed.
- Low noise.

RADIAL618

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
185/55R14	80	H	6J	450	250	194	560	8.0
185/60R14	82	H	5 1/2J	475	250	189	578	8.0
195/55R15	85	H/V	6J	515	250	201	595	8.0
195/60R15	88	H	6J	560	250	201	615	8.0
205/55R15	88	H	6 1/2J	560	250	214	607	8.0
215/60R16	95	H	6 1/2J	690	250	221	664	7.8
225/60R16	98	H	6 1/2J	750	250	228	676	7.8
195/60R15	88	V	6J	560	250	201	615	8.0
205/55R15	88	V	6 1/2J	560	250	214	607	8.0

- Skin resistance on wet and dry roads.
- Robust structure improves bead durability.

GL699

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
195/50R15	82	V	6J	475	250	201	577	7.8
235/60R15	98	H	7J	750	250	240	663	7.8

- Mobile single rotation pattern provides enduring, stable and comfortable driving.
- The speed per hour is above 240km/h.

RADIAL620

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
205/70R15	96	H	6J	710	250	209	669	10.2
205/80R16	104	T	5 1/2J	900	280	203	734	10.2
215/65R16	98	H	6 1/2J	750	250	221	686	10.2
215/70R16	100	T	6 1/2J	800	250	221	708	10.2
235/65R17	108	H	7J	1000	290	240	738	10.2
235/70R16	106	T	7J	950	250	240	736	10.2
245/70R16	107	H	7J	975	250	248	750	10.2
265/70R15	112	H	8J	1120	250	272	753	10.2
265/70R16	112	H	8J	1120	250	272	778	10.2
275/55R17	109	V	8 1/2J	1030	250	284	734	10.2

- Excellent traction.
- Skid prevention on wet road.
- Robust structure to improve bead durability.

LL700

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
155/70R13	75	T	4 1/2J	387	250	157	548	8.1
175/70R13	82	T/S	5.00B	475	250	177	576	8.1
185/70R13	86	T/S	5 1/2J	530	250	189	590	8.1
175/70R14	84	T/S	5J	500	250	177	602	8.1
185/70R14	88	T/S	5 1/2J	560	250	189	616	8.1
195/70R14	91	T/S	6J	615	250	201	630	8.1
205/70R14	94	T/S	6J	670	250	209	644	8.1
205/70R14	95	T	6J	690	250	209	644	8.1
215/70R14	96	T/S	6 1/2J	710	250	221	658	8.2
205/70R15	96	T/S	6J	710	250	209	669	8.2
215/70R15	98	T/S	6 1/2J	750	250	221	683	8.2

- Good drainage and handling on wet road.
- Stability.

LMA1

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
165/70R14	81	T	5J	462	250	170	588	7.8
165/70R13	83	S	5.00B	487	290	170	562	7.6
165/70R13	79	T	5.00B	437	250	170	562	7.6
165/70R13C	88/86	S	5.00B	D530 S560	375	170	562	7.6
165/70R13LT	92/90	N	5.00B	D600 S630	450	170	562	7.6

- Good drainage.
- Supreme high speed capacity.
- High lateral skid prevention capacity.
- Wear resistance for long life use.
- Good handling stability and traction that can be used on and off road.

LMA2

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
185/60R14	82	H	5 1/2J	475	250	189	578	7.8

Excellent drainage and traction suit all weather.

LMA7

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
185/65R14	86	H	5 1/2J	530	290	189	578	7.8

Large inclinable crossed cannellure helps swerve over with low noise.

LMA3

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
185/70R14	88	H	5 1/2J	560	250	189	616	7.8

Wide circular grooves that dispel water away at high speed.

LMA8

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
175/70R13	82	T	5.00B	475	250	177	576	7.8

- Good drainage.
- Supreme high speed capacity.
- High lateral skid prevention capacity.
- Wear resistance for long life use.
- Good handling stability and traction that can be used on and off road.

LMA9

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
145/70R12	69	S	4 1/2B	325	250	150	509	7.8
155/70R13	75	T	4 1/2B	387	250	157	548	7.8
165/65R13	77	H	5.00B	412	250	170	544	7.8

- High speed performance.
- Good handling and stability.
- Suits all weather.

LMA15

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
165/60R14	75	H	5J	387	250	170	554	7.8

- Good drainage.
- Supreme high speed capacity.
- High lateral skid prevention capacity.
- Wear resistance for long life use.
- Good handling stability and traction that can be used on and off road.

LMA16

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
175/70R14LT	95/93	S	5J	D650 S690	375	177	602	7.8
175/75R14LT	99/98	S	5J	D750 S775	450	177	618	7.8

- Good drainage.
- Supreme high speed capacity.
- High lateral skid prevention capacity.
- Wear resistance for long life use.
- Good handling stability and traction that can be used on and off road.

LMA18

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
155/65R13	73	H	4.50B	365	250	157	532	7.8
165/65R14	79	T	5J	437	250	170	570	7.8
175/65R13	80	H	5.00B	450	250	177	558	7.8
175/65R14	82	H	5J	475	250	177	584	7.8
195/60R14	86	H	6J	530	250	201	590	7.8

- Good drainage.
- High traction and wear resistance.
- Good drainage.
- Good handling on wet road.

Light Truck Tire

LMB2

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
P225/75R15	102	S	6J	850	250	223	719	10.3

- High mileage and wear resistance.
- Good handling at high speed.
- Excellent traction while running on snow and ice.
- High performance tire suits all terrain.

LMB3

Radial tire for passenger car



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
195/70R15C(WHITE)	104/102	R	6J	D850 S900	450	201	655	10.2
215/75R15	100	S	6J	800	250	216	703	9.2
235/75R15	105	S	6 1/2J	925	250	235	733	9.2
195/70R15C	100/98	Q	6J	D750 S800	375	201	655	10.2

- Suitable for all terrain.
- High mileage with wear resistance.



LMC2

Metric series radial light truck tire

Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
195/75R14C	106/104	N	5 1/2J	D900 S950	475	196	648	9.7

- Excellent traction.
- Skid prevention on wet road.
- Robust structure to improve bead durability.

RADIAL616

Radial tire for light truck



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
30*9.50R15LT	104	Q	7 1/2J	900	350	240	750	11.2
31*10.50R15LT	109	Q	8 1/2J	1030	350	265	775	11.2

- High mileage and wear resistance.
- Good handling at high speed.
- Excellent traction while running on snow and ice.
- High perform ancetyre suits all terrain.

RADIAL666

Metric series radial light truck tire



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
165/70R14C	89/87	R	5J	D545 S580	375	170	588	8.3
175/75R16C	101/99	R	5J	D775 S825	475	177	668	8.3
185/75R16C	104/102	R	5J	D850 S900	475	184	684	8.3
205/75R14C(WHITE)	109/107	R	5 1/2J	D975 S1030	475	203	664	9.2
205/75R16C	110/108	R	5 1/2J	D1000 S1060	475	203	714	9.2
225/70R15C	112/110	R	6 1/2J	D1060 S1120	450	228	697	9.2
215/75R16C	113/111	R	6J	D1090 S1150	475	216	728	9.2
225/75R16C	121/120	R	6J	D1400 S1450	575	223	744	9.2
155R12C	83/81	N	4.50B	D462 S487	350	157	553	7.8
185R14C	102/100	Q	5 1/2J	D800 S850	450	189	652	9.5
195/70R15C(WHITE)	104/102	R	6J	D850 S900	450	201	655	9.2
205/70R15C	106/104	S	6J	D900 S950	450	209	669	9.2
195/65R16C	104/102	R	6J	D850 S900	475	201	660	9.2
195/75R16C	107/105	R	5 1/2J	D925 S975	475	196	698	9.7
205/65R16C	107/105	R	6J	D925 S975	475	209	672	9.2
215/65R16C	109/107	R	6 1/2J	D975 S1030	475	221	686	9.2
225/65R16C	112/110	R	6 1/2J	D1060 S1120	475	228	698	9.3
235/65R16C	115/113	R	7J	D1150 S1215	475	240	712	9.2
215R14C	110/108	R	6J	D1000 S1060	450	218	700	9.7

- Excellent traction.
- Skid prevention on wet road.
- Robust structure to improve bead durability.

LMC7

Conventional section radial light truck tire



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
195R15C	106/104	Q	5 1/2J	D900 S950	450	198	690	9.7
195R15C(WHITE)	106/104	Q	5 1/2J	D900 S950	450	198	690	9.7

- Suitable for all terrain.
- High mileage with wear resistance.

LMC4

Conventional section radial light truck tire



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
6.50R16C	107/103	N	5.50F	D860 S975	560	176	742	10
7.00R15LT	110/105	L	5.50F	D915 S1040	560	200	750	10.7
7.50R16LT	116/112	L	6.00G	D1120 S1250	560	220	808	11.2
7.50R16LT	122/118	L	6.00G	D1320 S1500	770	220	808	11.2
6.50R16C	110/105	M	5.50F	D925 S1060	670	176	742	10
7.50R16LT	120/116	M	5.50F	D925 S1060	670	176	742	11.2

- Suitable for all terrain.
- High mileage with wear resistance.

LMC8

Conventional section radial light truck tire



Size	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kpa)	Inflated Section Width(mm)	Inflated Overall Diameter(mm)	Pattern Depth(mm)
195R14C(WHITE)	106/104	P	5 1/2J	D900 S950	450	198	666	9.2
195R14C(BLACK)	106/104	P	5 1/2J	D900 S950	450	198	666	9.2
205R14C(BLACK)	109/107	R	6J	D975 S1030	450	208	686	9.2
205R15C(WHITE)	110/108	R	6J	D1000 S1060	450	208	710	9.2

- The super physical design, shockproof and wear resistance.
- Good turning and road-surface controlling ability.