



ANTYRE



European Labeling Regulations

Rolling Noise Class

Tyre class	Nominal (Nominal) section width (mm)	Limit values in dB(A)
C1A	≤185	70
C1B	> 185≤215	71
C1C	> 215≤245	71
C1D	> 245≤275	72
C1E	> 275	74

For snow tyres, extra load tyres or reinforced tyres, or any combination of these classifications, the above limits shall be increased by 1 dB(A).

Tyre class	Category of use	Limit values in dB(A)
C2	Normal tyres	72
	Traction tyres	73
C3	Normal tyres	73
	Traction tyres	75

For special use tyres, the above limits shall be increased by 2 dB(A). An additional 2 dB(A) shall be allowed for snow tyres in the C2 traction tyre category. For all other categories (categories) of C2 and C3 tyres, and additional 1 dB(A) shall be allowed for snow tyres.

N in Db	External rolling noise class	N in Db	External rolling noise class	N in Db	External rolling noise class
N≤LV-3		LV-3<N≤LV		N>LV	

Wet Grip Class

C1 tyres G	Wet grip class	C2 tyres G	Wet grip class	C3 tyres G	Wet grip class
1.55≤G	A	1.40≤G	A	1.25≤G	A
1.40≤G≤1.54	B	1.25≤G≤1.39	B	1.10≤G≤1.24	B
1.25≤G≤1.39	C	1.10≤G≤1.24	C	0.95≤G≤1.09	C
Empty	D	Empty	D	0.80≤G≤0.94	D
1.10≤G≤1.24	E	0.95≤G≤1.09	E	0.65≤G≤0.79	E
G≤1.09	F	G≤0.94	F	G≤0.64	F
Empty	G	Empty	G	Empty	G

Rolling resistance Class

C1 tyres		C2 tyres		C3 tyres	
RRC in kg/t	Energy efficiency class	RRC in kg/t	Energy efficiency class	RRC in kg/t	Energy efficiency class
RRC≤6.5	A	RRC≤5.5	A	RRC≤4.0	A
6.6≤RRC≤7.7	B	5.6≤RRC≤6.7	B	4.1≤RRC≤5.0	B
7.8≤RRC≤9.0	C	6.8≤RRC≤8.0	C	5.1≤RRC≤6.0	C
Empty	D	Empty	D	6.1≤RRC≤7.0	D
9.1≤RRC≤10.5	E	8.1≤RRC≤9.2	E	7.1≤RRC≤8.0	E
10.6≤RRC≤12.0	F	9.3≤RRC≤10.5	F	RRC≥8.1	F
RRC≥12.1	G	RRC ≥10.6	G	Empty	G



TB655

- Designed for front and trailer wheels.
- With extra anti-side and wet skid resistance.
- Super Traction and braking performance.
- Heavy load and High Speed capability.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
275/80R22.5	16	M	16.0	20.2	149/146	3250/3000(7170/6620)	276	1012	850(123)	8.25	-	-	-	-
295/80R22.5	18	M	15.0	18.9	152/148	3550/3150(7830/6945)	298	1044	850(123)	9.00	71	2	C	C
315/80R22.5	18	M	15.0	18.9	154/151	3750/3450(8270/7610)	312	1076	830(120)	9.00	71	2	C	C
315/80R22.5	20	M	15.0	18.9	157/154	4125/3750(9090/8270)	312	1076	900(130)	9.00	71	2	C	C
11R22.5	14	M	15.0	18.9	144/142	2800/2650(6175/5840)	279	1050	720(105)	8.25	-	-	-	-
11R22.5	16	M	15.0	18.9	146/143	3000/2725(6610/6005)	279	1050	830(120)	8.25	-	-	-	-
11R24.5	14	M	15.0	18.9	146/143	3000/2725(6610/6005)	279	1104	720(105)	8.25	-	-	-	-
11R24.5	16	L	15.0	18.9	149/146	3250/3000(7160/6610)	279	1104	830(120)	8.25	-	-	-	-
12R22.5	18	M	15.0	18.9	152/149	3550/3250(7830/7160)	300	1084	930(135)	9.00	71	2	C	C
11.00R22	18	L	16.0	20.2	154/151	3750/3450(8270/7610)	293	1135	930(134)	8.0	-	-	-	-



TB656

- Designed for Driving wheels.
- With extra grip performance.
- Super Traction and braking performance.
- Heavy load and High Speed capability.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
295/80R22.5	18	M	22.0	27.7	152/148	3550/3150(7830/6945)	298	1044	850(123)	9.00	75	2	C	D
315/80R22.5	18	M	22.0	27.7	154/151	3750/3450(8270/7610)	312	1076	830(120)	9.00	75	2	C	D
315/80R22.5	20	M	22.0	27.7	157/154	4125/3750(9090/8270)	312	1076	900(130)	9.00	75	2	C	D
11R22.5	16	M	22.0	27.7	146/143	3000/2725(6610/6005)	279	1050	830(120)	8.25	-	-	-	-
12R22.5	18	M	22.0	27.7	152/149	3550/3250(7830/7160)	300	1084	930(135)	9.00	75	2	C	D
11.00R22	18	L	22.0	27.7	154/151	3750/3450(8270/7610)	293	1135	930(134)	8.0	-	-	-	-
10.00R20	18	L	22.0	27.7	149/146	3250/3000(7170/6610)	278	1055	930(134)	7.5	-	-	-	-



TB666

- Suitable for all position use, which provide good stability for steering, traction and trailer.
- Super high speed performance with lower noise emission.
- Good wear distribution and wider road contact.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
215/75R17.5	14	M	13.5	17.0	126/124	1700/1600(3750/3530)	211	767	700(102)	6.00	73	2	D	E
215/75R17.5	16	J	13.5	17.0	135/133	2180/2060(4805/4540)	211	767	865(125)	6.00	73	2	D	E
235/75R17.5	16	M	13.5	17.0	132/130	2000/1900(4410/4190)	233	797	775(112)	6.75	73	2	D	E
235/75R17.5	18	J	13.5	17.0	143/141	2725/2575(6005/5675)	233	797	875(128)	6.75	73	2	D	E



TB700

- Excellent performance for driving and braking, highly tear resistant, high cut resistance, wear resistant, and super loading capability.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
315/80R22.5	18	K	20.0	25.2	154/151	3750/3450(8270/7610)	312	1076	830(120)	9.00	73	2	C	C
315/80R22.5	20	K	20.0	25.2	157/154	4125/3750(9090/8270)	312	1076	900(130)	9.00	73	2	C	C
12R22.5	18	K	20.0	25.2	152/149	3550/3250(7830/7160)	300	1084	930(135)	9.00	73	2	C	C
13R22.5	18	K	21	26.5	154/151	3750/3450(8270/7610)	320	1124	830(120)	9.75	73	2	C	C
13R22.5	20	K	21	26.5	156/150	4000/3350(8820/7390)	320	1124	875(127)	9.75	73	2	C	C



TB668

- Designed for driving wheels.
- With extra grip performance.
- Super traction and braking performance.
- Heavy load and high speed capability.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
315/80R22.5	20	M	14.5	18.3	157/154	4125/3750(9090/8270)	312	1076	900(130)	9.00	73	2	C	C



TB707

- Improved resistance of tread block crack.
- Super Traction and long mileage with unique directional tread design.
- Excellent resistance of cuts and abrasions both on and off the road.
- Superior resistance of wear under worse road condition.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
295/80R22.5	18	L	20.5	25.8	152/148	3550/3150(7830/6945)	298	1044	850(123)	9.00	75	2	D	D
315/80R22.5	18	L	21.0	26.5	154/151	3750/3450(8270/7610)	312	1076	830(120)	9.00	75	2	D	D
10.00R20	18	L	22.0	27.7	149/146	3250/3000(7160/6610)	278	1055	930(134)	7.5	-	-	-	-
11R22.5	16	M	20.5	25.8	146/143	3000/2725(6610/6005)	279	1050	830(120)	8.25	-	-	-	-
12R22.5	18	K	21.0	26.5	152/149	3550/3250(7830/7160)	300	1084	930(135)	9.00	75	2	D	D
13R22.5	18	K	22.0	27.7	154/151	3750/3450(8270/7610)	320	1124	830(120)	9.75	75	2	D	D

TB726 TB726+

- Applicable for all wheels of Passenger Vehicle and front wheel of truck.
- The Pattern is designed for long mileage.
- Applicable for high speed and lower noise.



Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
11R22.5	14	M	15.0	19.0	144/142	2800/2650(6175/5840)	279	1050	720(105)	8.25	-	-	-	-
11R22.5	16	M	15.0	19.0	146/143	3000/2725(6610/6005)	279	1050	830(120)	8.25	-	-	-	-
11R24.5	14	M	15.0	19.0	146/143	3000/2725(6610/6005)	279	1104	720(105)	8.25	-	-	-	-
11R24.5	16	L	15.0	19.0	149/146	3250/3000(7160/6610)	279	1104	830(120)	8.25	-	-	-	-
295/75R22.5	14	M	15.0	19.0	144/141	2800/2575(6175/5675)	298	1014	760(110)	9.00	-	-	-	-
295/75R22.5	16	L	15.0	19.0	146/143	3000/2725(6610/6005)	298	1014	830(120)	9.00	-	-	-	-
285/75R24.5	14	M	15.0	19.0	144/141	2800/2575(6175/5675)	283	1050	760(110)	8.25	-	-	-	-
285/75R24.5	16	L	15.0	19.0	147/144	3075/2800(6780/6175)	283	1050	830(120)	8.25	-	-	-	-

TB735

- Applicable for driving wheels.
- The pattern provides good pulling force.
- Applicable for high speed and long mileage.



Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
11R22.5	14	M	22.0	27.7	144/142	2800/2650(6175/5840)	279	1050	720(105)	8.25	-	-	-	-
11R22.5	16	M	22.0	27.7	146/143	3000/2725(6610/6005)	279	1050	830(120)	8.25	-	-	-	-
11R24.5	14	M	22.0	27.7	146/143	3000/2725(6610/6005)	279	1104	720(105)	8.25	-	-	-	-
11R24.5	16	L	22.0	27.7	149/146	3250/3000(7160/6610)	279	1104	830(120)	8.25	-	-	-	-
295/75R22.5	14	M	22.0	27.7	144/141	2800/2575(6175/5675)	298	1014	760(110)	9.00	-	-	-	-
295/75R22.5	16	L	22.0	27.7	146/143	3000/2725(6610/6005)	298	1014	830(120)	9.00	-	-	-	-
285/75R24.5	14	M	22.0	27.7	144/141	2800/2575(6175/5675)	283	1050	760(110)	8.25	-	-	-	-
285/75R24.5	16	L	22.0	27.7	147/144	3075/2800(6780/6175)	283	1050	830(120)	8.25	-	-	-	-



TB728+

- Super ground grasping capability
- Good traction and braking performance
- Both have high loading and high speed capability
- Designed for driving

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
11.00R20	18	K	18.0	22.7	152/149	3550/3250(7830/7170)	293	1085	930(135)	8.0	-	-	-	-
12.00R20	18	K	19.0	23.9	154/151	3750/3450(8270/7610)	315	1125	830(120)	8.5	-	-	-	-

TB753

- Applicable for driving wheels.
- With extra grip performance.
- Super Traction and braking performance.
- Heavy load and High Speed capability.



Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
295/60R22.5	16	L	18.5	23.3	150/147	3350/30750(7385/6780)	292	926	900(130)	9.00	75	2	D	E
315/60R22.5	16	M	18.5	23.3	152/148	3550/3150(7830/6945)	316	949	900(130)	9.75	75	2	D	E
305/70R22.5	16	M	22.0	27.7	152/148	3550/3150(7830/6945)	305	1000	900(130)	9.00	75	2	D	E
315/70R22.5	16	M	20.5	25.8	154/150	3750/3350(8270/7385)	312	1014	900(130)	9.00	75	2	D	E
295/80R22.5	18	M	22.0	27.7	152/148	3550/3150(7830/6945)	298	1044	850(123)	9.00	75	2	D	E
315/80R22.5	18	M	22.0	27.7	154/151	3750/3450(8270/7610)	312	1076	830(120)	9.00	75	2	D	E
305/75R24.5	16	L	22.0	27.7	154/149	3750/3250(8270/7160)	305	1080	850(123)	9.00	-	-	-	-
12R22.5	18	M	22.0	27.7	152/149	3550/3250(7830/7160)	300	1084	930(135)	9.00	75	2	D	E
11.00R22	18	L	22.0	27.7	154/151	3750/3450(8270/7610)	293	1135	930(134)	8.0	-	-	-	-
10.00R20	18	L	22.0	27.7	149/146	3250/3000(7160/6610)	278	1055	930(134)	7.5	-	-	-	-



TB762

- Designed for front and trailer wheels.
- With extra anti-side and wet skid resistance.
- Super Traction and braking performance.
- Heavy load and High Speed capability.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
295/60R22.5	16	L	13.5	17.0	150/147	3350/3075(7385/6780)	292	926	900(130)	9.00	71	2	C	C
315/60R22.5	16	M	13.5	17.0	152/148	3550/3150(7830/6945)	316	949	900(130)	9.75	71	2	C	C
305/70R22.5	16	M	15.0	18.9	152/148	3550/3150(7830/6945)	305	1000	900(130)	9.00	71	2	C	C
315/70R22.5	16	M	15.0	18.9	154/150	3750/3350(8270/7385)	312	1014	900(130)	9.00	71	2	C	C
275/80R22.5	16	M	15.0	18.9	149/146	3250/3000(7165/6620)	276	1012	850(123)	8.25	71	2	C	C
295/80R22.5	18	M	15.0	18.9	152/148	3550/3150(7830/6945)	298	1044	850(123)	9.00	71	2	C	C
315/80R22.5	18	M	15.0	18.9	154/151	3750/3450(8270/7610)	312	1076	830(120)	9.00	71	2	C	C
305/75R24.5	16	L	15.0	18.9	154/149	3750/3250(8270/7160)	305	1080	850(123)	9.00	-	-	-	-
12R22.5	18	M	15.0	18.9	152/149	3550/3250(7830/7160)	300	1084	930(135)	9.00	71	2	C	C
11.00R22	18	L	15.0	18.9	154/151	3750/3450(8270/7610)	293	1135	930(134)	8.0	-	-	-	-



TB788

- Designed for trailer wheels specially.
- With extra anti-side and wet skid resistance.
- Light weight and lower rolling resistance.
- Heavy load and High speed capability.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
11R22.5	14	M	10.5	13.2	144/142	2800/2650(6175/5845)	279	1050	720(105)	8.25	-	-	-	-
11R24.5	14	M	10.5	13.2	146/143	3000/2725(6610/6010)	279	1104	720(105)	8.25	-	-	-	-
295/75R22.5	14	M	10.5	13.2	144/141	2800/2575(6175/5680)	298	1014	760(110)	9.00	-	-	-	-
285/75R24.5	14	M	10.5	13.2	144/141	2800/2575(6175/5680)	283	1050	760(110)	8.25	-	-	-	-



TB777

- Combination pattern for passenger and cargo vehicles.
- Strong damage resistance.
- High level wear resistance.
- Powerful driving force.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
12.00R24	20	K	14.5	18.3	160/157	4500/4125(9920/9090)	315	1226	900(130)	8.5	-	-	-	-



TB798

- Designed with Ultra-wear and anti-stab formula suitable for rough road conditions.
- Super deep tread provides long life and avoids cut through.
- Excellent traction provides strong power and better wear resistance.
- Heavy loads capability.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
11R22.5	16	M	22.0	27.7	146/143	3000/2725(6610/6005)	279	1050	830(120)	8.25	-	-	-	-
11R24.5	16	L	22.0	27.7	149/146	3250/3000(7160/6610)	279	1054	930(135)	8.25	-	-	-	-



TB877

- Designed combination pattern for all wheels of bus and trucks.
- Strong damage and wear resistance.
- Applicable for high speed, long mileage and powerful driving force.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
7.00R16LT	14	L	13.0	16.4	118/114	1320/1180(2910/2600)	200	775	770(110)	5.50F	-	-	-	-
7.50R16LT	16	L	12.5	15.7	124/120	1600/1400(3525/3085)	215	805	870(125)	6.00G	-	-	-	-
8.25R16LT	16	M	12.5	15.7	128/124	1800/1600(3970/3530)	235	856	770(112)	6.50H	-	-	-	-
8.25R20	16	L	14.5	18.3	139/137	2430/2300(5360/5070)	236	974	930(135)	6.5	-	-	-	-
9.00R20	16	L	15.5	19.5	144/142	2800/2650(6180/5850)	259	1019	900(130)	7.0	-	-	-	-
12.00R20	18	L	17.5	22.0	154/151	3750/3450(8270/7610)	315	1125	830(120)	8.5	-	-	-	-
12.00R24	20	K	14.5	18.3	160/157	4500/4125(9920/9090)	315	1226	900(130)	8.5	-	-	-	-
11R22.5	16	M	15.5	19.5	146/143	3000/2725(6610/6005)	279	1054	830(120)	8.25	-	-	-	-
11R24.5	14	M	15.5	19.5	146/143	3000/2725(6610/6005)	279	1104	720(105)	8.25	-	-	-	-
11R24.5	16	L	15.5	19.5	149/146	3250/3000(7160/6610)	279	1104	830(120)	8.25	-	-	-	-
12R22.5	18	M	17.0	21.5	152/149	3550/3250(7830/7160)	300	1084	930(135)	9.00	71	2	C	D
13R22.5	18	L	14.5	18.3	154/151	3750/3450(8270/7610)	320	1124	830(120)	9.75	71	2	C	D
315/80R22.5	18	M	17.0	21.5	154/151	3750/3450(8270/7610)	312	1076	830(120)	9.00	71	2	C	D
315/80R22.5	20	M	17.0	21.5	157/154	4125/3750(9090/8270)	312	1076	900(130)	9.00	71	2	C	D



TB882

- Applicable for high speed trailer wheel.
- Superior stability and safety with center lines.
- Delicate and popular center slits provide exceptional grip effect.
- Low noise offers a comfortable and reliable ride.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
215/75R17.5	14	M	12.5	15.7	126/124	1700/1600(3750/3530)	211	767	700(102)	6.00	71	2	D	E
215/75R17.5	16	J	12.5	15.7	135/133	2180/2060(4805/4540)	211	767	865(125)	6.00	-	-	-	-
235/75R17.5	16	M	12.5	15.7	132/130	2000/1900(4410/4190)	233	797	775(112)	6.75	-	-	-	-
235/75R17.5	18	J	12.5	15.7	143/141	2725/2575(6005/5675)	233	797	875(128)	6.75	-	-	-	-
385/65R22.5	20	K	16.5	20.8	160	4500(9920)	389	1072	900(130)	11.75	71	2	D	E
425/65R22.5	20	K	16.5	20.8	165	5150(11350)	430	1124	830(120)	13.00	71	2	D	E



TB900

- Designed with super mixed pattern suitable for mining and mountainous region;
- Super deep tread provides long life and avoids cut through.
- Excellent traction provides strong power and better wear resistance.
- Heavy loads capability.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
10.00R20	16	J	20.5	25.8	146/143	3000/2725(6620/6010)	278	1054	830(120)	7.5	-	-	-	-
10.00R20	18	J	20.5	25.8	149/146	3250/3000(7160/6610)	278	1054	930(135)	7.5	-	-	-	-
11.00R20	16	J	21.0	26.5	150/147	3350/3075(7390/6780)	293	1085	830(120)	8.0	-	-	-	-
11.00R20	18	J	21.0	26.5	152/149	3550/3250(7830/7170)	293	1085	930(135)	8.0	-	-	-	-
12.00R20	18	J	22.0	27.7	154/151	3750/3450(8270/7610)	315	1125	830(120)	8.5	-	-	-	-
12R22.5	18	G	22.0	27.7	152/149	3550/3250(7830/7160)	300	1084	930(135)	9.00	-	-	-	-



TB906

- Suitable for high speed and heavy loads.
- Applicable for all wheels, special for steer and trailer wheel.
- Excellent wear resistance ensures long mileage.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
9R22.5	14	M	14.5	18.3	136/134	2240/2120(4940/4675)	229	974	830(120)	6.75	-	-	-	-
10R22.5	16	M	15.5	19.5	144/142	2800/2650(6175/5845)	254	1019	900(130)	7.50	-	-	-	-
11R22.5	16	M	16.5	20.8	146/143	3000/2725(6610/6005)	279	1054	830(120)	8.25	-	-	-	-
11R24.5	16	L	16.5	20.8	149/146	3250/3000(7160/6610)	279	1104	830(120)	8.25	-	-	-	-
12R22.5	18	M	16.5	20.8	152/149	3550/3250(7830/7160)	300	1084	930(135)	9.00	71	2	C	E
13R22.5	18	M	16.5	20.8	154/151	3750/3450(8270/7610)	320	1124	830(120)	9.75	71	2	C	E
295/80R22.5	16	M	16.5	20.8	152/148	3550/3150(7830/6945)	298	1044	850(123)	9.00	71	2	C	E
295/80R22.5	18	M	16.5	20.8	154/151	3750/3450(8270/7610)	298	1044	900(130)	9.00	71	2	C	E
315/80R22.5	18	M	16.5	20.8	154/151	3750/3450(8270/7610)	312	1076	830(120)	9.00	71	2	C	E
315/80R22.5	20	M	16.5	20.8	157/154	4125/3750(9090/8270)	312	1076	900(130)	9.00	71	2	C	E



TB913

- Designed with block tread for on the road use specially.
- Super deep tread provides long life and avoids cut through.
- Excellent traction provides strong power and better wear resistance.
- Heavy loads capability.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
7.00R16LT	14	K	15.0	18.9	118/114	1320/1180(2910/2600)	200	775	770(110)	5.50F	-	-	-	-
7.50R16LT	16	K	15.0	18.9	124/120	1600/1400(3525/3085)	215	805	870(125)	6.00G	-	-	-	-
8.25R16LT	16	K	15.5	19.5	128/124	1800/1600(3970/3530)	235	855	770(112)	6.50H	-	-	-	-
8.25R20	16	K	16.5	20.8	139/137	2430/2300(5360/5070)	236	974	930(135)	6.5	-	-	-	-
9.00R20	16	K	18.5	23.3	144/142	2800/2650(6180/5850)	259	1019	900(130)	7.0	-	-	-	-
10.00R20	16	K	19.5	24.6	146/143	3000/2725(6620/6010)	278	1054	830(120)	7.5	-	-	-	-
10.00R20	18	K	19.5	24.6	149/146	3250/3000(7160/6610)	278	1054	930(135)	7.5	-	-	-	-
11.00R20	16	K	20.5	25.8	150/147	3350/3075(7390/6780)	293	1085	830(120)	8.0	-	-	-	-
11.00R20	18	K	20.5	25.8	152/149	3550/3250(7830/7170)	293	1085	930(135)	8.0	-	-	-	-
12.00R20	18	K	21.5	27.0	154/151	3750/3450(8270/7610)	315	1125	830(120)	8.5	-	-	-	-



TB926

- Super single tyre for trailer axle with excellent driving stability.
- Super wear resistance and durability provide long mileage.
- Applicable for high speed and lower noise.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
385/65R22.5	20	K	16.5	20.8	160	4500(9920)	389	1072	900(130)	11.75	73	2	D	C
425/65R22.5	18	J	16.5	20.8	162	4750(10475)	430	1124	760(110)	13.00	-	-	-	-
425/65R22.5	20	K	16.5	20.8	165	5150(11350)	430	1124	830(120)	13.00	-	-	-	-



TB935

- Super single tyre for on and off the road use.
- Wide and deep tread enhances the driving stability and traction.
- Applicable for all season traction with good pulling force.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
385/65R22.5	20	K	16.5	20.8	160	4500(9920)	389	1072	900(130)	11.75	73	2	D	C
425/65R22.5	18	J	16.5	20.8	162	4750(10475)	430	1124	760(110)	13.00	-	-	-	-
425/65R22.5	20	K	16.5	20.8	165	5150(11350)	430	1124	830(120)	13.00	-	-	-	-



TB1000

- Suitable for trailer positions.
- Strengthened structure provides excellent stability and safety.
- Latest pattern design provides lower noise and lower rolling resistance.
- An outstanding wear resistance and durability.
- Improved compound offers long mileage.

Sizes & Specifications

SIZES	PR	SPEED	TREAD DEPTH		LOAD INDEX	MAX. LOAD	SECTION WIDTH	OA DIA.	STD. PRESS	STD. RIM	Noise		Wet	RRC
			MM	32NDS							S/D	S/Dkg(LBS)		
385/55R19.5	18	J	15.5	19.5	156	4000(8820)	386	919	900(130)	12.25	73	2	D	C
385/55R22.5	20	J	15.5	19.5	160	4250(9370)	386	996	900(130)	12.25	73	2	D	C
385/65R22.5	20	K	16.0	20.2	160	4500(9920)	389	1072	900(130)	11.75	73	2	D	C