

**COMPASAL** 

**POWERFUL  
DRIVING FORCE**



# LONG HAUL

## PRODUCT MANUALS



## CPS21

**Position: All Position**

- High density, flexomatic blading, for outstanding braking on wet surfaces combined with high mileage.
- Groove bottom protectors help deliver additional defense against stone drilling.
- More mileage and greater lateral stability.

| Size        | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|             |          |      |         |          | Single        | Dual |         |         |         |
| 9.5R17.5    | 6.75     | 14   | CPS21   | 129/127L | 1850          | 1750 | 232     | 836     | 12.5    |
| 215/75R17.5 | 6.00     | 16   | CPS21   | 127/124M | 1750          | 1600 | 211     | 767     | 12      |
| 215/75R17.5 | 6.00     | 18   | CPS21   | 135/133J | 2180          | 2060 | 211     | 767     | 12      |
| 235/75R17.5 | 6.75     | 16   | CPS21   | 132/130M | 2000          | 1850 | 233     | 797     | 12.5    |
| 235/75R17.5 | 6.75     | 18   | CPS21   | 143/141J | 2725          | 2575 | 233     | 797     | 12.5    |
| 225/70R19.5 | 6.75     | 14   | CPS21   | 128/126M | 1800          | 1700 | 226     | 811     | 12.5    |
| 245/70R19.5 | 7.50     | 16   | CPS21   | 136/134M | 2180          | 2060 | 248     | 839     | 12.5    |
| 265/70R19.5 | 7.50     | 16   | CPS21   | 140/138M | 2500          | 2360 | 260     | 862     | 12.5    |
| 285/70R19.5 | 8.25     | 16   | CPS21   | 146/144M | 3000          | 2800 | 282     | 886     | 13      |
| 285/70R19.5 | 8.25     | 18   | CPS21   | 150/148J | 3150          | 2900 | 282     | 886     | 13      |
| 255/70R22.5 | 7.50     | 16   | CPS21   | 140/137M | 2500          | 2300 | 254     | 920     | 11      |
| 275/70R22.5 | 8.25     | 16   | CPS21   | 148/145M | 3150          | 2900 | 216     | 952     | 14.5    |
| 315/70R22.5 | 9.00     | 20   | CPS21   | 154/150M | 3750          | 3350 | 312     | 1014    | 15      |
| 385/55R22.5 | 12.25    | 20   | CPS21   | 160L     | 4500          | 4500 | 383     | 996     | 15.5    |
| 295/75R22.5 | 9.00     | 16   | CPS21   | 146/143M | 3000          | 2725 | 298     | 1014    | 15.5    |
| 295/80R22.5 | 9.00     | 18   | CPS21   | 154/151M | 3550          | 3250 | 298     | 1044    | 15.5    |
| 315/80R22.5 | 9.00     | 20   | CPS21   | 157/154M | 4125          | 3750 | 312     | 1076    | 15.5    |
| 385/65R22.5 | 11.75    | 20   | CPS21   | 160L     | 4500          | 4500 | 389     | 1071    | 15.5    |
| 11R22.5     | 8.25     | 16   | CPS21   | 148/145M | 3150          | 2900 | 268     | 1054    | 14.5    |
| 12R22.5     | 9.00     | 18   | CPS21   | 152/149M | 3550          | 3250 | 300     | 1075    | 14.5    |
| 11R24.5     | 8.25     | 16   | CPS21   | 149/146M | 3250          | 3000 | 279     | 1104    | 14.5    |
| 285/75R24.5 | 8.25     | 14   | CPS21   | 144/141M | 2800          | 2575 | 283     | 1050    | 15.5    |
| 285/75R24.5 | 8.25     | 16   | CPS21   | 147/144M | 3075          | 2800 | 283     | 1050    | 15.5    |



## CPS28

**Position: All Position**

- Outstanding self-cleaning tread design promote adaptability in long haul road conditions.
- High density, flexomatic blading, for outstanding braking on wet surfaces combined with high mileage.
- More mileage and greater lateral stability.

| Size        | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|             |          |      |         |          | Single        | Dual |         |         |         |
| 9.5R17.5    | 6.75     | 14   | CPS28   | 129/127L | 1850          | 1750 | 232     | 836     | 12.5    |
| 9.5R17.5    | 6.75     | 18   | CPS28   | 143/141J | 2725          | 2575 | 232     | 836     | 12.5    |
| 12R22.5     | 9.00     | 18   | CPS28   | 152/149M | 3550          | 3250 | 296     | 1075    | 14.5    |
| 315/80R22.5 | 9.00     | 20   | CPS28   | 156/150M | 4000          | 3350 | 312     | 1076    | 15.5    |





## CPS25

**Position: All Position**

- ▶ Premium five-rib tread with various micro sipes to provide high mileage, even wear, low noise.
- ▶ Wide, flat tread optimizes footprint shape for improved handling and response in long haul service.
- ▶ Latest technology carcass geometry and materials for enhanced damage resistance, durability.

| Size        | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|             |          |      |         |          | Single        | Dual |         |         |         |
| 11R22.5     | 8.25     | 16   | CPS25   | 148/145M | 3150          | 2900 | 268     | 1054    | 13      |
| 12R22.5     | 9.00     | 18   | CPS25   | 152/149M | 3550          | 3250 | 300     | 1075    | 14.5    |
| 255/70R22.5 | 7.50     | 16   | CPS25   | 140/137M | 2500          | 2300 | 254     | 926     | 14      |
| 295/75R22.5 | 9.00     | 16   | CPS25   | 146/143M | 3000          | 2725 | 298     | 1014    | 11      |
| 295/80R22.5 | 9.00     | 18   | CPS25   | 152/149M | 3550          | 3250 | 298     | 1044    | 14.5    |
| 315/80R22.5 | 9.00     | 20   | CPS25   | 156/150M | 4000          | 3350 | 312     | 1076    | 14.5    |
| 11R24.5     | 8.25     | 16   | CPS25   | 149/146M | 3250          | 3000 | 279     | 1104    | 11      |
| 11R24.5     | 8.25     | 14   | CPS25   | 146/143M | 3000          | 2725 | 279     | 1104    | 11      |
| 285/75R24.5 | 8.25     | 16   | CPS25   | 147/144M | 3075          | 2800 | 283     | 1050    | 11      |



## CPD88

**Position: Drive Position**

- ▶ Extra deep tread with stone drilling protectors to promote long original mileage.
- ▶ Optimised bead area construction for better durability.
- ▶ Closed-shoulder tread design provides even wear while maintaining excellent traction.

| Size        | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|             |          |      |         |          | Single        | Dual |         |         |         |
| 11R22.5     | 8.25     | 16   | CPD88   | 148/145M | 3150          | 2900 | 268     | 1054    | 20      |
| 295/75R22.5 | 9.00     | 16   | CPD88   | 146/143K | 3000          | 2725 | 298     | 1014    | 20      |
| 11R24.5     | 8.25     | 16   | CPD88   | 149/146K | 3250          | 3000 | 279     | 1104    | 20      |
| 285/75R24.5 | 8.25     | 16   | CPD88   | 147/144L | 3075          | 2800 | 283     | 1050    | 20      |



## CPT76

**Position: Trailer Position**

- ▶ Dual compound rubber helps ensure cool operating temperatures while abrasion resistant upper tread helps keep wear rates low.
- ▶ Lateral sipes along rib edges help enhance traction and braking in adverse weather conditions.
- ▶ Optimized bead area construction for better durability.

| Size        | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|             |          |      |         |          | Single        | Dual |         |         |         |
| 215/75R17.5 | 6.00     | 16   | CPT76   | 127/124M | 1750          | 1600 | 210     | 766     | 12      |
| 235/75R17.5 | 6.75     | 16   | CPT76   | 132/130M | 2000          | 1850 | 233     | 797     | 12.5    |
| 225/70R19.5 | 6.75     | 14   | CPT76   | 128/126M | 1800          | 1700 | 224     | 809     | 12.5    |
| 245/70R19.5 | 7.50     | 16   | CPT76   | 136/134M | 2180          | 2060 | 248     | 839     | 12.5    |
| 265/70R19.5 | 7.50     | 16   | CPT76   | 140/138M | 2500          | 2360 | 260     | 862     | 12.5    |
| 265/70R19.5 | 7.50     | 18   | CPT76   | 143/141J | 2725          | 2575 | 260     | 862     | 12.5    |
| 275/70R22.5 | 8.25     | 16   | CPT76   | 148/145M | 2800          | 2575 | 276     | 958     | 14.5    |
| 285/70R19.5 | 8.25     | 16   | CPT76   | 146/144M | 3000          | 2800 | 282     | 886     | 13      |
| 285/70R19.5 | 8.25     | 18   | CPT76   | 150/148J | 3150          | 2900 | 282     | 886     | 13      |
| 385/55R22.5 | 12.25    | 20   | CPT76   | 160L     | 4500          | 4500 | 383     | 996     | 15.5    |
| 385/65R22.5 | 11.75    | 20   | CPT76   | 160L     | 4500          | 4500 | 389     | 1071    | 15.5    |



# REGIONAL

## PRODUCT MANUALS



### CPD28

**Position: Drive Position**

- Wide, flat tread optimizes footprint shape for improved handling and response in long haul service.
- Vertical and horizontal pattern design promotes soft soil mobility and drive property.
- Better structure ensure driving safety and longer mileage.

| Size    | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|---------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|         |          |      |         |          | Single        | Dual |         |         |         |
| 12R22.5 | 9.00     | 18   | CPD28   | 152/149K | 3550          | 3250 | 296     | 1090    | 22      |



### CPD90

**Position: Drive Position**

- Special rubber compound designed for varied applications .
- Reinforced crown ply to improve resistance against oxidation.broad,directional block tread.
- Good mileage potential ,excellent resistance to damage and punctures on/off road with longer wear life and serice life.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 12.00R24 | 8.5      | 20   | CPD90   | 160/157K | 4500          | 4125 | 315     | 1226    | 16      |



### CPT75

**Position: Trailer Position**

- Five deep circumferential grooves for excellent water evacuation and wet traction.
- Low heat sidewall design, even load distribution for longer mileage and reduced tire wear.
- Optimized bead area construction for better durability.

| Size        | RIM inch | P.R. | Pattern | L./S.R. | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|---------|---------------|------|---------|---------|---------|
|             |          |      |         |         | Single        | Dual |         |         |         |
| 385/65R22.5 | 11.75    | 20   | CPT75   | 160L    | 4500          | 4500 | 389     | 1071    | 15.5    |





## CPS68

**Position: All Position**

- Premium five-rib tread with silica compound features longer tire life with low rolling resistance.
- Latest technology carcass geometry and materials for enhanced damage resistance, durability and loading capacity.
- Computer aided carcass design helps improve footprint for better mileage performance.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 7.50R16  | 6.00G    | 14   | CPS68   | 122/118L | 1500          | 1320 | 215     | 800     | 13      |
| 11.00R20 | 8.0      | 18   | CPS68   | 152/149K | 3550          | 3250 | 288     | 1079    | 16      |



## CPS92

**Position: Trailer Position**

- Longer wear life & service life.
- Improved irregular wear resistance.
- Improved cut/chipping resistance.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 12.00R24 | 8.5      | 20   | CPS92   | 160/157K | 4500          | 4125 | 315     | 1226    | 16      |



## CPS93

**Position: Trailer Position**

- More mileage and greater lateral stability.
- Low heat tread design, even load distribution for longer mileage and reduced tire wear.
- Optimized bead area construction for better durability.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 12.00R24 | 8.5      | 18   | CPS93   | 158/155K | 4250          | 3875 | 315     | 1226    | 16      |
| 12.00R24 | 8.5      | 20   | CPS93   | 160/157K | 4500          | 4125 | 315     | 1226    | 16      |





# CPD80

**Position: Drive Position**

- Deep tread with stone drilling protectors to promote traction and floatation capacity on rough roads.
- Latest technology carcass materials for reinforcing bead and loading capacity.
- Special mining rubber compound for high resistance against tread cut.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 9.00R20  | 7.0      | 16   | CPD80   | 144/142G | 2800          | 2650 | 260     | 1027    | 20      |
| 10.00R20 | 7.5      | 18   | CPD80   | 149/146G | 3250          | 3000 | 278     | 1058    | 20      |
| 11.00R20 | 8.0      | 18   | CPD80   | 152/149G | 3550          | 3250 | 288     | 1094    | 23.8    |
| 12.00R20 | 8.5      | 20   | CPD80   | 156/153G | 4000          | 3650 | 309     | 1130    | 24      |



# CPD69

**Position: Drive Position**

- High-intensity casing carcass materials for reinforcing bead and loading capacity.
- Special rubber compound ensuring more resistance to cuts and tearing.
- Wide and depth pattern design help enhance traction and provide good turning stability.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 12.00R20 | 8.5      | 20   | CPD69   | 156/153K | 4000          | 3650 | 309     | 1121    | 19.5    |



# ON&OFF MIXED

## PRODUCT MANUALS



## CPS60

**Position: All Position**

- ▶ Latest technology carcass geometry and materials for enhanced damage resistance, durability and loading capacity.
- ▶ Premium zigzag design promotes soft soil mobility.
- ▶ Offset block shoulder design with silica compound promotes good traction and abrasion resistance.

| Size        | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|             |          |      |         |          | Single        | Dual |         |         |         |
| 7.50R16     | 6.00G    | 14   | CPS60   | 122/118L | 1500          | 1320 | 215     | 800     | 13      |
| 8.25R16     | 6.50H    | 16   | CPS60   | 128/124K | 1800          | 1600 | 225     | 848     | 11.5    |
| 8.25R20     | 6.5      | 16   | CPS60   | 139/137K | 2430          | 2300 | 234     | 970     | 15      |
| 9.00R20     | 7.0      | 16   | CPS60   | 144/142K | 2800          | 2650 | 260     | 1018    | 15.5    |
| 10.00R20    | 7.5      | 18   | CPS60   | 149/146K | 3250          | 3000 | 278     | 1051    | 16.5    |
| 11.00R20    | 8.0      | 18   | CPS60   | 152/149K | 3550          | 3250 | 288     | 1079    | 16      |
| 12.00R20    | 8.5      | 18   | CPS60   | 154/151K | 3750          | 3450 | 309     | 1115    | 16.3    |
| 12.00R20    | 8.5      | 20   | CPS60   | 156/153K | 4000          | 3650 | 309     | 1115    | 16.3    |
| 11R22.5     | 8.25     | 16   | CPS60   | 148/145M | 3150          | 2900 | 268     | 1054    | 14.5    |
| 12R22.5     | 9.00     | 18   | CPS60   | 152/149M | 3550          | 3250 | 300     | 1075    | 14.5    |
| 13R22.5     | 9.75     | 20   | CPS60   | 156/150L | 3750          | 3450 | 320     | 1124    | 15.5    |
| 11R24.5     | 8.25     | 16   | CPS60   | 149/146M | 3250          | 3000 | 279     | 1104    | 14.5    |
| 12.00R24    | 8.5      | 20   | CPS60   | 160/157K | 4500          | 4125 | 315     | 1226    | 15      |
| 315/80R22.5 | 9.00     | 20   | CPS60   | 156/150M | 4000          | 3350 | 312     | 1076    | 14.5    |
| 295/80R22.5 | 9.00     | 18   | CPS60   | 152/149M | 3550          | 3250 | 298     | 1044    | 14.5    |



## CPD85

**Position: Drive Position**

- ▶ Drive axle tire applicable for mud and sand terrain with short on high-way use.
- ▶ Wide tread and open shoulder blocks help enhance traction and braking on rough roads with mud or gravel.
- ▶ Special tread compounds resist chipping, chunking and tearing.

| Size        | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|             |          |      |         |          | Single        | Dual |         |         |         |
| 315/80R22.5 | 9.00     | 20   | CPD85   | 156/150K | 4000          | 3350 | 312     | 1076    | 18      |



## CPD83

**Position: Drive Position**

- ▶ Special pattern design provides good traction and driving capacity.
- ▶ Tough belt for smooth tread wear and longer mileage.
- ▶ Special compound for high resistance against tread cut.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 10.00R20 | 7.5      | 18   | CPD83   | 149/146K | 3250          | 3000 | 278     | 1054    | 18      |





# CPD82

**Position: Drive Position**

- Maximized traction in soft soil and mud through massive, open lateral shoulder grooves.
- Aggressive direction tread with robust tread blocks providing extra traction for on&off road condition.
- Special rubber compound ensuring more resistance to cuts and tearing.

| Size        | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|             |          |      |         |          | Single        | Dual |         |         |         |
| 11R22.5     | 8.25     | 16   | CPD82   | 148/145M | 3150          | 2900 | 268     | 1054    | 20      |
| 13R22.5     | 9.75     | 20   | CPD82   | 156/150K | 4000          | 3350 | 320     | 1124    | 20      |
| 295/80R22.5 | 9.00     | 18   | CPD82   | 152/149L | 3550          | 3250 | 298     | 1044    | 20      |
| 315/80R22.5 | 9.00     | 20   | CPD82   | 156/150K | 4000          | 3350 | 312     | 1076    | 20      |



# CPD26

**Position: Drive Position**

- Suitable to drive position of truck on rough road.
- Wide tread and open shoulder blocks help enhance traction and braking on rough roads with mud or gravel.
- Special tread compounds resist chipping, chunking and tearing.

| Size        | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|             |          |      |         |          | Single        | Dual |         |         |         |
| 11R22.5     | 8.25     | 16   | CPD26   | 148/145K | 3150          | 2900 | 268     | 1054    | 20      |
| 12R22.5     | 9.00     | 18   | CPD26   | 152/149K | 3550          | 3250 | 292     | 1086    | 18      |
| 315/80R22.5 | 9.00     | 20   | CPD26   | 156/150K | 4000          | 3350 | 312     | 1076    | 20      |



# CPS91

**Position: All Position**

- Special designed tread with silica compound features longer tire life with low rolling resistance.
- Low heat build-up, even load distribution for longer mileage and reduced tire wear.
- Optimized bead area construction for better durability.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 12.00R24 | 8.5      | 20   | CPS91   | 160/157K | 4500          | 4125 | 315     | 1226    | 16      |





## CPD68

**Position: Drive Position**

- Wide tread and open shoulder blocks help enhance traction and braking on rough roads with mud or gravel.
- Wide and depth pattern design with low heat generating formula provides good turning stability.
- Outstanding self-cleaning tread design ensures long-life service in ON/OFF road conditions.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 7.50R16  | 6.00G    | 14   | CPD68   | 122/118K | 1500          | 1320 | 215     | 806     | 16      |
| 8.25R16  | 6.50H    | 16   | CPD68   | 128/124K | 1800          | 1600 | 225     | 854     | 14.5    |
| 8.25R20  | 6.5      | 16   | CPD68   | 139/137J | 2430          | 2300 | 234     | 974     | 17      |
| 9.00R20  | 7.0      | 16   | CPD68   | 144/142K | 2800          | 2650 | 260     | 1025    | 18      |
| 10.00R20 | 7.5      | 18   | CPD68   | 149/146K | 3250          | 3000 | 278     | 1054    | 18      |
| 11.00R20 | 8.0      | 18   | CPD68   | 152/149K | 3550          | 3250 | 288     | 1084    | 18.5    |
| 12.00R20 | 8.5      | 20   | CPD68   | 156/153J | 4000          | 3650 | 309     | 1121    | 19.5    |



## CPT65

**Position: Trailer Position**

- Reinforced bead and body to strengthen the puncture resistance tear resistance.
- Suitable for mixed road conditions and relatively poor road condition.
- Open groove and bottom design given excellent self-cleaning performance.

| Size        | RIM inch | P.R. | Pattern | L./S.R. | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|---------|---------------|------|---------|---------|---------|
|             |          |      |         |         | Single        | Dual |         |         |         |
| 385/55R22.5 | 12.25    | 20   | CPT65   | 160L    | 4500          | 4500 | 383     | 999     | 17      |
| 385/65R22.5 | 11.75    | 20   | CPT65   | 160L    | 4500          | 4500 | 389     | 1074    | 17      |



## CPT69

**Position: All Position**

- Optimized carcass construction for better durability.
- High-intensity casing carcass materials for reinforcing bead and loading capacity.
- Offset block shoulder design with silica compound promotes good traction and abrasion resistance.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 9.00R20  | 7.0      | 16   | CPT69   | 144/142K | 2800          | 2650 | 260     | 1018    | 15.5    |
| 10.00R20 | 7.5      | 18   | CPT69   | 149/146K | 3250          | 3000 | 278     | 1051    | 16.5    |
| 11.00R20 | 8.0      | 18   | CPT69   | 152/149K | 3550          | 3250 | 288     | 1079    | 16      |
| 12.00R20 | 8.5      | 20   | CPT69   | 156/153K | 4000          | 3650 | 309     | 1115    | 16.5    |



# MINING

## PRODUCT MANUALS



### CPD86

**Position: Drive Position**

- High-intensity casing carcass materials for reinforcing bead and loading capacity.
- Extra deep tread with stone drilling protectors to promote traction and long original mileage.
- Special rubber compound ensuring more resistance to cuts and tearing.

| Size        | RIM inch | P.R. | Pattern | L.I./S.R. | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|-------------|----------|------|---------|-----------|---------------|------|---------|---------|---------|
|             |          |      |         |           | Single        | Dual |         |         |         |
| 11R22.5     | 8.25     | 16   | CPD86   | 146/143K  | 3000          | 2725 | 268     | 1054    | 22      |
| 12R22.5     | 9.00     | 18   | CPD86   | 152/149K  | 3550          | 3250 | 300     | 1090    | 22      |
| 13R22.5     | 9.75     | 20   | CPD86   | 156/150K  | 4000          | 3650 | 320     | 1124    | 22      |
| 11.00R20    | 8.0      | 18   | CPD86   | 152/149G  | 3550          | 3250 | 293     | 1085    | 21      |
| 12.00R20    | 8.5      | 20   | CPD86   | 156/153G  | 4000          | 3650 | 309     | 1125    | 22      |
| 12.00R24    | 8.5      | 20   | CPD86   | 160/157K  | 4500          | 4125 | 315     | 1226    | 22      |
| 295/80R22.5 | 9.00     | 18   | CPD86   | 152/149K  | 3550          | 3250 | 292     | 1045    | 20      |



### CPD80+

**Position: Drive Position**

- Extra deep tread with stone drilling protectors to promote traction and floatation capacity on rough roads.
- Latest technology carcass materials for reinforcing bead and loading capacity.
- Special rubber compound for high resistance against tread cut.

| Size     | RIM inch | P.R. | Pattern | L.I./S.R. | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|-----------|---------------|------|---------|---------|---------|
|          |          |      |         |           | Single        | Dual |         |         |         |
| 8.25R16  | 6.50H    | 16   | CPD80+  | 128/124G  | 1800          | 1600 | 225     | 861     | 18      |
| 8.25R20  | 6.5      | 16   | CPD80+  | 139/137G  | 2430          | 2300 | 234     | 978     | 19      |
| 12.00R20 | 8.5      | 20   | CPD80+  | 156/153G  | 4000          | 3650 | 309     | 1130    | 24      |





## CPD80

**Position: Drive Position**

- Deep tread with stone drilling protectors to promote traction and floatation capacity on rough roads.
- Latest technology carcass materials for reinforcing bead and loading capacity.
- Special mining rubber compound for high resistance against tread cut.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 9.00R20  | 7.0      | 16   | CPD80   | 144/142G | 2800          | 2650 | 260     | 1027    | 20      |
| 10.00R20 | 7.5      | 18   | CPD80   | 149/146G | 3250          | 3000 | 278     | 1058    | 20      |
| 11.00R20 | 8.0      | 18   | CPD80   | 152/149G | 3550          | 3250 | 288     | 1094    | 23.8    |
| 12.00R20 | 8.5      | 20   | CPD80   | 156/153G | 4000          | 3650 | 309     | 1130    | 24      |



## CPD69

**Position: Drive Position**

- High-intensity casing carcass materials for reinforcing bead and loading capacity.
- Special rubber compound ensuring more resistance to cuts and tearing.
- Wide and depth pattern design help enhance traction and provide good turning stability.

| Size     | RIM inch | P.R. | Pattern | L./S.R.  | Max load (kg) |      | S.W. mm | O.D. mm | T.D. mm |
|----------|----------|------|---------|----------|---------------|------|---------|---------|---------|
|          |          |      |         |          | Single        | Dual |         |         |         |
| 12.00R20 | 8.5      | 20   | CPD69   | 156/153K | 4000          | 3650 | 309     | 1121    | 19.5    |