

KETER TYRE

WWW.KETERTYRE.COM



QINGDAO KETER TYRE CO., LTD

ADD: A-2502, Darron Center, No.180 Haier Road, Qingdao, China, 266100

Tel: 86-532-55579147, 86-532-55579148

Fax: 86-532-55579145 E-mail: info@ketertyre.com





FOUR SEASONS



TOUR-X

- Tiny grooves, less noise & rolling resistance.
- Better braking, higher safety.
- Excellent grip & traction on snowy & icy roads.



| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|------------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 13 | 155/70R13 | 75 T | 4½J | 548 / 21.6 | 157 / 6.2 | 8.0 / 10.0 |
| 14 | 165/70R14 | 81 T | 5J | 588 / 23.1 | 170 / 6.7 | 7.6 / 9.5 |
| 14 | 175/65R14 | 82 T | 5J | 584 / 23.0 | 177 / 7.0 | 7.6 / 9.5 |
| 14 | 175/70R14 | 88/XL T | 5J | 602 / 23.7 | 177 / 7.0 | 7.6 / 9.5 |
| 15 | 175/65R15 | 84 H | 5J | 609 / 24.0 | 177 / 7.0 | 7.6 / 9.5 |
| 15 | 185/55R15 | 86/XL H | 6J | 585 / 23.0 | 194 / 7.6 | 8.0 / 10.0 |
| 15 | 185/60R15 | 88/XL H | 5½J | 603 / 23.7 | 189 / 7.4 | 7.6 / 9.5 |
| 15 | 185/65R15 | 88 H | 5½J | 621 / 24.4 | 189 / 7.4 | 7.6 / 9.5 |
| 15 | 195/60R15 | 88 H | 6J | 615 / 24.2 | 201 / 7.9 | 7.6 / 9.5 |
| 15 | 195/65R15 | 91 H | 6J | 635 / 25.0 | 201 / 7.9 | 7.6 / 9.5 |
| 15 | 195/65R15 | 95/XL H | 6J | 635 / 25.0 | 201 / 7.9 | 7.6 / 9.5 |
| 16 | 195/55R16 | 91XL V | 6J | 620 / 24.4 | 201 / 7.9 | 8.0 / 10.0 |
| 16 | 205/55R16 | 91 V | 6½J | 632 / 24.9 | 214 / 8.4 | 8.0 / 10.0 |
| 16 | 205/55R16 | 94XL V | 6½J | 632 / 24.9 | 214 / 8.4 | 8.0 / 10.0 |
| 16 | 205/60R16 | 96XL V | 6J | 652 / 25.7 | 209 / 8.2 | 8.0 / 10.0 |
| 17 | 225/45ZR17 | 94/XL W | 7½J | 634 / 25.0 | 225 / 8.9 | 8.0 / 10.0 |
| 18 | 225/40ZR18 | 92/XL W | 8J | 637 / 25.1 | 230 / 9.1 | 8.0 / 10.0 |





KT777

UTQG: 320AA

- Wide grooves in the center, excellent handling in wetland
- Internal longitudinal and transverse grooves, faster drainage
- Asymmetric pattern design, good performance in drainage and handling



| SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds | |
|------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|------------|
| 16 | 195/55RF16 | 87 V | 6J | 620 / 24.4 | 201 / 7.9 | 8.0 / 10.0 |
| 16 | 205/55RF16 | 91 V | 6½J | 632 / 24.9 | 214 / 8.4 | 8.0 / 10.0 |
| 17 | 205/45ZRF17 | 84 W | 7J | 616 / 24.3 | 206 / 8.1 | 8.0 / 10.0 |
| 17 | 205/50ZRF17 | 89 W | 6½J | 638 / 25.1 | 214 / 8.4 | 8.0 / 10.0 |
| 17 | 225/50ZRF17 | 94 W | 7J | 658 / 25.9 | 233 / 9.2 | 8.0 / 10.0 |
| 17 | 225/55ZRF17 | 97 W | 7J | 680 / 26.8 | 233 / 9.2 | 8.0 / 10.0 |
| 17 | 225/45ZRF17 | 91 W | 7½J | 634 / 25.0 | 225 / 8.9 | 8.0 / 10.0 |
| 17 | 235/55ZRF17 | 99 W | 7½J | 690 / 27.2 | 245 / 9.6 | 8.0 / 10.0 |

| SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds | |
|------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|------------|
| 18 | 215/55RF18 | 95 V | 7J | 693 / 27.3 | 226 / 8.9 | 8.0 / 10.0 |
| 18 | 225/45ZRF18 | 91 W | 7½J | 659 / 25.9 | 225 / 8.9 | 8.0 / 10.0 |
| 18 | 235/50RF18 | 97 V | 7½J | 693 / 27.3 | 245 / 9.6 | 7.8 / 10.0 |
| 18 | 235/55RF18 | 100 V | 7½J | 715 / 28.1 | 245 / 9.6 | 8.0 / 10.0 |
| 18 | 245/50ZRF18 | 100 W | 7½J | 703 / 27.7 | 253 / 10.0 | 8.0 / 10.0 |
| 18 | 245/45ZRF18 | 96 W | 8J | 677 / 26.7 | 243 / 9.6 | 8.0 / 10.0 |
| 19 | 245/45ZRF19 | 98 W | 8J | 703 / 27.7 | 243 / 9.6 | 8.0 / 10.0 |
| 19 | 285/45RF19 | 107 V | 9½J | 739 / 29.1 | 285 / 11.2 | 8.0 / 10.0 |



KT779

UTQG: 420AA

- Special shoulder design, better control for high-speed turning.
- The rib design in the middle greatly improving control and braking performance.
- S-type narrow belt design, better serve driving comfort



| SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds | |
|------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|------------|
| 18 | 225/60RF18 | 100 V | 6½J | 727 / 28.6 | 228 / 9.0 | 8.3 / 10.5 |
| 18 | 235/60RF18 | 103 V | 7J | 739 / 29.1 | 240 / 9.4 | 8.3 / 10.5 |

RUN FLAT TYRE





KT877

- 8mm deeper pattern design guarantee long mileage
- Double carcass design meet long-term stable use requirements
- Super wear resistant formula



SIZE

16

215/60R16

LOAD INDEX/
SPEED CODE
95 VSTANDARD
RIM
6½JOVERALL DIA
(mm)/inch
664 / 26.1SECTION WIDTH
(mm)/inch
221 / 8.7O.T.D
(mm)/32nds
8.0 / 10.1

TAXI



MUD TERRAIN



KT666

- Excellent slip resistance
- Good traction performance
- Avoiding groove crack



| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/3.2nds |
|----|---------------|---------------------------|-----------------|--------------------------|----------------------------|----------------------|
| 15 | LT235/75R15 | 104/101 S | 6½J | 733 / 28.9 | 235 / 9.3 | 13.4 / 17.0 |
| 16 | LT245/75R16 | 108/104 Q | 7J | 780 / 30.7 | 248 / 9.8 | 13.6 / 17.0 |
| 16 | LT265/70R16 | 117/114 Q | 8J | 784 / 30.9 | 272 / 10.7 | 14.6 / 18.5 |
| 16 | LT265/75R16 | 123/120 Q | 7½J | 804 / 31.7 | 267 / 10.5 | 12.3 / 15.5 |
| 16 | LT285/75R16 | 126/123 R | 8J | 840 / 33.1 | 286 / 11.3 | 14.6 / 18.5 |
| 17 | LT285/70R17 | 121/118 R | 8½J | 838 / 33.0 | 292 / 11.5 | 14.6 / 18.5 |
| 17 | LT265/70R17 | 121/118 Q | 8J | 810 / 31.9 | 272 / 10.7 | 14.6 / 18.5 |
| 17 | LT265/65R17 | 120/117 S | 8J | 782 / 30.8 | 272 / 10.7 | 14.6 / 18.5 |
| 17 | LT295/70R17 | 121/118 Q | 8½J | 852 / 33.5 | 299 / 11.8 | 14.8 / 18.6 |
| 20 | LT275/65R20 | 126/123 Q | 8J | 872 / 34.3 | 279 / 11.0 | 14.6 / 18.5 |
| 15 | 30×9.50R15LT | 104 Q | 7½J | 756 / 29.8 | 240 / 9.4 | 13.4 / 17.0 |
| 15 | 31×10.50R15LT | 109 Q | 8½J | 781 / 30.7 | 268 / 10.6 | 13.6 / 17.0 |
| 15 | 33×12.5R15LT | 108 Q | 10J | 832 / 32.8 | 318 / 12.5 | 14.6 / 18.5 |
| 17 | 35×12.50R17LT | 121 Q | 10J | 877 / 34.5 | 318 / 12.5 | 16.3 / 20.5 |
| 18 | 33×12.50R18LT | 118 Q | 10J | 826 / 32.5 | 318 / 12.5 | 16.3 / 20.5 |
| 18 | 35×12.50R18LT | 118 Q | 10J | 877 / 34.5 | 318 / 12.5 | 16.3 / 20.5 |
| 20 | 33×12.50R20LT | 114 Q | 10J | 832 / 32.8 | 318 / 12.5 | 16.3 / 20.5 |
| 20 | 35×12.50R20LT | 121 Q | 10J | 883 / 34.8 | 318 / 12.5 | 16.3 / 20.5 |



ALL TERRAIN



KT787

UTQG: 500AA

- "Big Shoulder Block" Design
- Tiger Tooth Bionic Tread Pattern Design
- Special 3D Groove and shoulder reinforcement Design



| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|---------------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 16 | 235/70R16 | 106 S | 7J | 736 / 29.0 | 240 / 9.4 | 10.8 / 13.5 |
| 16 | 245/70R16 | 111/XL T | 7J | 750 / 29.5 | 248 / 9.8 | 10.8 / 13.5 |
| 16 | 255/70R16 | 111 T | 7½J | 764 / 30.1 | 260 / 10.2 | 10.8 / 13.5 |
| 16 | 265/70R16 | 112 S | 8J | 778 / 30.6 | 272 / 10.7 | 10.8 / 13.5 |
| 17 | 265/65R17 | 112 S | 8J | 776 / 30.6 | 272 / 10.7 | 10.8 / 13.5 |
| 17 | 275/65R17 | 115 S | 8J | 790 / 31.1 | 279 / 11.0 | 10.8 / 13.5 |
| 18 | 265/60R18 | 110 H | 8J | 775 / 30.5 | 272 / 10.7 | 10.3 / 13.0 |
| 18 | 285/60R18 | 116 H | 8½J | 799 / 31.5 | 292 / 11.5 | 10.1 / 12.5 |
| 20 | 265/50R20 | 111/XL V | 8½J | 774 / 30.5 | 277 / 10.9 | 9.6 / 12.0 |
| 20 | 285/50R20 | 116/XL V | 9J | 794 / 31.3 | 297 / 11.7 | 10.8 / 13.5 |
| LT | 30×9.50R15LT | 104 S | 7½J | 750 / 29.5 | 240 / 9.4 | 10.8 / 13.5 |
| LT | 31×10.50R15LT | 109 Q | 8½J | 775 / 30.5 | 268 / 10.6 | 11.6 / 14.5 |
| LT | 215/75R15LT | 100/97 S | 6J | 703 / 27.7 | 216 / 8.5 | 10.8 / 13.5 |
| LT | LT235/85R16 | 120/116 S | 6½J | 806 / 31.7 | 235 / 9.3 | 10.8 / 13.5 |
| LT | LT245/75R16 | 108/104 S | 7J | 774 / 30.5 | 248 / 9.8 | 10.8 / 13.5 |
| LT | LT265/75R16 | 123/120 S | 7½J | 804 / 31.7 | 267 / 10.5 | 10.8 / 13.5 |
| LT | LT285/75R16 | 126/123 R | 8J | 834 / 32.8 | 286 / 11.3 | 10.8 / 13.5 |
| LT | LT265/70R17 | 121/118 S | 8J | 804 / 31.7 | 272 / 10.7 | 10.8 / 13.5 |
| LT | LT285/70R17 | 121/118 R | 8½J | 832 / 32.8 | 292 / 11.5 | 10.8 / 13.5 |



WINTER



KN966

- Upgraded Technology and Formula
- Strong Grip Performance Excellent Braking Ability
- Good handling stability and drainage performance on snow covered road.



| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|-----------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 13 | 155/65R13 | 73 Q | 4.50B/4½J | 532 / 20.9 | 157 / 6.2 | 9.1 / 11.5 |
| 13 | 165/65R13 | 77 Q | 5.00B/5J | 544 / 21.4 | 170 / 6.7 | 9.1 / 11.5 |
| 13 | 165/70R13 | 83/XL Q | 5.00B/5J | 562 / 22.1 | 170 / 6.7 | 9.1 / 11.5 |
| 13 | 175/60R13 | 77 Q | 5.00B/5J | 540 / 21.3 | 177 / 7.0 | 9.1 / 11.5 |
| 13 | 175/70R13 | 82 Q | 5.00B/5J | 576 / 22.7 | 177 / 7.0 | 9.1 / 11.5 |
| 14 | 155/65R14 | 75 Q | 4½J/4.50B | 558 / 22.0 | 157 / 6.2 | 9.1 / 11.5 |
| 14 | 165/60R14 | 75 Q | 5.00B/5J | 554 / 21.8 | 170 / 6.7 | 9.1 / 11.5 |
| 14 | 165/70R14 | 85/XL Q | 5J/5.00B | 588 / 23.1 | 170 / 6.7 | 9.1 / 11.5 |
| 14 | 175/60R14 | 79 Q | 5.00B/5J | 566 / 22.3 | 177 / 7.0 | 9.1 / 11.5 |
| 14 | 175/65R14 | 82 Q | 5.00B/5J | 584 / 23.0 | 177 / 7.0 | 9.1 / 11.5 |
| 14 | 175/70R14 | 88/XL Q | 5.00B/5J | 602 / 23.7 | 177 / 7.0 | 9.1 / 11.5 |
| 14 | 185/60R14 | 82 Q | 5½J | 578 / 22.8 | 189 / 7.4 | 9.1 / 11.5 |
| 14 | 185/65R14 | 90/XL Q | 5½J | 596 / 23.5 | 189 / 7.4 | 9.1 / 11.5 |
| 14 | 185/70R14 | 88 Q | 5½J | 616 / 24.3 | 189 / 7.4 | 9.1 / 11.5 |
| 14 | 195/60R14 | 86 Q | 6J | 590 / 23.2 | 201 / 7.9 | 9.1 / 11.5 |
| 15 | 175/65R15 | 84 Q | 5J | 609 / 24.0 | 177 / 7.0 | 9.1 / 11.5 |
| 15 | 185/55R15 | 86/XL Q | 6J | 585 / 23.0 | 194 / 7.6 | 9.1 / 11.5 |
| 15 | 185/60R15 | 84 Q | 5½J | 603 / 23.7 | 189 / 7.4 | 9.1 / 11.5 |
| 15 | 185/65R15 | 88 Q | 5½J | 621 / 24.4 | 189 / 7.4 | 9.1 / 11.5 |
| 15 | 195/55R15 | 85 Q | 6J | 595 / 23.4 | 201 / 7.9 | 9.1 / 11.5 |
| 15 | 195/60R15 | 88 Q | 6J | 615 / 24.2 | 201 / 7.9 | 9.1 / 11.5 |
| 15 | 195/65R15 | 91 Q | 6J | 635 / 25.0 | 201 / 7.9 | 9.1 / 11.5 |
| 15 | 205/65R15 | 94 Q | 6J | 647 / 25.5 | 209 / 8.2 | 9.1 / 11.5 |
| 15 | 205/70R15 | 96 Q | 6J | 669 / 26.3 | 209 / 8.2 | 9.1 / 11.5 |
| 16 | 195/60R16 | 89 Q | 6J | 640 / 25.2 | 201 / 7.9 | 9.1 / 11.5 |
| 16 | 205/55R16 | 91 Q | 6½J | 632 / 24.9 | 214 / 8.4 | 9.1 / 11.5 |
| 16 | 205/60R16 | 92 Q | 6J | 652 / 25.7 | 209 / 8.2 | 9.1 / 11.5 |
| 16 | 205/65R16 | 95 Q | 6J | 672 / 26.5 | 209 / 8.2 | 9.1 / 11.5 |

| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|-----------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 16 | 215/70R16 | 100 Q | 6½J | 708 / 27.9 | 221 / 8.7 | 9.1 / 11.5 |
| 17 | 215/50R17 | 95/XL S | 7J | 648 / 25.5 | 226 / 8.9 | 9.1 / 11.5 |
| 17 | 215/55R17 | 94 S | 7J | 668 / 26.3 | 226 / 8.9 | 9.1 / 11.5 |
| 17 | 215/60R17 | 96 S | 6½J | 690 / 27.2 | 221 / 8.7 | 9.1 / 11.5 |
| 17 | 225/50R17 | 98/XL S | 7J | 658 / 25.9 | 233 / 9.2 | 9.1 / 11.5 |
| 17 | 225/55R17 | 97 S | 7J | 680 / 26.8 | 233 / 9.2 | 9.1 / 11.5 |
| 17 | 225/60R17 | 103/XL S | 6½J | 702 / 27.6 | 228 / 9.0 | 9.1 / 11.5 |
| 17 | 225/65R17 | 102 S | 6½J | 724 / 28.5 | 228 / 9.0 | 9.1 / 11.5 |
| 17 | 235/45R17 | 97/XL S | 8J | 644 / 25.4 | 236 / 9.3 | 9.1 / 11.5 |
| 17 | 235/50R17 | 100/XL S | 7½J | 668 / 26.3 | 245 / 9.6 | 9.1 / 11.5 |
| 17 | 235/55R17 | 103/XL S | 7½J | 690 / 27.2 | 245 / 9.6 | 9.1 / 11.5 |
| 17 | 235/65R17 | 104 S | 7J | 738 / 29.1 | 240 / 9.4 | 9.1 / 11.5 |
| 17 | 245/65R17 | 111/XL S | 7J | 750 / 29.5 | 248 / 9.8 | 9.1 / 11.5 |
| 17 | 255/45R17 | 102/XL S | 8½J | 662 / 26.1 | 255 / 10.0 | 9.1 / 11.5 |
| 17 | 265/65R17 | 112 S | 8J | 776 / 30.6 | 272 / 10.7 | 9.1 / 11.5 |
| 18 | 215/55R18 | 99/XL S | 7J | 693 / 27.3 | 226 / 8.9 | 9.1 / 11.5 |
| 18 | 225/45R18 | 95/XL S | 7½J | 659 / 25.9 | 225 / 8.9 | 9.1 / 11.5 |
| 18 | 225/60R18 | 104/XL S | 6½J | 727 / 28.6 | 228 / 9.0 | 9.1 / 11.5 |
| 18 | 235/50R18 | 101/XL S | 7½J | 693 / 27.3 | 245 / 9.6 | 9.1 / 11.5 |
| 18 | 235/55R18 | 104/XL S | 7½J | 715 / 28.1 | 245 / 9.6 | 9.1 / 11.5 |
| 18 | 235/60R18 | 107/XL S | 7J | 739 / 29.1 | 240 / 9.4 | 9.1 / 11.5 |
| 18 | 245/45R18 | 100/XL S | 8J | 677 / 26.7 | 243 / 9.6 | 9.1 / 11.5 |
| 18 | 265/60R18 | 114/XL S | 8J | 775 / 30.5 | 272 / 10.7 | 9.1 / 11.5 |
| 19 | 235/55R19 | 101 T | 7½J | 741 / 29.2 | 245 / 9.6 | 9.1 / 11.5 |
| 19 | 245/55R19 | 103 S | 7½J | 753 / 29.6 | 253 / 10.0 | 9.1 / 11.5 |
| 19 | 255/50R19 | 103 T | 8J | 739 / 29.1 | 265 / 10.4 | 9.1 / 11.5 |
| 20 | 275/45R20 | 110/XL L | 9J | 756 / 29.8 | 273 / 10.7 | 9.1 / 11.5 |



KN989

- Quick drainage pattern design
- More balanced performance
- Cold weather tread compound



| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch |
|----|-----------|---------------------------|-----------------|--------------------------|----------------------------|
| 13 | 165/70R13 | 83/XL T | 5J | 562 / 22.1 | 170 / 6.7 |
| 13 | 175/70R13 | 82 T | 5J | 576 / 22.7 | 177 / 7.0 |
| 14 | 165/70R14 | 85/XL T | 5J | 588 / 23.1 | 170 / 6.7 |
| 14 | 175/65R14 | 86/XL T | 5J | 584 / 23.0 | 177 / 7.0 |
| 14 | 175/70R14 | 88/XL T | 5J | 602 / 23.7 | 177 / 7.0 |
| 14 | 185/60R14 | 86/XL T | 5½J | 578 / 22.8 | 189 / 7.4 |
| 14 | 185/65R14 | 86 T | 5½J | 596 / 23.5 | 189 / 7.4 |
| 14 | 185/70R14 | 88 T | 5½J | 616 / 24.3 | 189 / 7.4 |
| 15 | 185/65R15 | 88 T | 5½J | 621 / 24.4 | 189 / 7.4 |
| 15 | 195/60R15 | 88 T | 6J | 615 / 24.2 | 201 / 7.9 |
| 15 | 195/65R15 | 95/XL T | 6J | 635 / 25.0 | 201 / 7.9 |
| 15 | 205/65R15 | 99/XL T | 6J | 647 / 25.5 | 209 / 8.2 |
| 19 | 255/40R19 | 100/XL V | 9J | 687 / 27.0 | 260 / 10.2 |



KN999

- Upgraded formula for icy and snowy roads
- Three longitudinal tread grooves, higher safety on slippery roads
- Herring Bone Pattern design for better grip ability



| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|-----------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 15 | 185/55R15 | 86/XL H | 6J | 585 / 23.0 | 194 / 7.6 | - |
| 15 | 195/50R15 | 82 H | 6J | 577 / 22.7 | 201 / 7.9 | 8.3 / 10.5 |
| 15 | 195/55R15 | 85 H | 6J | 595 / 23.4 | 201 / 7.9 | - |
| 16 | 195/55R16 | 87 H | 6J | 620 / 24.4 | 201 / 7.9 | 8.3 / 10.5 |
| 16 | 205/60R16 | 96/XL H | 6J | 652 / 25.7 | 209 / 8.2 | - |
| 16 | 215/65R16 | 98 H | 6½J | 686 / 27.0 | 221 / 8.7 | - |
| 16 | 215/60R16 | 99/XL H | 6½J | 664 / 26.1 | 221 / 8.7 | - |
| 16 | 215/55R16 | 97/XL H | 7J | 642 / 25.3 | 226 / 8.9 | - |
| 16 | 225/55R16 | 99/XL H | 7J | 654 / 25.7 | 233 / 9.2 | - |
| 16 | 225/60R16 | 102/XL H | 6½J | 676 / 26.6 | 228 / 9.0 | - |
| 16 | 235/60R16 | 100 H | 7J | 688 / 27.1 | 240 / 9.4 | 8.8 / 11.0 |
| 17 | 205/50R17 | 93/XL V | 6½J | 638 / 25.1 | 214 / 8.4 | 8.8 / 11.0 |
| 17 | 225/45R17 | 94/XL V | 7½J | 634 / 25.0 | 225 / 8.9 | 8.3 / 10.5 |
| 18 | 225/40R18 | 92/XL V | 8J | 637 / 25.1 | 230 / 9.1 | 8.3 / 10.5 |
| 18 | 235/40R18 | 95/XL V | 8½J | 645 / 25.4 | 241 / 9.5 | 8.3 / 10.5 |
| 18 | 245/40R18 | 97/XL V | 8½J | 653 / 25.7 | 248 / 9.8 | 8.3 / 10.5 |
| 19 | 255/40R19 | 100/XL V | 9J | 687 / 27.0 | 260 / 10.2 | 8.3 / 10.5 |



SUMMER



KT616

UTQG: 500AA

- Better heat release
- Effective drainage performance
- Good driving stability



| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|------------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 15 | 235/75R15 | 109/XL T | 6½J | 733 / 28.9 | 235 / 9.3 | 8.3 / 10.5 |
| 16 | 215/70R16 | 100 T | 6½J | 708 / 27.9 | 221 / 8.7 | 8.3 / 10.5 |
| 16 | 225/65R16 | 100 T | 6½J | 698 / 27.5 | 228 / 9.0 | 8.3 / 10.5 |
| 16 | 225/70R16 | 103 T | 6½J | 722 / 28.4 | 228 / 9.0 | 8.3 / 10.5 |
| 16 | 235/65R16 | 103 T | 7J | 712 / 28.0 | 240 / 9.4 | 8.3 / 10.5 |
| 16 | 235/70R16 | 106 T | 7J | 736 / 29.0 | 240 / 9.4 | 8.3 / 10.5 |
| 16 | 245/70R16 | 111/XL T | 7J | 750 / 29.5 | 248 / 9.8 | 8.3 / 10.5 |
| 16 | 255/70R16 | 111 T | 7½J | 764 / 30.1 | 260 / 10.2 | 8.3 / 10.5 |
| 16 | 265/70R16 | 112 T | 8J | 778 / 30.6 | 272 / 10.7 | 8.3 / 10.5 |
| 17 | 215/60R17 | 96 H | 6½J | 690 / 27.2 | 221 / 8.7 | 8.3 / 10.5 |
| 17 | 215/65R17 | 99 T | 6½J | 712 / 28.0 | 221 / 8.7 | 8.3 / 10.5 |
| 17 | 225/60R17 | 99 H | 6½J | 702 / 27.6 | 228 / 9.0 | 8.3 / 10.5 |
| 17 | 225/65R17 | 102 T | 6½J | 724 / 28.5 | 228 / 9.0 | 8.3 / 10.5 |
| 17 | 235/50ZR17 | 96 W | 7½J | 668 / 26.3 | 245 / 9.6 | 8.3 / 10.5 |
| 17 | 235/60R17 | 102 H | 7J | 714 / 28.1 | 240 / 9.4 | 8.3 / 10.5 |
| 17 | 255/60R17 | 106 T | 7½J | 738 / 29.1 | 260 / 10.2 | 8.3 / 10.5 |
| 17 | 245/65R17 | 107 T | 7J | 750 / 29.5 | 248 / 9.8 | 8.3 / 10.5 |
| 17 | 245/70R17 | 110 T | 7J | 776 / 30.6 | 248 / 9.8 | 8.3 / 10.5 |
| 17 | 265/65R17 | 112 T | 8J | 776 / 30.6 | 272 / 10.7 | 8.1 / 10.2 |
| 17 | 265/70R17 | 115 T | 8J | 804 / 31.7 | 272 / 10.7 | 8.3 / 10.5 |

| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|---------------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 17 | 285/65R17 | 116 T | 8½J | 802 / 31.6 | 292 / 11.5 | 8.3 / 10.5 |
| 18 | 225/50ZR18 | 95 W | 7J | 683 / 26.9 | 233 / 9.2 | 8.3 / 10.5 |
| 18 | 225/55R18 | 98 V | 7J | 705 / 27.8 | 233 / 9.2 | 8.3 / 10.5 |
| 18 | 225/60R18 | 104/XL V | 6½J | 727 / 28.6 | 228 / 9.0 | 8.3 / 10.5 |
| 18 | 235/50ZR18 | 97 W | 7½J | 693 / 27.3 | 245 / 9.6 | 8.3 / 10.5 |
| 18 | 235/60R18 | 107/XL V | 7J | 739 / 29.1 | 240 / 9.4 | 8.3 / 10.5 |
| 18 | 235/65R18 | 106 T | 7J | 763 / 30.0 | 240 / 9.4 | 8.3 / 10.5 |
| 18 | 255/70R18 | 113 T | 7½J | 815 / 32.1 | 260 / 10.2 | 8.3 / 10.5 |
| 18 | 265/60R18 | 110 H | 8J | 775 / 30.5 | 272 / 10.7 | 8.3 / 10.5 |
| 18 | 265/70R18 | 116 T | 8J | 829 / 32.6 | 272 / 10.7 | 8.3 / 10.5 |
| 18 | 275/70R18 | 116 T | 8J | 843 / 33.2 | 279 / 11.0 | 8.3 / 10.5 |
| 20 | 285/50R20 | 116/XL V | 9J | 794 / 31.3 | 297 / 11.7 | 8.1 / 10.2 |
| LT | LT215/85R16 | 110/107 S | 6J | 772 / 30.4 | 216 / 8.5 | 9.0 / 11.3 |
| LT | LT225/75R16 | 115/112 S | 6J | 744 / 29.3 | 223 / 8.8 | 9.0 / 11.3 |
| LT | LT235/85R16 | 120/116 S | 6½J | 806 / 31.7 | 235 / 9.3 | 9.0 / 11.3 |
| LT | LT245/75R16 | 120/116 S | 7J | 774 / 30.5 | 248 / 9.8 | 9.0 / 11.3 |
| LT | LT265/75R16 | 123/120 S | 7½J | 804 / 31.7 | 267 / 10.5 | 9.0 / 11.3 |
| LT | LT245/75R17 | 121/118 S | 7J | 800 / 31.5 | 248 / 9.8 | 9.0 / 11.3 |
| LT | 31×10.50R15LT | 109 S | 8½J | 775 / 30.5 | 268 / 10.6 | 9.0 / 11.3 |



KT626

UTQG: 420AA

- Good handling ability
- Effective drainage performance
- Better wear resistance



| SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds | |
|------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|-----------|
| 13 | 165/65R13 | 77 T | 5.00B/5J | 544 / 21.4 | 170 / 6.7 | 7.0 / 8.8 |
| 13 | 165/70R13 | 79 T | 5.00B/5J | 562 / 22.1 | 170 / 6.7 | 7.0 / 8.8 |
| 13 | 175/70R13 | 82 T | 5.00B/5J | 576 / 22.7 | 177 / 7.0 | 7.0 / 8.8 |
| 13 | 185/70R13 | 86 H | 5.00B/5½J | 590 / 23.2 | 189 / 7.4 | 7.0 / 8.8 |
| 14 | 165/60R14 | 75 H | 5J | 554 / 21.8 | 170 / 6.7 | 7.0 / 8.8 |
| 14 | 165/65R14 | 79 T | 5J | 570 / 22.4 | 170 / 6.7 | 7.0 / 8.8 |
| 14 | 165/70R14 | 81 T | 5J | 588 / 23.1 | 170 / 6.7 | 7.0 / 8.8 |
| 14 | 175/65R14 | 86/XL T | 5J | 584 / 23.0 | 177 / 7.0 | 7.0 / 8.8 |
| 14 | 175/65R14 | 82 T | 5J | 584 / 23.0 | 177 / 7.0 | 7.0 / 8.8 |
| 14 | 175/70R14 | 84 T | 5J | 602 / 23.7 | 177 / 7.0 | 7.0 / 8.8 |
| 14 | 185/55R14 | 80 H | 6J | 560 / 22.0 | 194 / 7.6 | 7.0 / 8.8 |
| 14 | 185/60R14 | 82 H | 5½J | 578 / 22.8 | 189 / 7.4 | 7.0 / 8.8 |
| 14 | 185/65R14 | 86 H | 5½J | 596 / 23.5 | 189 / 7.4 | 7.0 / 8.8 |
| 14 | 185/70R14 | 88 H | 5½J | 616 / 24.3 | 189 / 7.4 | 7.0 / 8.8 |
| 14 | 195/70R14 | 91 H | 6J | 630 / 24.8 | 201 / 7.9 | 7.0 / 8.8 |
| 14 | 205/70R14 | 95 H | 6J | 644 / 25.4 | 209 / 8.2 | 7.0 / 8.8 |
| 15 | 185/55R15 | 82 V | 6J | 585 / 23.0 | 185 / 7.6 | 7.3 / 9.2 |
| 15 | 185/60R15 | 84 H | 5½J | 603 / 23.7 | 189 / 7.4 | 7.3 / 9.2 |
| 15 | 185/65R15 | 88 H | 5½J | 621 / 24.4 | 189 / 7.4 | 7.3 / 9.2 |
| 15 | 195/50R15 | 82 V | 6J | 577 / 22.7 | 195 / 7.9 | 7.3 / 9.2 |

| SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds | |
|------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|-----------|
| 15 | 195/55R15 | 85 V | 6J | 595 / 23.4 | 201 / 7.9 | 7.3 / 9.2 |
| 15 | 195/60R15 | 88 V | 6J | 615 / 24.2 | 195 / 7.9 | 7.3 / 9.2 |
| 15 | 195/65R15 | 91 V | 6J | 635 / 25.0 | 195 / 7.9 | 7.3 / 9.2 |
| 15 | 195/65R15 | 91 H | 6J | 635 / 25.0 | 195 / 7.9 | 7.3 / 9.2 |
| 15 | 205/60R15 | 91 V | 6J | 627 / 24.7 | 209 / 8.2 | 7.3 / 9.2 |
| 15 | 205/65R15 | 94 V | 6J | 647 / 25.5 | 205 / 8.2 | 7.3 / 9.2 |
| 15 | 205/70R15 | 96 H | 6J | 669 / 26.3 | 209 / 8.2 | 7.3 / 9.2 |
| 15 | 215/65R15 | 96 H | 6½J | 661 / 26.0 | 211 / 8.3 | 7.3 / 9.2 |
| 15 | 215/75R15 | 100 T | 6J | 683 / 26.9 | 215 / 8.7 | 7.3 / 9.2 |
| 15 | 215/70R15 | 98 T | 6½J | 703 / 27.7 | 216 / 8.5 | 7.3 / 9.2 |
| 16 | 195/55R16 | 91/XL V | 6J | 620 / 24.4 | 201 / 7.9 | 7.3 / 9.2 |
| 16 | 205/55R16 | 91 V | 6½J | 632 / 24.9 | 205 / 8.4 | 7.3 / 9.2 |
| 16 | 205/60R16 | 92 H | 6J | 652 / 25.7 | 205 / 8.2 | 7.3 / 9.2 |
| 16 | 205/65R16 | 95 H | 6J | 672 / 26.5 | 205 / 8.2 | 7.3 / 9.2 |
| 16 | 215/55R16 | 97/XL V | 7J | 642 / 25.3 | 226 / 8.9 | 7.3 / 9.2 |
| 16 | 215/65R16 | 98 H | 6½J | 664 / 26.1 | 215 / 8.7 | 7.3 / 9.2 |
| 16 | 215/60R16 | 95 H | 6½J | 686 / 27.0 | 221 / 8.7 | 7.3 / 9.2 |
| 16 | 225/55R16 | 99/XL V | 7J | 654 / 25.7 | 233 / 9.2 | 7.3 / 9.2 |
| 16 | 225/60R16 | 98 V | 6½J | 676 / 26.6 | 225 / 9.0 | 7.3 / 9.2 |



KT828

- Closed shoulder tread design, effectively lower noise
- Three vertical tread grooves, excellent water drainage.
- Central ribs with little steel sheets increase driving comfort.



| SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | PRESSURE (kpa)/psi | |
|------|---------------------------|-----------------|--------------------------|----------------------------|-----------------------|----------|
| 13 | 155/65R13 | 73 T | 4½J | 532 / 20.9 | 157 / 6.2 | 250 / 36 |
| 13 | 155/70R13 | 75 T | 4½J | 548 / 21.6 | 157 / 6.2 | 250 / 36 |
| 13 | 155/80R13 | 79 T | 4½J | 578 / 22.8 | 157 / 6.2 | 240 / 35 |
| 14 | 155/65R14 | 75 T | 4½J | 558 / 22 | 157 / 6.2 | 250 / 36 |
| 14 | 195/60R14 | 86 H | 6J | 590 / 23.2 | 201 / 7.9 | 250 / 36 |
| 15 | 175/65R15 | 84H | 5J | 609 / 24.0 | 177 / 7.0 | 300 / 44 |



KT696

UTQG: 320AA

- Good handling ability
- Effective drainage performance
- Good driving stability



| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|------------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 16 | 195/45R16 | 84/XL V | 6½J | 582 / 22.9 | 195 / 7.7 | 7.3 / 9.2 |
| 16 | 205/45ZR16 | 87/XL W | 7J | 590 / 23.2 | 206 / 8.1 | 7.3 / 9.2 |
| 16 | 205/50R16 | 92 V | 7J | 653 / 25.7 | 233 / 9.2 | 7.3 / 9.2 |
| 16 | 225/50R16 | 92 V | 7J | 632 / 24.9 | 233 / 9.2 | 7.3 / 9.2 |
| 17 | 205/40ZR17 | 84/XL W | 7½J | 596 / 23.5 | 212 / 8.3 | 7.3 / 9.2 |
| 17 | 205/45ZR17 | 88/XL W | 7J | 616 / 24.3 | 206 / 8.1 | 7.3 / 9.2 |
| 17 | 205/50ZR17 | 93/XL W | 6½J | 638 / 25.1 | 214 / 8.4 | 7.3 / 9.2 |
| 17 | 215/40R17 | 87/XL V | 7½J | 604 / 23.8 | 218 / 8.6 | 7.3 / 9.2 |
| 17 | 215/45ZR17 | 91/XL W | 7J | 626 / 24.6 | 213 / 8.4 | 7.3 / 9.2 |
| 17 | 215/50ZR17 | 95/XL W | 7J | 648 / 25.5 | 226 / 8.9 | 7.3 / 9.2 |
| 17 | 215/55ZR17 | 98/XL W | 7J | 668 / 26.3 | 226 / 8.9 | 7.3 / 9.2 |
| 17 | 225/45ZR17 | 94/XL W | 7½J | 634 / 25.0 | 225 / 8.9 | 7.3 / 9.2 |
| 17 | 225/50ZR17 | 98/XL W | 7J | 658 / 25.9 | 233 / 9.2 | 7.3 / 9.2 |
| 17 | 225/55ZR17 | 101/XL W | 7J | 680 / 26.8 | 233 / 9.2 | 7.3 / 9.2 |
| 17 | 235/40ZR17 | 90 W | 8½J | 620 / 24.4 | 241 / 9.5 | 7.3 / 9.2 |
| 17 | 235/45ZR17 | 97/XL W | 8J | 644 / 25.4 | 236 / 9.3 | 7.3 / 9.2 |
| 17 | 235/55R17 | 103/XL V | 7½J | 690 / 27.2 | 245 / 9.6 | 7.3 / 9.2 |
| 17 | 245/45ZR17 | 95 W | 8J | 652 / 25.7 | 243 / 9.6 | 7.3 / 9.2 |
| 18 | 215/35ZR18 | 84/XL W | 7½J | 607 / 23.9 | 218 / 8.6 | 7.3 / 9.2 |
| 18 | 215/40ZR18 | 85 W | 7½J | 629 / 24.8 | 218 / 8.6 | 7.3 / 9.2 |
| 18 | 225/40ZR18 | 92/XL W | 8J | 637 / 25.1 | 230 / 9.1 | 7.3 / 9.2 |
| 18 | 235/40ZR18 | 95/XL W | 8½J | 645 / 25.4 | 241 / 9.5 | 7.3 / 9.2 |

| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|------------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 18 | 235/45ZR18 | 98/XL W | 8J | 669 / 26.3 | 236 / 9.3 | 7.3 / 9.2 |
| 18 | 235/55ZR18 | 100 W | 7½J | 715 / 28.1 | 245 / 9.6 | 7.8 / 9.8 |
| 18 | 245/40ZR18 | 97/XL W | 8½J | 653 / 25.7 | 248 / 9.8 | 7.3 / 9.2 |
| 18 | 245/45ZR18 | 100/XL W | 8J | 677 / 26.7 | 243 / 9.6 | 7.3 / 9.2 |
| 18 | 255/35ZR18 | 94/XL W | 9J | 635 / 25.0 | 260 / 10.2 | 7.3 / 9.2 |
| 18 | 265/35ZR18 | 97/XL W | 9.5J | 643 / 25.3 | 271 / 10.7 | 7.3 / 9.2 |
| 19 | 215/35ZR19 | 85/XL W | 7½J | 633 / 24.9 | 218 / 8.6 | 7.3 / 9.2 |
| 19 | 225/35ZR19 | 88/XL W | 8J | 641 / 25.2 | 230 / 9.1 | 7.3 / 9.2 |
| 19 | 235/35ZR19 | 91/XL W | 8½J | 647 / 25.5 | 241 / 9.5 | 7.3 / 9.2 |
| 19 | 245/35ZR19 | 93/XL W | 8½J | 655 / 25.8 | 248 / 9.8 | 7.3 / 9.2 |
| 19 | 245/40ZR19 | 98/XL W | 8½J | 679 / 26.7 | 248 / 9.8 | 7.3 / 9.2 |
| 19 | 245/45ZR19 | 102/XL W | 8J | 703 / 27.7 | 243 / 9.6 | 7.3 / 9.2 |
| 19 | 255/40ZR19 | 100/XL W | 9J | 687 / 27.0 | 260 / 10.2 | 7.3 / 9.2 |
| 19 | 255/50ZR19 | 107/XL W | 8J | 739 / 29.1 | 265 / 10.4 | 7.8 / 9.8 |
| 19 | 275/30ZR19 | 96/XL W | 9½J | 649 / 25.6 | 278 / 10.9 | 7.3 / 9.2 |
| 19 | 275/40ZR19 | 101 W | 9½J | 703 / 27.7 | 278 / 10.9 | 7.3 / 9.2 |
| 19 | 275/45ZR19 | 108/XL W | 9J | 731 / 28.8 | 273 / 10.7 | 7.3 / 9.2 |
| 19 | 275/55R19 | 111 V | 8½J | 785 / 30.9 | 284 / 11.2 | 7.8 / 9.8 |
| 20 | 225/30ZR20 | 90/XL W | 8J | 666 / 26.2 | 230 / 9.1 | 7.3 / 9.2 |
| 20 | 225/35ZR20 | 90/XL W | 8J | 666 / 26.2 | 230 / 9.1 | 7.3 / 9.2 |
| 20 | 245/35ZR20 | 95/XL W | 8½J | 680 / 26.8 | 248 / 9.8 | 7.3 / 9.2 |
| 20 | 275/40ZR20 | 106/XL W | 9½J | 728 / 28.7 | 278 / 10.9 | 7.3 / 9.2 |



KT686

UTQG: 420AA

- Low rolling resistance
- Extremely low noise
- Good driving experience



| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|------------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 20 | 235/35ZR20 | 92/XL W | 8½J | 672 / 26.5 | 241 / 9.5 | 8.0 / 10.1 |
| 20 | 265/50R20 | 111/XL V | 8½J | 774 / 30.5 | 277 / 10.9 | 8.8 / 11.1 |
| 20 | 285/30ZR20 | 99/XL W | 10J | 680 / 26.8 | 290 / 11.4 | 8.0 / 10.1 |
| 22 | 235/30ZR22 | 90/XL W | 8½J | 701 / 27.6 | 242 / 9.5 | 8.0 / 10.1 |
| 22 | 245/30ZR22 | 92/XL W | 8½J | 707 / 27.8 | 248 / 9.8 | 8.0 / 10.1 |
| 22 | 255/30ZR22 | 95/XL W | 9J | 713 / 28.1 | 260 / 10.2 | 8.0 / 10.1 |
| 22 | 265/40R22 | 106/XL V | 9½J | 771 / 30.4 | 271 / 10.7 | 9.0 / 11.3 |
| 22 | 265/45R22 | 109/XL V | 9J | 797 / 31.4 | 266 / 10.5 | 8.8 / 11.1 |
| 22 | 265/30ZR22 | 97/XL W | 9½J | 719 / 28.3 | 271 / 10.7 | 8.0 / 10.1 |
| 22 | 285/35ZR22 | 106/XL W | 10J | 759 / 29.9 | 290 / 11.4 | 8.8 / 11.1 |

| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|------------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 22 | 295/25ZR22 | 97/XL W | 10½J | 707 / 27.8 | 301 / 11.9 | 8.0 / 10.1 |
| 22 | 305/45R22 | 118/XL V | 10J | 833 / 32.8 | 303 / 11.9 | 8.8 / 11.1 |
| 24 | 245/30ZR24 | 94/XL W | 8½J | 758 / 29.8 | 248 / 9.8 | 8.0 / 10.1 |
| 24 | 255/30ZR24 | 97/XL W | 9J | 764 / 30.1 | 260 / 10.2 | 8.0 / 10.1 |
| 24 | 275/25ZR24 | 96/XL W | 10J | 748 / 29.4 | 283 / 11.1 | 8.8 / 11.1 |
| 24 | 275/30ZR24 | 101/XL W | 9½J | 776 / 30.6 | 278 / 10.9 | 8.7 / 11.0 |
| 24 | 295/35R24 | 110/XL V | 10½J | 816 / 32.1 | 301 / 11.9 | 8.8 / 11.1 |
| 26 | 295/30ZR26 | 107/XL W | 10½J | 838 / 33.0 | 301 / 11.9 | 8.7 / 11.0 |
| 26 | 305/30ZR26 | 109/XL W | 11J | 844 / 33.2 | 313 / 12.3 | 8.7 / 11.0 |



KT818

UTQG: 420AA

- Better traction performance
- Excellent grip ability on snowy roads
- Higher security



| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|------------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 16 | 205/50R16 | 87 V | 6½J | 612 / 24.1 | 214 / 8.4 | 8.0 / 10.1 |
| 18 | 235/40ZR18 | 95/XL W | 8½J | 645 / 25.4 | 241 / 9.5 | 8.0 / 10.1 |
| 18 | 245/40ZR18 | 97/XL W | 8½J | 653 / 25.7 | 248 / 9.8 | 8.0 / 10.1 |

| | SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds |
|----|------------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|
| 18 | 265/35ZR18 | 97/XL W | 9½J | 643 / 25.3 | 271 / 10.7 | 8.0 / 10.1 |
| 18 | 275/35ZR18 | 95 W | 9½J | 649 / 25.6 | 278 / 10.9 | 7.6 / 9.6 |



KT858C

- Efficient water expulsion, ensures safety on wet slippery surface.
- Central Tread Pattern enhanced tire performance and life span.
- Closed Tread for higher stability & gripping



| SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | |
|------|---------------------------|-----------------|--------------------------|----------------------------|-----------|
| 13LT | 165R13LT | 89/88 S | 4½J | 596 / 23.5 | 167 / 6.6 |
| 13LT | 175R13LT | 97/95 R | 5J | 610 / 24.0 | 177 / 7.0 |
| 14LT | 165R14LT | 96/95 T | 4½J | 620 / 24.4 | 165 / 6.5 |
| 14LT | 195R14LT | 105/103 R | 5½J | 668 / 26.3 | 196 / 7.7 |
| 15LT | 195R15LT | 106/104 S | 5½J | 693 / 27.3 | 198 / 7.8 |
| 15LT | 195/70R15LT | 108/105 R | 6J | 655 / 25.8 | 201 / 7.9 |
| 16LT | 205/65R16LT | 107/105 R | 6J | 672 / 26.5 | 209 / 8.2 |
| 16LT | 215/75R16LT | 112/109 S | 6J | 728 / 28.7 | 216 / 8.5 |
| 14C | 165/70R14C | 99/98 R | 5J | 634 / 25.0 | 178 / 7.0 |
| 14C | 175/65R14C | 102/100 R | 5½J | 650 / 25.6 | 188 / 7.4 |

| SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | |
|------|---------------------------|-----------------|--------------------------|----------------------------|-----------|
| 15C | 205/70R15C | 89/87 R | 5J | 588 / 23.1 | 170 / 6.7 |
| 14C | 175R14C | 90/88 T | 5J | 584 / 23.0 | 177 / 7.0 |
| 14C | 185R14C | 106/104 R | 6J | 669 / 26.3 | 209 / 8.2 |
| 16C | 195/60R16C | 109/107 S | 6½J | 683 / 26.9 | 221 / 8.7 |
| 16C | 215/60R16C | 106/103 R | 6½J | 697 / 27.4 | 228 / 9.0 |
| 16C | 195/65R16C | 104/102 R | 5J | 684 / 26.9 | 184 / 7.2 |
| 16C | 235/65R16C | 99/97 H | 6J | 640 / 25.2 | 201 / 7.9 |
| 15C | 215/70R15C | 104/102 T | 6J | 660 / 26.0 | 201 / 7.9 |
| 15C | 225/70R15C | 108/106 T | 6½J | 664 / 26.1 | 221 / 8.7 |
| 16C | 185/75R16C | 115/113 T | 7J | 712 / 28 | 240 / 9.4 |



KT797

- Avoiding irregular wear
- Effective drainage performance
- Super load capacity ability



| SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds | |
|------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|-------------|
| 16 | 7.00R16LT | 117/116 M | 5½J/5.50F | 775 / 30.5 | 200 / 7.9 | 11.1 / 14.0 |



KT656

- Purpose design for all weather
- Good traction performance
- Longer tyre life



| SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds | |
|------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|------------|
| 14 | 205R14C | 109/107 P | 6J | 686 / 27.0 | 208 / 8.2 | 8.8 / 11.1 |
| 15 | 205/65R15C | 102/100 T | 6J | 647 / 25.5 | 209 / 8.2 | 9.1 / 11.5 |
| 16 | 215/65R16C | 109/107 R | 6½J | 686 / 27.0 | 221 / 8.7 | 9.5 / 12.0 |
| 16 | 225/65R16C | 112/110 R | 6½J | 698 / 27.5 | 228 / 9.0 | 9.7 / 12.2 |



KT737

- Avoiding irregular wear
- Better wet grip performance
- Longer tyre life



| SIZE | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | O.T.D (mm)/32nds | |
|------|---------------------------|-----------------|--------------------------|----------------------------|---------------------|-------------|
| 16 | 7.50R16LT | 122/118 N | 6J/6.00G | 805 / 31.7 | 215 / 8.5 | 12.1 / 15.2 |




TRUCK & BUS TYRE



KTHD1

Drive



- TMS technology and special compound for smooth wear.
- Special pattern design provides good anti eccentric wear. Block tread.




| SIZE | PR | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|---------------------------|--------------|--------------------------|----------------------------|---------------------|---------------------|-----------------------|
| 11R22.5 | 16 | 146/143 M | 8.25 | 1050 / 41.3 | 279 / 11.0 | 3000/2750 | 20 / 25.2 | 830 / 120 |
| 12R22.5 | 18 | 152/149 M | 9.00 | 1084 / 42.7 | 300 / 11.8 | 3550/3275 | 20 / 25.2 | 930 / 135 |
| 295/80R22.5 | 18 | 152/149 M | 9.00 | 1044 / 41.1 | 298 / 11.7 | 3550/3250 | 20 / 25.2 | 900 / 130 |



KTHD3

Drive



- Widened tread design provides excellent driving and gripping power.
- Extra deep tread provides powerful traction and a long tread life.
- Closed shoulder maintains good irregular wear resistance.
- Excellent crack and tear resistance character.




| SIZE | PR | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|---------------------------|--------------|--------------------------|----------------------------|---------------------|---------------------|-----------------------|
| 11R22.5 | 16 | 146/143 M | 8.25 | 1050 / 41.3 | 279 / 11.0 | 3000/2725 | 20 / 25.2 | 830 / 120 |
| 11R24.5 | 16 | 149/146 L | 8.25 | 1104 / 43.5 | 279 / 11.0 | 3250/3000 | 20 / 25.2 | 830 / 120 |
| 295/75R22.5 | 16 | 146/143 L | 9.00 | 1014 / 39.9 | 298 / 11.7 | 3000/2725 | 20 / 25.2 | 830 / 120 |
| 285/75R24.5 | 16 | 147/144 L | 8.25 | 1050 / 41.3 | 283 / 11.1 | 3070/2800 | 20 / 25.2 | 830 / 120 |



KTHD7

Drive



- Block tread pattern provides excellent gripping and traction power.
- Touch belt construction for smooth wear and longer mileage.
- Special tread compound for high resistance against tread cut.




| SIZE | PR | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|---------------------------|-----------------|--------------------------|----------------------------|---------------------|---------------------|-----------------------|
| 9.5R17.5 | 18 | 143/141 J | 6.75 | 842 / 33.1 | 240 / 9.4 | 2725/2575 | 20 / 25.2 | 875 / 127 |
| 315/80R22.5 | 20 | 157/153 L | 9.00 | 1076 / 42.4 | 312 / 12.3 | 4125/3650 | 20 / 25.2 | 860 / 126 |



KTHD9

Drive



- Mixed pattern design provides strong traction and breaking power.
- Longer block pattern design enhances the ability of anti-eccentric wear and the abnormal wear.
- Five deep grooves, multi block&tiny kerfs on the blocks assure a firm grip and a powerful tread.




| SIZE | PR | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|---------------------------|-----------------|--------------------------|----------------------------|---------------------|---------------------|-----------------------|
| 315/80R22.5 | 20 | 157/153 L | 9.00 | 1076 / 42.4 | 312 / 12.3 | 4125/3650 | 20 / 25.2 | 860 / 126 |



KTHD8

Drive



- Mixed pattern design provides strong traction and breaking power.
- Longer block pattern design enhances the ability of anti-eccentric wear and the abnormal wear.
- Five deep grooves, multi block&tiny kerfs on the blocks assure a firm grip and a powerful tread.




| SIZE | PR | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|---------------------------|-----------------|--------------------------|----------------------------|---------------------|---------------------|-----------------------|
| 315/70R22.5 | 20 | 154/150 M | 9.00 | 1017 / 40.0 | 312 / 12.3 | 3750/3350 | 20 / 25.2 | 900 / 130 |



KTHS1

Steer/Trailer



- Special recipe design provides tear resistance, high wear resistance, and excellent load capacity.
- low rolling resistance&noise emission.
- Excellent heat radiation, guiding stability. Excellent fuel efficiency.




| SIZE | PR | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|---------------------------|-----------------|--------------------------|----------------------------|---------------------|---------------------|-----------------------|
| 11R22.5 | 16 | 146/143 M | 8.25 | 1050 / 41.3 | 279 / 11.0 | 3000/2750 | 16 / 20.2 | 830 / 120 |
| 12R22.5 | 18 | 152/149 M | 9.00 | 1084 / 42.7 | 300 / 11.8 | 3550/3250 | 16 / 20.2 | 930 / 135 |
| 295/80R22.5 | 18 | 152/149 M | 9.00 | 1044 / 41.1 | 298 / 11.7 | 3550/3250 | 16 / 20.2 | 900 / 130 |
| 315/80R22.5 | 20 | 157/153 L | 9.00 | 1076 / 42.4 | 312 / 12.3 | 4125/3650 | 16 / 20.2 | 860 / 126 |



KTHS4

Steer/Trailer



Four straight grooves provide excellent braking and driving performances.




| SIZE | PR | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|----------|----|---------------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 11.00R20 | 18 | 152/149 K | 8.0 | 1085 / 42.7 | 296 / 11.7 | 3550/3250 | 15 / 18.9 | 930 /135 |



KTHS8

All position



- High wear resistance.
- Cost effective.




| SIZE | PR | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|----------|----|---------------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 9.5R17.5 | 18 | 143/141 M | 6.75 | 974 / 38.3 | 229 / 9.0 | 2725/2575 | 13 / 16.4 | 930 /135 |



KTHS3

All position



- 3 continuous ribs, and the cricumferential grooves enhances superior adhesion porperties of the ground.
- Excellent wet skid resistance.
- Special tread design provides low heating and wear resistance.




| SIZE | PR | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|----------|----|---------------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 12.00R24 | 20 | 160/157 K | 8.5 | 1226 / 48.3 | 313 / 12.3 | 4500/4125 | 16 / 20.2 | 900 /130 |



KTHS5

Steer/Trailer



- Improved tread design, high wear resistance and eccentric wear resistance.
- Low rolling resistance, Less fuel consumption, good handling quality.




| SIZE | PR | LOAD INDEX/ SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|---------------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 11R22.5 | 16 | 146/143 M | 8.25 | 1050 / 41.3 | 279 / 11.0 | 3000/2750 | 15 / 18.9 | 830 /120 |
| 11R24.5 | 16 | 149/146 L | 8.25 | 1104 / 43.5 | 279 / 11.0 | 3250/3000 | 15 / 18.9 | 830 /120 |
| 205/75R17.5 | 16 | 124/122 M | 6.00 | 753 / 29.6 | 200 / 7.9 | 1600/1500 | 14 / 17.6 | 760 /110 |
| 215/75R17.5 | 16 | 126/124 M | 6.00 | 767 / 30.2 | 211 / 8.3 | 1650/1500 | 15 / 18.9 | 760 /110 |
| 235/75R17.5 | 16 | 132/130 M | 6.75 | 797 / 31.4 | 233 / 9.2 | 2000/1850 | 15 / 18.9 | 830 /120 |
| 225/70R19.5 | 14 | 128/126 M | 6.75 | 811 / 31.9 | 226 / 8.9 | 1800/1700 | 15 / 18.9 | 760 /110 |
| 245/70R19.5 | 16 | 136/134 M | 7.50 | 818 / 32.2 | 241 / 9.5 | 2180/2060 | 15 / 18.9 | 830 /120 |
| 265/70R19.5 | 16 | 140/138 M | 7.50 | 867 / 34.1 | 262 / 10.3 | 2500/2360 | 15 / 18.9 | 830 /120 |
| 255/70R22.5 | 16 | 140/137 M | 7.50 | 930 / 36.6 | 255 / 10.0 | 2500/2300 | 15 / 18.9 | 830 /120 |
| 275/70R22.5 | 16 | 148/145 M | 8.25 | 958 / 37.7 | 276 / 10.9 | 3150/2900 | 15 / 18.9 | 900 /130 |
| 295/75R22.5 | 16 | 146/143 L | 9.00 | 1014 / 39.9 | 298 / 11.7 | 3000/2725 | 15 / 18.9 | 830 /120 |
| 285/75R24.5 | 16 | 147/144 L | 8.25 | 1050 / 41.3 | 283 / 11.1 | 3070/2800 | 15 / 18.9 | 830 /120 |





KTMA1

All position



- Good handling and traction and super abrasion resistance.
- Excellent heat dissipation performance and excellent fuel efficiency.
- Higher original mileage.




| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 6.50R16 | 12 | 110/105 K | 5.50F | 745 / 29.3 | 195 / 7.7 | 1060/925 | 12 / 15.1 | 670 / 97 |
| 7.00R16 | 14 | 118/114 K/L | 5.50F | 775 / 30.5 | 205 / 8.1 | 1320/1180 | 13 / 16.4 | 770 / 112 |
| 7.50R16 | 14 | 122/118 K/L | 6.00G | 805 / 31.7 | 215 / 8.5 | 1500/1320 | 13 / 16.4 | 770 / 112 |
| 8.25R16 | 16 | 128/124 K/L | 6.50H | 855 / 33.7 | 235 / 9.3 | 1800/1600 | 15 / 18.9 | 770 / 112 |
| 8.25R20 | 16 | 139/137 K | 6.5 | 974 / 38.3 | 236 / 9.3 | 2430/2300 | 15 / 18.9 | 930 / 135 |
| 9.00R20 | 16 | 144/142 K | 7.0 | 1018 / 40.1 | 258 / 10.2 | 2800/3650 | 16 / 20.2 | 900 / 130 |
| 10.00R20 | 18 | 149/146 K | 7.5 | 1052 / 41.4 | 275 / 10.8 | 3250/3000 | 17 / 21.4 | 930 / 135 |
| 11.00R20 | 18 | 152/149 K | 8.0 | 1085 / 42.7 | 296 / 11.7 | 3550/3250 | 18 / 22.7 | 930 / 135 |
| 12.00R20 | 20 | 156/153 K | 8.5 | 1122 / 44.2 | 313 / 12.3 | 3750/3450 | 18 / 22.7 | 900 / 130 |
| 11R22.5 | 16 | 146/143 M | 8.25 | 1050 / 41.3 | 279 / 11.0 | 3000/2750 | 16 / 20.2 | 830 / 120 |
| 12R22.5 | 18 | 152/149 M | 9.00 | 1084 / 42.7 | 300 / 11.8 | 3550/3275 | 16 / 20.2 | 930 / 135 |
| 13R22.5 | 18 | 154/151 L | 9.75 | 1124 / 44.3 | 320 / 12.6 | 3750/3450 | 17 / 21.4 | 850 / 125 |
| 12.00R24 | 20 | 160/157 K | 8.5 | 1226 / 48.3 | 313 / 12.3 | 4500/4125 | 18 / 22.7 | 900 / 130 |
| 315/80R22.5 | 20 | 157/153 L | 9.00 | 1076 / 42.4 | 312 / 12.3 | 4125/3650 | 17 / 21.4 | 860 / 126 |
| 11R24.5 | 16 | 149/146 L | 8.25 | 1104 / 43.5 | 279 / 11.0 | 3250/3000 | 17 / 21.4 | 830 / 120 |



KTHS9

Steer/Trailer



- Suitable for medium/long-haul vehicles running on high-grade road.
- Excellent load capacity, straight shallow grooves.
- Straight ride and Anti-sidewall-scuffing performance.




| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 315/70R22.5 | 20 | 154/150 M | 9.00 | 1017 / 40.0 | 312 / 12.3 | 3750/3350 | 16 / 20.2 | 900 / 130 |



KTMD1

Drive



- Big deep blocks provide strong traction and braking power.
- Open groove and bottom design gives excellent self-cleaning performance. Reinforced bead and body




| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|----------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 11.00R20 | 18 | 152/149 K | 8.0 | 1085 / 42.7 | 296 / 11.7 | 3550/3250 | 19.5 / 24.6 | 930 / 135 |
| 12.00R20 | 20 | 156/153 K | 8.5 | 1122 / 44.2 | 313 / 12.3 | 3750/3450 | 18 / 22.7 | 900 / 130 |





KTMD7

Drive



- Reinforced belt and body construction enhance the load capacity.
- Special tread compound for high resistance against tread cut.




| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|----------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 12.00R24 | 20 | 160/157 K | 8.5 | 1226 / 48.3 | 313 / 12.3 | 4500/4125 | 18 / 22.7 | 900 /130 |



KTMD8

Drive



- Tough belt construction with high wear resistance and good impact force.
- Reinforced bead provides good traction.




| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|----------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 10.00R20 | 18 | 149/146 K | 7.5 | 1052 / 41.4 | 275 / 10.8 | 3250/3000 | 19 / 23.9 | 930 /135 |



KTMD5

Drive



- Good handling and traction and super abrasion resistance.
- Excellent heat dissipation performance and excellent fuel efficiency.
- Longer mileage.




| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 315/80R22.5 | 20 | 157/153 L | 9.00 | 1076 / 42.4 | 312 / 12.3 | 4125/3650 | 20 / 25.2 | 860 /126 |



KTMT1

Steer/Trailer



- Good handling and traction and super abrasion resistance.
- Excellent heat dissipation performance and excellent fuel efficiency.
- Higher original mileage.




| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 385/65R22.5 | 20 | 160 K | 11.75 | 1072 / 42.2 | 389 / 15.3 | 4500 | 17 / 21.4 | 900 /130 |





KTMT2

Steer/Trailer



- Good handling and traction and super abrasion resistance.
- Excellent heat dissipation performance and excellent fuel efficiency.
- Higher original mileage.




| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 385/65R22.5 | 20 | 160 K | 11.75 | 1072 / 42.2 | 389 / 15.3 | 4500 | 17 / 21.4 | 900 / 130 |



KTOD1

All position



- Transverse big block type and deepened pattern design, provide superior driving performance.
- The open type groove design has a good self-cleaning ability.
- In particular, reinforced carcass design, provide greater carrying capacity.




| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|----------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 12.00R20 | 20 | 156/153 K | 8.5 | 1122 / 44.2 | 313 / 12.3 | 3750/3450 | 22 / 27.7 | 900 / 130 |



KTMT3

Trailer



- Excellent traction and draining performance, more original mileage.
- Trailer tyre of bus and truck, not suitable for drive and steer wheel position running on well-paved roads and mixed pavements and medium/long-haul vehicles.




| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 385/65R22.5 | 20 | 160 K | 11.75 | 1072 / 42.2 | 389 / 15.3 | 4500 | 16.5 / 20.8 | 900 / 130 |



KTOD5

All position



- Unique belt structure, with high wear-resistance and low heat producing formulation.
- Strong grip and wet-slip resistance performance.
- Optimized and enhanced bead design, especially for special conditions.



| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|----------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 10.00R20 | 18 | 149/146 K | 7.5 | 1052 / 41.4 | 275 / 10.8 | 3250/3000 | 20 / 25.2 | 930 / 135 |
| 11.00R20 | 18 | 152/149 K | 8.0 | 1085 / 42.7 | 296 / 11.7 | 3550/3250 | 20 / 25.2 | 930 / 135 |
| 12.00R20 | 20 | 156/153 K | 8.5 | 1122 / 44.2 | 313 / 12.3 | 3750/3450 | 20 / 25.2 | 900 / 130 |
| 13R22.5 | 18 | 154/151 L | 9.75 | 1124 / 44.3 | 320 / 12.6 | 3750/3450 | 20 / 25.2 | 850 / 125 |




ECO TRUCK & BUS TIRE



DR908

All position



APPLICATION

Applied for express way, highway and urban road.
For driving position of truck.

PERFORMANCE


Circumferential grooves, high-speed driving.
Unique narrow grooves design, preventing stones lodged in the tread.
Big pattern groove on shoulder, good grip on dry, wet and mud road conditions.
Excellent wear-resistant tread, excellent puncture resistance, tear resistance and longer mileage.

| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 11R22.5 | 16 | 148/145 M | 8.25 | 1054 / 41.5 | 279 / 11.0 | 3150/2900 | 15 / 18.9 | 840 / 120 |
| 12R22.5 | 16 | 152/148 L | 9.00 | 1085 / 42.7 | 300 / 11.8 | 3550/3150 | 17 / 21.4 | 840 / 120 |
| 12R22.5 | 18 | 152/149 L | 9.00 | 1085 / 42.7 | 300 / 11.8 | 3550/3250 | 17 / 21.4 | 930 / 135 |
| 13R22.5 | 18 | 154/151 L | 9.75 | 1124 / 44.3 | 320 / 12.6 | 3750/3450 | 17.5 / 22.0 | 830 / 120 |
| 295/80R22.5 | 16 | 152/148 M | 9.00 | 1044 / 41.1 | 298 / 11.7 | 3550/3150 | 15 / 18.9 | 830 / 120 |
| 315/80R22.5 | 20 | 156/151 M | 9.00 | 1074 / 42.3 | 312 / 12.3 | 4000/3450 | 15 / 18.9 | 850 / 125 |



DR920

Drive



APPLICATION

Apply for normal and urban road.
For truck driving tire.

PERFORMANCE

Deep pattern design, stronger driving power and longer lifespan.
Special tread, excellent wear resistance.
Special mixed pattern with lug and rib type, driving stability and high speed.
Special steel slice design, anti-side-skid.
Excellent wear-proof tread, better puncture and tear resistance and longer mileage.

| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 11R22.5 | 16 | 148/145 L | 8.25 | 1065 / 41.9 | 279 / 11 | 3150/2900 | 20.5 / 26.0 | 840 / 120 |
| 11R24.5 | 16 | 149/146 L | 8.25 | 1116 / 43.9 | 279 / 11 | 3250/3000 | 20.5 / 26.0 | 830 / 120 |
| 295/75R22.5 | 14 | 144/141 L | 9.00 | 1020 / 40.2 | 298 / 11.7 | 2800/2575 | 20.5 / 26.0 | 760 / 110 |
| 295/80R22.5 | 16 | 152/148 M | 9.00 | 1050 / 41.3 | 298 / 11.7 | 3550/3150 | 20.5 / 26.0 | 830 / 120 |
| 315/80R22.5 | 20 | 156/151 M | 9.00 | 1082 / 42.6 | 312 / 12.3 | 4000/3450 | 20.5 / 26.0 | 850 / 125 |
| 285/75R24.5 | 14 | 144/141 L | 8.25 | 1056 / 41.6 | 283 / 11.1 | 2800/2575 | 20.5 / 26.0 | 760 / 110 |



DR909/909T

Steer/Trailer

Trailer
*DR909T



APPLICATION
Apply for highway and normal road.
For all bus application and steer tire for truck.

PERFORMANCE
4-rib main grooves with its unique zigzag pattern on sides, excellent traction and braking force, good water evacuation and stability. Special tread groove design, optimal self-cleaning. Variable pitch design, lower noise characteristics. Wide pattern grooves on shoulder with low-heating compound, high speed and good durability performance.

| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 9R22.5 | 14 | 136/134 M | 6.75 | 974 / 38.3 | 229 / 9 | 2240/2120 | 14 / 17.6 | 830 / 120 |
| 10R22.5 | 16 | 144/142 M | 7.50 | 1019 / 40.1 | 254 / 10 | 2800/2650 | 14 / 17.6 | 900 / 130 |
| 11R22.5 | 16 | 148/145 M | 8.25 | 1054 / 41.5 | 279 / 11 | 3150/2900 | 15 / 18.9 | 840 / 120 |
| 12R22.5 | 16 | 152/148 L | 9.00 | 1085 / 42.7 | 300 / 11.8 | 3550/3150 | 15.5 / 19.5 | 840 / 120 |
| 11R24.5 | 16 | 149/146 M | 8.25 | 1104 / 43.5 | 279 / 11 | 3250/3000 | 15 / 18.9 | 830 / 120 |
| 295/75R22.5 | 14 | 144/141 M | 9.00 | 1014 / 39.9 | 298 / 11.7 | 2800/2575 | 15 / 18.9 | 760 / 110 |
| 295/80R22.5 | 16 | 152/148 M | 9.00 | 1044 / 41.1 | 298 / 11.7 | 3550/3150 | 15.5 / 19.5 | 830 / 120 |
| 315/80R22.5 | 20 | 156/151 M | 9.00 | 1076 / 42.4 | 312 / 12.3 | 4000/3450 | 15 / 18.9 | 850 / 125 |
| 285/75R24.5 | 14 | 144/141 M | 8.25 | 1050 / 41.3 | 283 / 11.1 | 2800/2575 | 15 / 18.9 | 760 / 110 |


*DR909T

| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 11R22.5 | 14 | 148/145 M | 8.25 | 1054 / 41.5 | 279 / 11 | 3150/2900 | 10.5 / 13.2 | 840 / 120 |
| 295/75R22.5 | 14 | 144/141 M | 9.00 | 1014 / 39.9 | 298 / 11.7 | 2800/2575 | 10.5 / 13.2 | 760 / 110 |



DR926

Drive



APPLICATION
Apply for express way, highway and urban road.
For driving position of truck.


PERFORMANCE
Wide tread and grooves, great wear-resistance and powerful driving and breaking performance. Special grooves, excellent drainage and tight grip on the wet. Noncontinuous grooves on shoulder, excellent heat dispersing; steel splice design, high speed and durability performance.

| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 12R22.5 | 16 | 152/148 L | 9.00 | 1096 / 43.1 | 300 / 11.8 | 3550/3150 | 18 / 22.5 | 840 / 120 |
| 315/80R22.5 | 20 | 156/151 L | 9.00 | 1082 / 42.6 | 312 / 12.3 | 4000/3450 | 21 / 26.5 | 850 / 125 |



DR928

Drive



APPLICATION
Applied for highway, urban and country road.
For driving position.


PERFORMANCE
Solid tread pattern ensures tight grip performance. Block tread in the center effectively reduces damage caused by mixed road. Tread pattern resists wear and puncture, effectively disperses heat.

| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 9.5R17.5 | 18 | 143/141 K | 6.75 | 842 / 33.1 | 240 / 9.4 | 2725/2575 | 15 / 19.0 | 875 / 125 |
| 11R22.5 | 16 | 148/145 L | 8.25 | 1054 / 41.5 | 279 / 11 | 3150/2900 | 17 / 21.5 | 840 / 120 |
| 13R22.5 | 18 | 154/151 L | 9.75 | 1124 / 44.3 | 320 / 12.6 | 3750/3450 | 19 / 24.0 | 830 / 120 |
| 315/80R22.5 | 20 | 156/151 L | 9.00 | 1082 / 42.6 | 312 / 12.3 | 4000/3450 | 21 / 26.5 | 850 / 125 |



DR930

All position



APPLICATION
Apply for construction and mining area.
For driving position of tractor, light truck, and concrete mixing truck for short distance.


PERFORMANCE
Excellent puncture and tear resistance of the tread, great driving and performance. Deeper pattern, longer mileage.

| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 11R22.5 | 16 | 148/145 G | 8.25 | 1065 / 41.9 | 279 / 11 | 3150/2900 | 23 / 29.0 | 840 / 120 |
| 12R22.5 | 18 | 152/149 G | 9.00 | 1096 / 43.1 | 300 / 11.8 | 3550/3250 | 23 / 29.0 | 930 / 135 |
| 315/80R22.5 | 20 | 156/151 G | 9.00 | 1082 / 42.6 | 312 / 12.3 | 4000/3450 | 23 / 29.0 | 850 / 125 |



DR938

Drive



APPLICATION
Apply for highway and urban road.
For driving position of truck.

PERFORMANCE
Widened tread design, good wear resistance on tread. Special block design, increasing grooves vertically and laterally, good anti-slip performance. Slim ditch on block. Deep pattern design and wear-resistance compound formula, longer lifespan and mileage.

| SIZE | PR | LOAD INDEX/SPEED CODE | STANDARD RIM | OVERALL DIA (mm)/inch | SECTION WIDTH (mm)/inch | LOAD Single/Dual | O.T.D (mm)/32nds | PRESSURE (kpa/psi) |
|-------------|----|-----------------------|--------------|-----------------------|-------------------------|------------------|------------------|--------------------|
| 11R22.5 | 16 | 148/145 L | 8.25 | 1065 / 41.9 | 279 / 11 | 3150/2900 | 22 / 27.5 | 840 / 120 |
| 12R22.5 | 18 | 152/148 L | 9.00 | 1096 / 43.1 | 300 / 11.8 | 3550/3250 | 21 / 26.5 | 930 / 135 |
| 295/80R22.5 | 16 | 152/148 M | 9.00 | 1050 / 43.1 | 298 / 11.7 | 3550/3150 | 20.5 / 26.0 | 830 / 120 |
| 315/80R22.5 | 20 | 156/151 M | 9.00 | 1082 / 42.6 | 312 / 12.3 | 4000/3450 | 22 / 27.5 | 850 / 125 |