

ARDUZZA



**PCR TYRE
CATALOGUE**

SHANDONG TERAFLEX TYRE



BànlǚTires

ARDUZZA ALL RANGE



EPOCH NUOVO HP		EPOCH SPORT ES		MUDBREAKER MT		ANSWER LIFESTYLE AL		EMPIRE TRAC ET2		EMPIRE TRAC ET3		EPOCH TRAVELER ST		EMPIRE TRAC ET		PATHBREAKER A/T	
195/50R15	175/70R13	215/35ZR18	245/45ZR18	LT285/70R17		235/45R19	275/60R20	155R13C		6.50R16LT		ST205/75R14		185R14C		31X10.50R15LT	
195/55R15	185/70R13	255/35ZR18	255/45R18	LT265/70R17		255/45R19	215/65R16	165R13C		7.00R16LT		ST205/75R15		195R14C		285/60R18	
185/55R15	165/70R14	265/35ZR18	245/45ZR20	LT275/70R18		265/45R21	215/65R17	175R13C		7.50R16LT		ST225/75R15		195R15C		235/60R18	
185/55R16	175/70R14	225/35ZR19	245/45ZR19	LT235/75R16		265/45ZR20	225/65R17	165/70R13LT				ST175/80R13		175/70R14LT		225/65R17	
205/55R16	185/70R14	235/35ZR19	255/45ZR20	LT245/75R16		275/45ZR21	235/65R17	165/70R14LT				ST235/80R16		195/70R15C		LT245/65R17	
175/60R13	195/70R14	245/35ZR19	275/45ZR20	LT265/75R16		235/50R19	245/65R17	6.50R16LT						205/70R15C		LT265/65R17	
165/60R14	155/80R13	255/35ZR19	195/50R16	LT285/75R16		255/50ZR19	265/65R17	7.00R16LT						225/70R15C		LT285/65R18	
185/60R14		275/30ZR20	205/50ZR16	LT235/85R16		265/50ZR19	285/65R17	7.00R16LT						215/70R16LT		235/70R16	
195/60R14		275/35ZR19	215/50ZR17	31x10.50R15LT		265/50R20	235/65R18	7.50R16LT						195/65R16C		LT245/70R16	
205/60R14		255/35ZR20	225/50ZR17	33X12.50R15LT		275/50ZR20	265/65R18	7.50R16LT						205/65R16C		LT255/70R16	
165/60R15		275/35ZR20	235/50ZR17	35X12.50R18LT		275/50R21	205/70R15							215/65R16C		LT265/70R16	
175/60R15		205/40ZR17	205/50ZR17	35X12.50R20LT		275/50R22	255/70R15							225/65R16C		LT285/70R17	
185/60R15		215/40ZR17	215/50R18	35X12.50R17LT		285/50R20	225/70R16							235/65R16C		LT215/75R15	
195/60R15		215/40ZR18	225/50R18			235/55R17	235/70R16							185/75R16C		LT235/75R15	
205/60R15		225/40ZR18	235/50ZR18			275/55R17	255/70R16							195/75R16C		LT245/75R16	
205/60R16		235/40ZR18	245/50ZR18			215/55R18	255/70R18							215/75R15LT		LT265/75R16	
215/60R16		245/40ZR18	195/55ZR16			225/55R18	265/70R18							215/75R16C		LT285/75R16	
225/60R16		235/40ZR19	205/55ZR16			235/55R18											
155/65R13		245/40ZR19	215/55ZR16			255/55ZR18											
165/65R13		275/40ZR19	225/55ZR16			225/55R19											
155/65R14		245/40ZR20	205/55ZR17			235/55R19											
165/65R14		275/40ZR20	215/55ZR17			245/55ZR19											
175/65R14		195/45R16	225/55ZR17			255/55R19											
185/65R14		205/45ZR16	235/55ZR17			275/55R19											
175/65R15		215/45ZR16	235/55R18			235/55R20											
185/65R15		205/45ZR17	275/55R20			235/60R16											
195/65R15		215/45ZR17	195/60R16			215/60R17											
205/65R15		225/45ZR17				225/60R17											
215/65R15		235/45ZR17				225/60R18											
205/65R16		245/45ZR17				235/60R18											
215/65R16		215/45ZR18				245/60R18											
155/70R13		225/45ZR18				255/60R18											
165/70R13		235/45ZR18				265/60R18											
40 Sizes		60 Sizes		13 Sizes		49 Sizes		10 Sizes		3 Sizes		5 Sizes		17 Sizes		17 Sizes	
Page:01-02		Page:03-04		Page:05-06		Page:07-08		Page:09		Page:09		Page:10		Page:11		Page:12	

UTQG	TREADWEAR	TRACTION	TEMPERATURE
	400	A	A



EPOCH NUOVO HP



Series	size	L.I	S.R	Standard Rim	Section Width(mm)	Overall Diameter(mm)	Max KG	Load LBS	Max Pressure KPA	PSI	Tread Depth(mm)
50	195/50R15	82	V	6J	201	577	475	1047	300	44	7
55	195/55R15	85	V	6J	201	595	515	1135	300	44	7
	185/55R15	82	H	6J	194	585	475	1047	300	44	7
	185/55R16	87 XL	V	6J	194	610	545	1201	340	49	7
	205/55R16	91	V	6½J	214	632	615	1356	300	44	7.8
60	175/60R13	77	H	5.00B	177	540	412	908	300	44	6.7
	165/60R14	75	T	5 J	170	554	387	853	300	44	6.7
	185/60R14	82	H	5½J	189	578	475	1047	300	44	7.6
	195/60R14	86	H	6J	201	590	530	1168	300	44	7
	205/60R14	88	V	6J	209	602	560	1235	300	44	7
	165/60R15	77	H	5J	170	579	412	908	300	44	6.7
	175/60R15	81	H	5J	177	591	462	1019	300	44	6.7
	185/60R15	84	H	5½J	189	603	500	1102	300	44	7.6
	195/60R15	88	H	6 J	201	615	560	1235	300	44	7
	205/60R15	91	V	6J	209	627	615	1356	300	44	7
	205/60R16	92	V	6J	209	652	630	1389	300	44	7
	215/60R16	95	V	6½J	221	664	690	1521	300	44	7
	225/60R16	98	H	6½J	228	676	750	1653	300	44	7
65	155/65R13	73	T	4.50B	157	532	365	805	300	44	6.7
	165/65R13	77	T	5 J	170	544	412	908	300	44	7.3
	155/65R14	75	H	4½J	157	558	387	853	300	44	6.7
	165/65R14	79	H	5J	170	570	437	963	300	44	6.7
	175/65R14	82	T	5 J	177	584	475	1047	300	44	6.7
	185/65R14	86	H	5½J	189	596	530	1168	300	44	7
	175/65R15	84	H	5J	177	609	500	1102	300	44	6.7
	185/65R15	88	H	5 1/2 J	189	621	560	1235	300	44	7.6
	195/65R15	91	H	6 J	201	635	615	1356	300	44	7.8
	205/65R15	94	H	6 J	209	647	670	1477	300	44	7.8
	215/65R15	100 XL	T	6½J	221	661	800	1784	340	49	7
	205/65R16	95	V	6J	209	672	690	1521	300	44	7
	215/65R16	98	V	6½J	221	686	750	1653	300	44	7
70	155/70R13	75	T	4.50B	157	548	387	853	300	44	6.7
	165/70R13	79	T	5 J	170	562	437	963	300	44	6.7
	175/70R13	82	T	5 J	177	576	475	1047	300	44	7.6
	185/70R13	86	T	5.50B	189	590	530	1168	300	44	7
	165/70R14	81	T	5 J	170	588	462	1019	300	44	6.7
	175/70R14	84	T	5 J	177	602	500	1102	300	44	7.6
	185/70R14	88	H	5½J	189	616	560	1235	300	44	7
	195/70R14	91	H	6J	201	630	615	1356	300	44	7
80	155/80R13	79	T	4.50B	157	578	437	963	300	44	6.7

UTQG	TREADWEAR	TRACTION	TEMPERATURE
	320	AA	A



EPOCH SPORT ES

Series	size	LI	S.R	Standard Rim	Section Width(mm)	Overall Diameter(mm)	Max KG	Load LBS	Max Pressure KPA	PSI	Tread Depth(mm)
30	275/30ZR20	93	W	9½J	278	674	650	1433	300	44	7.2
35	215/35ZR18	84 XL	W	7½J	218	607	500	1102	340	49	7.2
	255/35ZR18	94 XL	W	9 J	260	635	670	1477	340	49	7.2
	265/35ZR18	93	W	9½J	271	643	650	1433	300	44	7.2
	225/35ZR18	84	W	8 J	230	641	500	1102	300	44	7.2
	235/35ZR19	91 XL	W	8½J	241	647	615	1356	340	49	7.2
	245/35ZR19	93 XL	W	8½J	248	655	650	1433	340	49	7.2
	255/35ZR19	96 XL	W	9J	260	661	710	1565	340	49	7.2
	275/35ZR19	100 XL	W	9½J	278	675	800	1764	340	49	7.2
	255/35ZR20	97 XL	W	9J	260	686	730	1609	340	49	7.2
	275/35ZR20	98	W	9½J	278	700	750	1653	300	44	7.2
40	205/40ZR17	84 XL	W	7½J	212	596	500	1102	340	49	7.2
	215/40ZR17	87 XL	W	7½J	218	604	545	1201	340	49	7.2
	215/40ZR18	85	W	7½J	218	629	515	1135	300	44	7.2
	225/40ZR18	92 XL	W	8 J	230	637	630	1389	340	49	7.2
	235/40ZR18	95 XL	W	8½ J	241	645	690	1521	340	49	7.2
	245/40ZR18	97 XL	W	8½J	248	653	730	1609	340	49	7.2
	235/40ZR19	92	W	8½J	241	671	630	1389	300	44	7.2
	245/40ZR19	98 XL	W	8½J	248	679	750	1653	340	49	7.2
	275/40ZR19	101	W	9½J	278	703	825	1819	300	44	7.2
	245/40ZR20	95	W	8½J	248	704	690	1521	300	44	7.2
	275/40ZR20	106 XL	W	9½J	278	728	950	2094	340	49	7.2
45	195/45R16	84 XL	V	6½J	195	582	500	1102	340	49	7.2
	205/45ZR16	87 XL	W	7J	206	590	545	1201	340	49	7.2
	215/45ZR16	90 XL	W	7J	213	600	600	1323	340	49	7.2
	205/45ZR17	88 XL	W	7J	206	616	560	1235	340	49	7.2
	215/45ZR17	91 XL	W	7 J	213	626	615	1356	340	49	7.2
	225/45ZR17	94 XL	W	7½J	225	634	670	1477	340	49	7.2
	235/45ZR17	97 XL	W	8 J	236	644	730	1609	340	49	7.2
	245/45ZR17	99 XL	W	8J	243	652	775	1709	340	49	7.2

Series	size	LI	S.R	Standard Rim	Section Width(mm)	Overall Diameter(mm)	Max KG	Load LBS	Max Pressure KPA	PSI	Tread Depth(mm)
45	215/45ZR18	89	W	7J	213	651	580	1279	300	44	7.2
	225/45ZR18	95 XL	W	7½J	225	659	690	1521	340	49	7.2
	235/45ZR18	98 XL	W	8 J	236	669	750	1653	340	49	7.2
	245/45ZR18	100 XL	W	8J	243	677	800	1764	340	49	7.2
	255/45R18	99	W	8½J	255	687	775	1709	300	44	7.2
	245/45ZR20	99	W	8J	243	728	775	1709	300	44	7.2
	245/45ZR19	98	W	8J	243	703	750	1653	300	44	7.2
	255/45ZR20	101	W	8½J	255	738	825	1819	300	44	7.2
	275/45ZR20	110 XL	W	9J	273	756	1060	2337	340	49	7.2
50	195/50R16	88 XL	V	6J	201	602	560	1235	340	49	7.2
	205/50ZR16	87	W	6½J	214	612	545	1201	300	44	7.2
	215/50ZR17	95 XL	W	7J	226	648	690	1521	340	49	7.2
	225/50ZR17	94	W	7 J	233	658	670	1477	300	44	7.2
	235/50ZR17	96	W	7½J	245	668	710	1565	300	44	7.2
	205/50ZR17	93 XL	W	6 1/2 J	214	638	650	1433	340	49	7.2
	215/50R18	92	V	7J	226	673	630	1389	300	44	7.2
	225/50R18	95	V	7J	233	683	690	1521	300	44	7.2
	235/50ZR18	101 XL	W	7½J	245	693	825	1819	340	49	7.2
	245/50ZR18	100	W	7½J	253	703	800	1764	300	44	7.2
55	195/55ZR16	87	W	6J	201	620	545	1201	300	44	7.2
	205/55ZR16	91	W	6½J	214	632	615	1356	300	44	7.2
	215/55ZR16	97 XL	W	7J	226	642	730	1609	340	49	7.2
	225/55ZR16	99 XL	W	7J	233	654	775	1709	340	49	7.2
	205/55ZR17	95 XL	W	6½J	214	658	690	1521	340	49	7.2
	215/55ZR17	98 XL	W	7 J	226	668	750	1653	340	49	7.8
	225/55ZR17	101 XL	W	7 J	233	680	825	1819	340	49	7.2
	235/55ZR17	103 XL	W	7½J	245	690	875	1929	340	49	7.2
	235/55R18	104 XL	V	7½J	245	715	900	1984	340	49	7.2
	275/55R20	117 XL	V	8½J	284	810	1285	2833	340	49	7.2
60	195/60R16	89	H	6J	201	640	580	1279	300	44	7.2



MUDBREAKER MT

size	PR	LI	S.R	Standard Rim	Section Width(mm)	Overall Diameter(mm)	Max KG	Load LBS	Max Pressure KPA	PSI	Tread Depth(mm)
LT285/70R17	8PR	121/118	Q	8½J	292	832	1450	3195	450	65	14.6
LT265/70R17	10PR	121/118	Q	8J	272	804	1450	3195	550	80	14.6
LT275/70R18	10PR	125/122	Q	8J	279	843	1650	3640	550	80	14.6
LT235/75R16	10PR	117/114	Q	6½J	235	758	1285	2835	550	80	14.6
LT245/75R16	10PR	120/116	N	7J	248	774	1380	3042	550	80	14.6
LT265/75R16	10PR	123/120	N	7½J	267	804	1550	3415	550	80	14.6
LT285/75R16	8PR	122/119	Q	8J	288	834	1500	3305	450	65	14.6
LT235/85R16	10PR	120/116	N	6½J	235	806	1380	3042	550	80	14.6
31x10.50R15LT	6PR	109	Q	8½J	268	775	1030	2270	350	50	14.6
33X12.50R15LT	6PR	108	Q	10J	318	828	1000	2205	250	35	14.6
35X12.50R18LT	10PR	123	Q	10J	318	877	1550	3415	450	65	14.6
35X12.50R20LT	10PR	121	Q	10J	318	877	1450	3195	450	65	14.6
35X12.50R17LT	8PR	119	Q	10J	318	877	1360	3000	350	50	14.6

UTQG	TREADWEAR	TRACTION	TEMPERATURE
	440	A	A

ANSWER LIFESTYLE AL



Series	size	LI	S.R	Standard Rim	Section Width(mm)	Overall Diameter(mm)	Max KG	Load LBS	Max Pressure KPA	PSI	Tread Depth(mm)
45	235/45R19	95	V	8J	236	695	690	1521	300	44	7.8
	255/45R19	100	V	8½J	255	713	800	1764	300	44	7.8
	265/45R21	108 XL	V	9J	266	771	1000	2205	340	49	7.3
	265/45ZR20	104	W	9J	266	746	900	1964	300	44	7.8
	275/45ZR21	110 XL	W	9J	273	781	1060	2337	340	49	7.8
50	235/50R19	99	V	7½J	245	719	775	1709	300	44	7.8
	255/50ZR19	107 XL	W	8J	265	739	975	2149	340	49	7.8
	265/50ZR19	110 XL	W	8½J	277	749	1060	2337	340	49	7.8
	265/50R20	111 XL	V	8½J	277	774	1090	2403	340	49	7.3
	275/50ZR20	113 XL	W	8½J	284	784	1150	2535	340	44	8
	275/50R21	113 XL	V	8½J	284	809	1150	2535	340	49	7.3
	275/50R22	111	V	8½J	284	835	1090	2403	300	44	7.3
	285/50R20	112	V	9J	297	794	1120	2469	300	44	7.3
55	235/55R17	99	V	7½J	245	690	775	1709	300	44	7.8
	275/55R17	109	H	8½J	284	734	1030	2271	300	44	8
	215/55R18	95	V	7J	226	693	690	1521	300	44	7.8
	225/55R18	98	V	7J	233	705	750	1653	300	44	7.8
	235/55R18	100	V	7½J	245	715	800	1764	300	44	7.8
	255/55ZR18	109 XL	W	8J	265	737	1030	2271	340	49	7.8
	225/55R19	99	V	7J	233	731	775	1709	300	44	7.8
	235/55R19	105 XL	V	7½J	245	741	925	2039	340	49	7.8
	245/55ZR19	103	W	7½J	253	753	875	1929	300	44	7.8
	255/55R19	111 XL	V	8J	265	763	1090	2403	340	49	7.8
	275/55R19	111	W	8½J	284	785	1090	2403	300	44	8
	235/55R20	105 XL	V	7½J	245	766	925	2039	340	49	7.3
60	235/60R16	100	V	7J	240	688	800	1764	300	44	7.8
	215/60R17	96	H	6½J	221	690	710	1565	300	44	7.8
	225/60R17	99	V	6½J	228	702	775	1709	300	44	7.8
	225/60R18	100	H	6½J	228	727	800	1764	300	44	7.8
	235/60R18	107 XL	V	7J	240	739	975	2149	340	49	7.8
	245/60R18	105	V	7J	248	751	925	2039	300	44	7.8
	255/60R18	108	H	7½J	260	763	1000	2205	300	44	7.8
	265/60R18	110	H	8J	272	775	1060	2337	300	44	7.8
65	275/60R20	115	H	8J	279	838	1215	2679	300	44	7.3
	215/65R16	98	H	6½J	221	686	750	1653	300	44	7.8
	215/65R17	99	V	6½J	221	712	775	1709	300	44	7.3
	225/65R17	102	V	6½J	228	724	850	1874	300	44	7.8
	235/65R17	108 XL	V	7J	240	738	1000	2205	340	49	7.8
	245/65R17	107	H	7J	248	750	975	2149	300	44	7.8
	265/65R17	112	H	8J	272	776	1120	2469	300	44	7.8
	285/65R17	116	H	8½J	292	802	1250	2756	300	44	8
	235/65R18	106	H	7J	240	763	950	2094	300	44	7.8
	265/65R18	114	H	8J	272	801	1180	2601	300	44	7.3
70	205/70R15	96	H	6J	209	669	710	1565	300	44	7.8
	255/70R15	108	H	7½J	260	739	1000	2205	300	44	8
	225/70R16	103	H	6½J	228	722	875	1929	300	44	7.8
	235/70R16	106	H	7J	240	736	950	2094	300	44	8
	255/70R16	111	H	7½J	260	764	1090	2403	300	44	8
	255/70R18	113	H	7½J	260	815	1150	2535	300	44	7.3
265/70R18	116	T	8J	272	829	1250	2756	300	44	8	



EMPIRE TRAC ET2



size	P.R	L.I	S.R	Standard Rim	Section Width(mm)	Overall Diameter(mm)	Max KG	Load LBS	Max Pressure KPA	PSI	Tread Depth(mm)
155R13C	8PR	90/88	N	4.50B	157	578	600	1323	450	65	8
165R13C	8PR	94/93	N	4.50B	165	594	670	1475	450	65	8
175R13C	8PR	97/95	Q	5.00B	177	610	730	1609	450	65	8
165/70R13LT	6PR	88/86	T	5.00B	170	562	560	1235	375	54	8
165/70R14LT	6PR	89/87	R	5J	170	588	580	1280	375	54	8

EPOCH TRAVELER ST



size	P.R	L.I	S.R	Standard Rim	Section Width(mm)	Overall Diameter(mm)	Max KG	Load LBS	Max Pressure KPA	PSI	Tread Depth(mm)
ST205/75R14	6PR	105/101	L	5½J	203	664	925	2040	450	65	7.6
ST205/75R15	8PR	107/102	L	5½J	203	689	975	2150	450	65	7.6
ST225/75R15	8PR	117/112	L	6J	223	719	1285	2830	550	80	7.6
ST175/80R13	10PR	91/87	L	5J	177	610	615	1360	350	51	7.1
ST235/80R16	10PR	123/119	L	6½J	235	782	1550	3420	550	80	7.8

EMPIRE TRAC ET3



size	P.R	L.I	S.R	Standard Rim	Section Width(mm)	Overall Diameter(mm)	Max KG	Load LBS	Max Pressure KPA	PSI	Tread Depth(mm)
6.50R16LT	10PR	107/102	M	5.50F	185	750	975	2150	560	81	9.7
7.00R16LT	10PR	111/107	M	5.50F	200	775	1090	2405	560	81	10.7
7.50R16LT	14PR	123/121	M	6.00G	215	805	1510	3330	700	102	10.7





EMPIRE TRAC ET

size	P.R	LI	S.R	Standard Rim	Section Width(mm)	Overall Diameter(mm)	Max KG	Load LBS	Max Pressure KPA	PSI	Tread Depth(mm)
185R14C	8PR	102/100	Q	5½J	188	650	850	1874	450	65	8.4
195R14C	8PR	106/104	Q	5½J	198	666	950	2094	450	65	8.7
195R15C	8PR	106/104	Q	5½J	198	690	950	2094	450	65	8.7
195/65R16C	6PR	104/102	R	6J	201	680	900	1984	475	68	9.7
205/65R16C	8PR	107/105	R	6J	209	672	975	2149	475	68	9.7
215/65R16C	8PR	109/107	R	6½J	221	686	1030	2271	475	68	9.7
225/65R16C	8PR	112/110	R	6½J	228	698	1120	2469	475	68	9.7
235/65R16C	6PR	115/113	R	7J	240	712	1215	2679	475	68	9.7
175/70R14LT	8PR	95/93	R	5J	177	602	690	1520	375	54	8
195/70R15C	8PR	104/102	R	6J	201	655	900	1984	450	65	10.2
205/70R15C	8PR	106/104	R	6J	209	669	950	2094	450	65	10.2
225/70R15C	8PR	112/110	R	6½J	228	697	1120	2469	450	65	10.2
215/70R16LT	8PR	100/97	N	6½J	221	708	800	1765	350	50	9.7
185/75R16C	8PR	104/102	R	5J	184	684	900	1984	475	68	8.4
195/75R16C	8PR	107/105	R	5½J	196	698	975	2149	475	68	8.7
215/75R15LT	6PR	100/97	N	6J	216	703	800	1765	350	50	9.7
215/75R16C	10PR	116/114	R	6J	216	728	1250	2756	525	76	9.7

PATHBREAKER A/T

size	P.R	LI	S.R	Standard Rim	Section Width(mm)	Overall Diameter(mm)	Max KG	Load LBS	Max Pressure KPA	PSI	Tread Depth(mm)
31X10.50R15LT	6PR	109	S	8½J	268	775	1030	2270	350	50	11.5
285/60R18	-	120 XL	H	8½J	292	799	1400	3086	340	49	10.2
235/60R18	-	107 XL	H	7J	240	739	975	2149	340	49	9.5
225/65R17	-	106 XL	H	6½J	228	724	950	2094	340	49	9.5
LT245/65R17	8PR	111/108	S	7J	248	750	1090	2405	450	65	11.5
LT265/65R17	10PR	120/117	S	8J	272	776	1400	3085	550	80	11.5
LT285/65R18	10PR	125/122	S	8½J	292	827	1650	3640	550	80	12.1
235/70R16	-	106	T	7J	240	736	950	2094	300	44	10.2
LT245/70R16	10PR	118/115	S	7J	248	750	1320	2910	550	80	11.5
LT255/70R16	8PR	115/112	S	7½J	280	784	1215	2680	450	65	11.5
LT265/70R16	10PR	121/118	S	8J	272	778	1450	3195	550	80	11.5
LT285/70R17	8PR	121/118	S	8½J	292	832	1450	3195	450	65	12.1
LT215/75R15	6PR	100/97	S	6J	216	703	800	1765	350	50	11.8
LT235/75R15	10PR	116/113	S	6½J	235	733	1250	2755	550	80	11.5
LT245/75R16	10PR	120/116	S	7J	248	774	1380	3042	550	80	11.5
LT265/75R16	10PR	123/120	S	7½J	267	804	1550	3415	550	80	11.5
LT285/75R16	8PR	122/119	S	8 J	286	834	1500	3305	450	65	12.1