



 **CONSTANCY**
NEW ROADS AHEAD **Tire**

TRUCK & BUS TYRES

BànlǔTires

6.50R16LT

NEW ROADS AHEAD



896



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX. LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|------|---------------------|----------------------------|-------------------|--------------------|
| 896 | 12 | 110/105 | K | 5.50 | 10.5 | 1060/925 | 670 | All POSITION |

7.00R16LT

NEW ROADS AHEAD



896



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX. LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|-------|---------------------|----------------------------|-------------------|--------------------|
| 896 | 14 | 118/114 | K | 5.50F | 11.5 | 1320/1180 | 770 | All POSITION |

7.50R16LT

NEW ROADS AHEAD



896

899

AH23



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX. LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|-------|---------------------|----------------------------|-------------------|--------------------|
| 896 | 14 | 122/118 | L | 6.00G | 13.5 | 1500/1320 | 770 | All POSITION |
| 899 | 14 | 122/118 | L | 6.00G | 16.0 | 1500/1320 | 770 | DRIVING |
| AH23 | 16 | 125/121 | L | 6.00G | 14.0 | 1650/1450 | 870 | All POSITION |

8.25R16

NEW ROADS AHEAD



896

899



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX. LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|-------|---------------------|----------------------------|-------------------|--------------------|
| 896 | 16 | 128/124 | K | 6.50H | 13.0 | 1800/1600 | 770 | All POSITION |
| 899 | 16 | 128/124 | K | 6.50H | 16.0 | 1800/1600 | 770 | DRIVING |

8.25R20LT

NEW ROADS AHEAD



896



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX. LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|------------------|--------------|------|------------------|----------------------|----------------|--------------------|
| 896 | 16 | 139/137 | K | 6.50 | 13.0 | 2430/2300 | 930 | All POSITION |

9.00R20

NEW ROADS AHEAD



896

897

807



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX. LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|------------------|--------------|------|------------------|----------------------|----------------|--------------------|
| 896 | 16 | 144/142 | K | 7.00 | 15.5 | 2800/2650 | 900 | All POSITION |
| 897 | 16 | 144/142 | K | 7.00 | 15.5 | 2800/2650 | 900 | All POSITION |
| 807 | 16 | 144/142 | K | 7.00 | 20.0 | 2800/2650 | 900 | DRIVING |

9.5R17.5

NEW ROADS AHEAD



FC33

DM55



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX. LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|------------------|--------------|------|------------------|----------------------|----------------|--------------------|
| FC33 | 18 | 143/141 | L | 6.75 | 13.5 | 2725/2575 | 875 | DRIVING |
| DM55 | 18 | 143/141 | L | 6.75 | 15.0 | 2725/2575 | 875 | STEER&TRAILER |

10.00R20

NEW ROADS AHEAD



896

897

ASR97

868

YL919

807



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX. LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|------------------|--------------|------|------------------|----------------------|----------------|--------------------|
| 896 | 18 | 149/146 | K | 7.50 | 16.5 | 3250/3000 | 930 | All POSITION |
| 897 | 18 | 149/146 | K | 7.50 | 16.5 | 3250/3000 | 930 | All POSITION |
| ASR97 | 18 | 149/146 | K | 7.50 | 16.5 | 3250/3000 | 930 | All POSITION |
| 868 | 18 | 149/146 | K | 7.50 | 20.0 | 3250/3000 | 930 | DRIVING |
| YL919 | 18 | 149/146 | E | 7.50 | 21.5 | 3250/3000 | 930 | DRIVING |
| 807 | 18 | 149/146 | K | 7.50 | 22.5 | 3250/3000 | 930 | DRIVING |

11.00R20

NEW ROADS AHEAD



896 896+ 686 696 897 897+



899 901 868 807 809 YL919



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| 896 | 18 | 152/149 | K | 8.00 | 17.0 | 3550/3250 | 930 | All POSITION |
| 896+ | 18 | 152/149 | K | 8.00 | 17.0 | 3550/3250 | 930 | All POSITION |
| 686 | 18 | 152/149 | K | 8.00 | 16.0 | 3550/3250 | 930 | DRIVING |
| 696 | 18 | 152/149 | K | 8.00 | 15.0 | 3550/3250 | 930 | STEER&TRAILER |
| 897 | 18 | 152/149 | K | 8.00 | 17.0 | 3550/3250 | 930 | All POSITION |
| 897+ | 18 | 152/149 | K | 8.00 | 17.0 | 3550/3250 | 930 | All POSITION |
| 899 | 18 | 152/149 | K | 8.00 | 19.0 | 3550/3250 | 930 | All POSITION |
| 901 | 18 | 152/149 | K | 8.00 | 19.0 | 3550/3250 | 930 | DRIVING |
| 868 | 18 | 152/149 | K | 8.00 | 19.0 | 3550/3250 | 930 | DRIVING |
| 807 | 18 | 152/149 | K | 8.00 | 23.0 | 3550/3250 | 930 | DRIVING |
| 809 | 18 | 152/149 | E | 8.00 | 23.0 | 3550/3250 | 930 | DRIVING |
| YL919 | 18 | 152/149 | E | 8.00 | 21.5 | 3550/3250 | 930 | DRIVING |

12.00R20

NEW ROADS AHEAD



896 896+ 897 899 901 868



807 809 YL918 YL919 TK032 ZY81 DM39-JS



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| 896 | 20 | 156/153 | K | 8.50 | 17.5 | 4000/3650 | 900 | All POSITION |
| 896+ | 20 | 156/153 | K | 8.50 | 17.5 | 4000/3650 | 900 | All POSITION |
| 897 | 20 | 156/153 | K | 8.50 | 17.5 | 4000/3650 | 900 | All POSITION |
| 899 | 20 | 156/153 | K | 8.50 | 19.0 | 4000/3650 | 900 | All POSITION |
| 901 | 20 | 156/153 | K | 8.50 | 19.0 | 4000/3650 | 900 | DRIVING |
| 868 | 20 | 156/153 | K | 8.50 | 19.0 | 4000/3650 | 900 | DRIVING |
| 807 | 20 | 156/153 | K | 8.50 | 23.0 | 4000/3650 | 900 | DRIVING |
| 809 | 20 | 156/153 | E | 8.50 | 24.5 | 4000/3650 | 900 | DRIVING |
| YL918 | 20 | 156/153 | K | 8.50 | 18.0 | 4000/3650 | 900 | DRIVING |
| YL919 | 20 | 156/153 | E | 8.50 | 21.5 | 4000/3650 | 900 | DRIVING |
| TK032 | 20 | 156/153 | E | 8.50 | 26.0 | 4000/3650 | 900 | DRIVING |
| ZY81 | 20 | 156/153 | J | 8.50 | 17.0 | 4000/3650 | 900 | All POSITION |
| DM39-JS | 22 | 158/155 | F | 8.50 | 25.5 | 4250/3875 | 970 | DRIVING |

12.00R24

NEW ROADS AHEAD



896 828 982



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| 896 | 20 | 160/157 | K | 8.50 | 15.0 | 4500/4125 | 900 | All POSITION |
| 828 | 20 | 160/157 | K | 8.50 | 14.5 | 4500/4125 | 900 | All POSITION |
| 982 | 20 | 160/157 | K | 8.50 | 14.5 | 4500/4125 | 900 | STEER&TRAILER |

11R22.5

NEW ROADS AHEAD



668 698 699 903 DM775 TH58



AH96 DM55 DM59 DM357 DM373 FC33



D7 TRUEGRIP 2 TRUEGRIP 3



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|------------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| 668 | 16 | 146/143 | L | 8.25 | 20.0 | 3000/2725 | 830 | DRIVING |
| 698 | 18 | 148/145 | M | 8.25 | 15.0 | 3150/2900 | 850 | STEER&TRAILER |
| 699 | 16 | 146/143 | M | 8.25 | 16.0 | 3000/2725 | 830 | STEER&TRAILER |
| 903 | 18 | 148/145 | M | 8.25 | 18.0 | 3150/2900 | 850 | STEER&TRAILER |
| DM775 | 18 | 148/145 | K | 8.25 | 24.5 | 3150/2900 | 850 | DRIVING |
| TH58 | 18 | 148/145 | M | 8.25 | 14.5 | 3150/2900 | 850 | STEER&TRAILER |
| AH96 | 18 | 148/145 | M | 8.25 | 15.0 | 3150/2900 | 850 | All POSITION |
| DM55 | 18 | 148/145 | M | 8.25 | 21.5 | 3150/2900 | 850 | DRIVING |
| DM59 | 18 | 148/145 | M | 8.25 | 21.5 | 3150/2900 | 850 | DRIVING |
| DM357 | 18 | 148/145 | M | 8.25 | 21.5 | 3150/2900 | 850 | DRIVING |
| DM373 | 18 | 148/145 | M | 8.25 | 19.5 | 3150/2900 | 850 | DRIVING |
| FC33 | 18 | 148/145 | M | 8.25 | 13.5 | 3150/2900 | 850 | STEER&TRAILER |
| D7 | 18 | 148/145 | M | 8.25 | 19.5 | 3150/2900 | 850 | DRIVING |
| TRUEGRIP 2 | 18 | 148/145 | L | 8.25 | 23.0 | 3150/2900 | 850 | DRIVING |
| TRUEGRIP 3 | 18 | 148/145 | L | 8.25 | 23.0 | 3150/2900 | 850 | DRIVING |

12R22.5

NEW ROADS AHEAD



668 669 699 886 896 896+



DM55 DM58 FH052 FH081 FH091 TH051



TH082 TH092 TM061 YL608 YL661 YL662



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX. LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|------|---------------------|----------------------------|-------------------|--------------------|
| 668 | 18 | 152/149 | L | 9.00 | 20.0 | 3550/3250 | 930 | DRIVING |
| 669 | 18 | 152/149 | L | 9.00 | 19.0 | 3550/3250 | 930 | All POSITION |
| 699 | 18 | 152/149 | M | 9.00 | 16.5 | 3550/3250 | 930 | STEER&TRAILER |
| 886 | 18 | 152/149 | L | 9.00 | 18.0 | 3550/3250 | 930 | DRIVING |
| 896 | 18 | 152/149 | M | 9.00 | 17.0 | 3550/3250 | 930 | All POSITION |
| 896+ | 18 | 152/149 | L | 9.00 | 17.0 | 3550/3250 | 930 | All POSITION |
| DM55 | 18 | 152/149 | L | 9.00 | 22.5 | 3550/3250 | 930 | DRIVING |
| DM58 | 18 | 152/149 | J | 9.00 | 22.5 | 3550/3250 | 930 | DRIVING |
| FH052 | 18 | 152/149 | L | 9.00 | 15.0 | 3550/3250 | 930 | TRAILER |
| FH081 | 18 | 152/149 | L | 9.00 | 16.5 | 3550/3250 | 930 | All POSITION |
| FH091 | 18 | 152/149 | L | 9.00 | 17.0 | 3550/3250 | 930 | STEER&TRAILER |
| TH051 | 18 | 152/149 | L | 9.00 | 15.0 | 3550/3250 | 930 | TRAILER |
| TH082 | 18 | 152/149 | M | 9.00 | 17.0 | 3550/3250 | 930 | STEER&TRAILER |
| TH092 | 18 | 152/149 | L | 9.00 | 17.0 | 3550/3250 | 930 | All POSITION |
| TM061 | 18 | 152/149 | L | 9.00 | 17.0 | 3550/3250 | 930 | All POSITION |
| YL608 | 18 | 152/149 | L | 9.00 | 21.0 | 3550/3250 | 930 | DRIVING |
| YL661 | 18 | 152/149 | M | 9.00 | 15.0 | 3550/3250 | 930 | All POSITION |
| YL662 | 18 | 152/149 | M | 9.00 | 15.0 | 3550/3250 | 930 | STEER&TRAILER |



11R24.5

NEW ROADS AHEAD



FC33 DM373



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| FC33 | 18 | 149/146 | M | 8.25 | 13.5 | 3250/3000 | 830 | STEER&TRAILER |
| DM373 | 18 | 149/146 | M | 8.25 | 19.5 | 3250/3000 | 830 | DRIVING |

12R24.5

NEW ROADS AHEAD



ECOSMART81



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|------------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| ECOSMART81 | 18 | 154/151 | K | 9.00 | 16.5 | 3750/3450 | 930 | All POSITION |

13R22.5

NEW ROADS AHEAD



896 DM051 ECOSMART79



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|------------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| 896 | 18 | 154/151 | L | 9.75 | 17.5 | 3750/3450 | 830 | All POSITION |
| DM051 | 18 | 154/151 | K | 9.75 | 20.5 | 3750/3450 | 830 | DRIVING |
| ECOSMART79 | 18 | 156/150 | L | 9.75 | 17.5 | 4000/3350 | 875 | DRIVING |

215/75R17.5

NEW ROADS AHEAD



FC33 DH39



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| FC33 | 18 | 135/133 | L | 6.00 | 12.0 | 2180/2060 | 860 | STEER&TRAILER |
| DH39 | 18 | 135/133 | L | 6.00 | 15.5 | 2180/2060 | 860 | DRIVING |

235/75R17.5

NEW ROADS AHEAD



FC33

DH39



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| FC33 | 18 | 143/141 | L | 6.75 | 13.0 | 2725/2575 | 900 | STEER&TRAILER |
| DH39 | 18 | 143/141 | L | 6.75 | 16.0 | 2725/2575 | 900 | DRIVING |

275/70R22.5

NEW ROADS AHEAD



FC33



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| FC33 | 18 | 146/143 | L | 8.25 | 14.0 | 3000/2725 | 900 | STEER&TRAILER |

275/80R22.5

NEW ROADS AHEAD



FC33



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| FC33 | 18 | 149/146 | L | 8.25 | 14.0 | 3250/3000 | 900 | STEER&TRAILER |

295/80R22.5

NEW ROADS AHEAD



668

698

FC33

DM36



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|---------------------|--------------|------|---------------------|---------------------------|-------------------|--------------------|
| 668 | 18 | 152/149 | L | 9.00 | 20.0 | 3550/3250 | 900 | DRIVING |
| 698 | 18 | 152/149 | M | 9.00 | 15.0 | 3550/3250 | 900 | STEER&TRAILER |
| FC33 | 18 | 152/149 | M | 9.00 | 16.0 | 3550/3250 | 900 | STEER&TRAILER |
| DM36 | 18 | 152/149 | L | 9.00 | 20.0 | 3550/3250 | 900 | DRIVING |

295/60R22.5

NEW ROADS AHEAD



TH082



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|---------|----|------------------|--------------|------|------------------|---------------------|----------------|--------------------|
| TH082 | 18 | 150/147 | K | 9.00 | 15.5 | 3350/3075 | 900 | STEER&TRAILER |

315/70R22.5

NEW ROADS AHEAD



ECOSMART62

ECOSMART78



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|------------|----|------------------|--------------|------|------------------|---------------------|----------------|--------------------|
| ECOSMART62 | 18 | 152/148 | M | 9.00 | 15.0 | 3550/3150 | 830 | STEER&TRAILER |
| ECOSMART78 | 18 | 152/148 | M | 9.00 | 20.0 | 3550/3150 | 830 | DRIVING |

315/80R22.5

NEW ROADS AHEAD



668

698

828

866

886

896



DM59

SH57

SH55

TRUEGRIP 3

ECOSMART73



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|------------|----|------------------|--------------|------|------------------|---------------------|----------------|--------------------|
| 668 | 20 | 156/150 | L | 9.00 | 20.0 | 4000/3350 | 850 | DRIVING |
| 698 | 20 | 156/150 | M | 9.00 | 15.0 | 4000/3350 | 850 | STEER&TRAILER |
| 828 | 20 | 156/150 | M | 9.00 | 15.0 | 4000/3350 | 850 | All POSITION |
| 866 | 20 | 156/150 | M | 9.00 | 15.0 | 4000/3350 | 850 | STEER&TRAILER |
| 886 | 20 | 156/150 | L | 9.00 | 20.0 | 4000/3350 | 850 | DRIVING |
| 896 | 20 | 156/150 | M | 9.00 | 16.0 | 4000/3350 | 850 | All POSITION |
| DM59 | 20 | 156/150 | L | 9.00 | 24.5 | 4000/3350 | 850 | DRIVING |
| SH57 | 20 | 156/150 | L | 9.00 | 16.5 | 4000/3350 | 850 | STEER&TRAILER |
| SH55 | 20 | 156/150 | M | 9.00 | 15.0 | 4000/3350 | 850 | STEER&TRAILER |
| TRUEGRIP 3 | 22 | 158/156 | K | 9.00 | 22.0 | 4250/4000 | 900 | DRIVING |
| ECOSMART73 | 22 | 158/156 | J | 9.00 | 22.0 | 4250/4000 | 900 | DRIVING |

385/55R22.5

NEW ROADS AHEAD



ECOSMART66



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|------------|----|------------------|--------------|-------|------------------|---------------------|----------------|--------------------|
| ECOSMART66 | 20 | 160 | K | 12.25 | 14.5 | 4500 | 900 | STEER&TRAILER |

385/65R22.5

NEW ROADS AHEAD



688 AH367 AH398 ECOSMART77



TECHNICAL DATA

| PATTERN | PR | LOAD INDEX S D | SPEED RATING | RIM | TREAD DEPTH (mm) | MAX.LOAD (Kg) S D | PRESSURE (kPa) | RECOMMEND POSITION |
|------------|----|------------------|--------------|-------|------------------|---------------------|----------------|--------------------|
| 688 | 24 | 164 | K | 11.75 | 14.5 | 5000 | 900 | TRAILER |
| AH367 | 24 | 164 | K | 11.75 | 15.0 | 5000 | 900 | TRAILER |
| AH398 | 24 | 164 | K | 11.75 | 14.5 | 5000 | 900 | STEER&TRAILER |
| ECOSMART77 | 24 | 164 | K | 11.75 | 15.0 | 5000 | 900 | DRIVING |

